


Latest Products from...

Surface Mount Fuses




See page 321

Automotive Fuses



See page 343

PTC Resettable Fuses



See page 347

HRC Fuses & Fuseholders



See page 353

Contents

Page

10x35mm Fuses	351
10x38mm Fuses	351
14x51mm Fuses	352
22x58mm Fuses	352
4.7x15.9mm Fuses & Fuseholders	337
5x20mm Fuses	324
5x20mm Fuseholders	328
5x25mm Fuses	337
6.35x25.4mm Fuses & Fuseholders	336
6.3x32mm Fuses & Fuseholders	333
8x31mm Fuses	350
Automotive Fuses	342
Bottle Fuses & Fuseholders	355
Consumer Units & Distribution Boards	364
DIN Standard Fuses & Fuseholders	355
Fuse Kits	338
Fuse Links	355
Industrial HRC Fuses & Fuseholders	353
MCB's and Accessories	361
Resettable Fuses	345
Surface Mount Fuses	321
Thermal Fuses & Circuit Breakers	356
Thermal Fuses	356
Wire Ended Fuses	338



i-Buy is the new online purchasing system, FREE from Farnell

Completely flexible and personalised to your company's needs, i-Buy provides many of the custom features of an expensive eProcurement system but at no cost to your company!

- ▶ Fully automated approval process for reduced paperwork
- ▶ Set individual users' spend and department budgets for complete cost control
- ▶ Download reports at line level detail for total transparency of your company's spend
- ▶ Fully integrated into the Farnell website, it's easy to use and easy to set up

Intelligent buying, free from Farnell
www.farnell.com/i-Buy

Turn to page iv for more information

Fuse Characteristics

Each fuselink is categorised according to its blowing characteristic.

(FF) - Super Quick Acting (Ultra Rapid). These fuselinks have very low fusing factors and are designed to blow under low current overloads.

(F) - Quick Acting (Quick Blow). For use when a fast blowing time is required under relatively low overloads and when a long and reliable usage is required under full rated conditions.

(M) - Medium Time Lag (Semi-Delay). Fairly rapid blowing under moderate current overloads, combined with some tolerance of moderate transient current surges.

(T) - Time Lag (Antisurge). Capable of withstanding short duration transient currents of considerable magnitude, whilst blowing rapidly under sustained overload conditions.

Breaking Capacity (Interrupting Rating)

This is the maximum short circuit current that the fuselink can safely interrupt under prescribed conditions, usually at rated voltage.

HRC (High Rupture Capacity). Designed with a high current breaking, or rupture, capacity. Usually manufactured with ceramic fuse bodies.

Fuse Sizes

1¼" x ¼" Fuses are normally used in North American markets, and are generally manufactured to UL and CSA standards.


20 x 5mm Fuses are normally used in European markets and are usually manufactured to IEC 127.

Apart from the physical size differences, the current / time characteristics of these fuses are different, and are therefore not interchangeable.

213844

Surface Mount Fuses

Fast Acting SMD Thin Film



This series of fuses is based on thin-film techniques. This technology provides a level of control on the component electrical and physical characteristics that is generally not possible with standard fuse technologies. This enables this series of devices to be designed into small consumer equipment such as mobile phones, PDA's, LCD screens and video cameras.


- Accurate current rating
- Small, standard chip sizes
- Compatible with all SMT soldering systems
- UL Recognised

Height - mm (Nominal)	Width - mm (Nominal)	Depth - mm (Nominal)	Case Style
0.4	1	0.55	0402E
0.63	1.6	0.81	0603E
0.9	2.1	1.27	0805B
1.2	3.1	1.6	1206B

460642

Order Multiple=10		Price Each				
Rating	Mfrs. List No.	Order Code	10+	50+	100+	250+ 500+
Case Style 0402E						
0.25A	MCF0402E0R25FSTR	SMD-133-7395	0.360	0.350	0.340	0.310 0.250
0.5A	MCF0402E0R50FSTR	SMD-133-7396	0.220	0.220	0.210	0.196 0.154
0.75A	MCF0402E0R75FSTR	SMD-133-7399	0.220	0.220	0.210	0.196 0.154
1A	MCF0402E1R00FSTR	SMD-133-7400	0.360	0.350	0.340	0.310 0.250
1.5A	MCF0402E1R50FSTR	SMD-133-7402	0.360	0.350	0.340	0.310 0.250
2A	MCF0402E2R00FSTR	SMD-133-7404	0.360	0.350	0.340	0.310 0.250
Case Style 0603E						
0.25A	MCF0603E0R25FSTR	SMD-133-7405	0.360	0.290	0.250	0.220 0.210
0.5A	MCF0603E0R50FSTR	SMD-133-7406	0.360	0.290	0.250	0.220 0.210
0.75A	MCF0603E0R75FSTR	SMD-133-7407	0.360	0.290	0.250	0.220 0.210
1A	MCF0603E1R00FSTR	SMD-133-7408	0.360	0.290	0.250	0.220 0.210
1.25A	MCF0603E1R25FSTR	SMD-133-7409	0.360	0.290	0.250	0.220 0.210
1.5A	MCF0603E1R50FSTR	SMD-133-7410	0.360	0.290	0.250	0.220 0.210
2A	MCF0603E2R00FSTR	SMD-133-7411	0.360	0.290	0.250	0.220 0.210
Case Style 0805B						
0.25A	MCF0805B0R25FSTR	SMD-133-7414	0.420	0.340	0.300	0.280 0.240
0.5A	MCF0805B0R50FSTR	SMD-133-7416	0.420	0.340	0.300	0.280 0.240
0.75A	MCF0805B0R75FSTR	SMD-133-7417	0.300	0.240	0.220	0.200 0.168
1A	MCF0805B1R00FSTR	SMD-133-7418	0.420	0.340	0.300	0.280 0.240
1.25A	MCF0805B1R25FSTR	SMD-133-7419	0.420	0.340	0.300	0.280 0.240
1.5A	MCF0805B1R50FSTR	SMD-133-7420	0.420	0.340	0.300	0.280 0.240
2A	MCF0805B2R00FSTR	SMD-133-7421	0.420	0.340	0.300	0.280 0.240
2.5A	MCF0805B2R50FSTR	SMD-133-7422	0.420	0.340	0.300	0.280 0.240
3A	MCF0805B3R00FSTR	SMD-133-7423	0.420	0.340	0.300	0.280 0.240
Case Style 1206B						
0.2A	MCF1206B0R20FSTR	SMD-133-7424	0.360	0.290	0.250	0.220 0.210
0.5A	MCF1206B0R50FSTR	SMD-133-7425	0.360	0.290	0.250	0.220 0.210
1A	MCF1206B1R00FSTR	SMD-133-7426	0.360	0.290	0.250	0.220 0.210
1.5A	MCF1206B1R50FSTR	SMD-133-7428	0.360	0.290	0.250	0.220 0.210
2A	MCF1206B2R00FSTR	SMD-133-7429	0.360	0.290	0.250	0.220 0.210
3A	MCF1206B3R00FSTR	SMD-133-7431	0.360	0.290	0.250	0.220 0.210

Fast Acting - 1608FF 0603 Case Size



- Thick and thin metal film technologies giving superior fusing and enhanced reliability
- UL Recognised and CSA approved

Voltage rating 24V dc
Time/current characteristics 100% rated current for 4 hours min.
250% rated current for 5 seconds


Breaking capacity 35A dc

Current Rating (A)	Colour Code	TYP. Resistance @ 10% rated current (Ω)	Typ voltage Drop @ Rated Current (V)	Mfrs. List No.	Order Code
250mA	Green	3	0.9	0603FA250-R	112-3012
500mA	Blue	0.9	0.54	0603FA500-R	112-3019
750mA	Blue / White	0.51	0.45	0603FA750-R	112-3020
1A	Brown	0.15	0.18	0603FA1-R	112-3010
1.5A	Brown/white	0.068	0.12	0603FA1.5-R	112-3009
2A	Black	0.042	0.11	0603FA2-R	112-3013
2.5A	Black/white	0.029	0.09	0603FA2.5-R	112-3011
3A	Violet	0.022	0.087	0603FA3-R	112-3017
3.5A	Violet/white	0.018	0.08	0603FA3.5-R	112-3015
4A	Yellow	0.014	0.08	0603FA4-R	112-3018
5A		0.011	0.090	0603FA5-R	161-5138

204519

Order Multiple=10		Price Each				
Rating	Order Code	10+	50+	100+	250+	500+ 3K+
250mA	112-3012	0.520	0.370	0.320	0.300	0.290 0.270
500mA	112-3019	0.490	0.360	0.300	0.290	0.270 0.260
750mA	112-3020	0.400	0.290	0.240	0.230	0.220 0.210
1A	112-3010	0.560	0.400	0.340	0.320	0.310 0.300
1.5A	112-3009	0.400	0.290	0.240	0.230	0.220 0.210
2A	112-3013	0.560	0.400	0.340	0.320	0.310 0.300
2.5A	112-3011	0.400	0.290	0.240	0.230	0.220 0.210
3A	112-3017	0.330	0.290	0.260	0.250	0.240 0.220
3.5A	112-3015	0.270	0.192	0.168	0.161	0.153 0.143
4A	112-3018	0.290	0.210	0.176	0.168	0.160 0.150
5A	161-5138	0.410	0.300	0.250	0.240	0.230 0.220

Super Quick Acting USF 1206 - 32V ac, 63V dc



- Lead Free
- High breaking capacity
- Small loss, low voltage drop - 100mV typical
- UL Recognised

H = 0.6, W = 3.2, D = 1.6mm

Breaking capacity 50A @ 32V ac/dc
Materials: Terminals - Copper, tin plated


Operating temperature -55 to 90°C
Housing - Glass epoxy

Mfrs. List No.	Order Code	Mfrs. List No.	Order Code
3413.0113.22	778-5712	3413.0119.22	778-5763
3413.0114.22	778-5720	3413.0120.22	778-5771
3413.0115.22	778-5739	3413.0121.22	778-5780
3413.0116.22	778-5747	3413.0123.22	778-5798
3413.0117.22	778-5755		

347695

Order Multiple=10		Price Each				
Rating	Order Code	10+	25+	50+	100+	500+
500mA	SMD-778-5712	0.68	0.61	0.57	0.52	0.43
750mA	SMD-778-5720	0.68	0.61	0.57	0.52	0.43
1A	SMD-778-5739	0.68	0.61	0.57	0.52	0.43
1.25A	SMD-778-5747	0.68	0.61	0.57	0.52	0.43
1.5A	SMD-778-5755	0.68	0.61	0.57	0.52	0.43
2A	SMD-778-5763	0.68	0.61	0.57	0.52	0.43
2.5A	SMD-778-5771	0.68	0.61	0.57	0.52	0.43
3A	SMD-778-5780	0.68	0.61	0.57	0.52	0.43

Fast Acting - 3216FF 1206 Case Size



- Metal film and ultrasonic wire bond technologies for high reliability fusing
- Fuse element encapsulated with glass
- UL Recognised and CSA approved

Voltage rating 32V ac/63V dc
Time/current characteristics 100% rated current for 4 hours min.
250% rated current for 5 seconds Max
4A and 5A fuses open within 1s @ 350% rated current

Breaking capacity 50A ac/dc



Surface Mount Fuses - continued

Fast Acting - 3216FF - continued

1206 Case Size - continued

Rating (A)	Device Marking	TYP. Resistance @ 10% rated current (Ω)	Typ voltage Drop @ Rated Current (V)	Mfrs. List No.	Order Code
250mA	.25	4.5	1.4	3216FF250-R	112-3250
375mA	White dot	1.8	0.73	3216FF375-R	112-3251
500mA	.5	1.15	0.66	3216FF500-R	112-3252
750mA	.75	0.75	0.63	3216FF750-R	112-3253
1A	1	0.168	0.2	3216FF1-R	112-3254
1.5A	1.5	0.098	0.18	3216FF1.5-R	112-3255
2A	2	0.063	0.16	3216FF2-R	112-3256
2.5A	2.5	0.046	0.14	3216FF2.5-R	112-3258
3A	3	0.037	0.13	3216FF3-R	112-3259
4A	4	0.019	0.11	3216FF4-R	112-3260
5A	5	0.013	0.09	3216FF5-R	112-3262
6.5A		0.0082	0.076	3216FF-6-5-R	161-5139
7A		0.0078	0.078	3216FF-7-R	161-5140

204520

Order Multiple=10	Order Code	10+	50+	100+	250+	500+	1K+
250mA	112-3250● RL	0.390	0.360	0.330	0.300	0.270	0.240
375mA	112-3251● RL	0.320	0.260	0.220	0.200	0.195	0.185
500mA	112-3252● RL	0.370	0.340	0.320	0.290	0.260	0.230
750mA	112-3253● RL	0.330	0.260	0.220	0.200	0.198	0.188
1A	112-3254● RL	0.420	0.390	0.360	0.320	0.290	0.260
1.5A	112-3255● RL	0.340	0.310	0.280	0.260	0.250	0.240
2A	112-3256● RL	0.350	0.300	0.280	0.260	0.250	0.230
2.5A	112-3258● RL	0.250	0.210	0.198	0.188	0.177	0.166
3A	112-3259● RL	0.350	0.300	0.280	0.260	0.250	0.230
4A	112-3260● RL	0.250	0.210	0.198	0.188	0.177	0.166
5A	112-3262● RL	0.250	0.210	0.198	0.188	0.177	0.166
6.5A	SMD161-5139● NEW	0.280	0.240	0.220	0.210	0.197	0.185
7A	SMD161-5140● NEW	0.280	0.240	0.220	0.210	0.197	0.185

Very Fast Acting (FF)

1206 - Type MGA



- "Flip Chip" design mounts on any side
- Hermetically sealed for operating temperatures in excess of 150°C
- Low energy let-through
- CSA Approved, UL Recognised


Breaking capacity 50A @ 125V dc
 Interrupt capacity 50A
 Operating Temperature (max.) 150°C
 H = 1.52, W = 3.05, D = 1.52mm
 Pad = 0.25 x 1.52mm

429007

Order Multiple = 10	Mfrs. List No.	Rating	Order Code	10+	50+	100+	250+
	3410002101	200mA	SMD116-2746● RL	1.22	0.93	0.65	0.56
	3410002701	500mA	SMD116-2747● RL	1.27	0.92	0.69	0.57

Very Fast Acting

Slimline 1206 Package - 466 Series



- Extremely small with low profile (1206 chip size)
- Utilizes thin film technology for precise electrical characteristics
- UL recognised and CSA approved

Breaking Capacity - 125 mA to 375 mA
 Breaking Capacity - 500 mA to 2 A
 Breaking Capacity - 2.5 A to 5 A
 Operating temperature -55 to 90°C

50 A @ 125V ac/dc
 50 A @ 63V ac/dc
 50 A @ 32V ac/dc
 -55 to 90°C

Mfrs. List No. = 466 + Rating

233676

Order Multiple=10	Order Code	10+	100+	250+	500+	1K+
250mA	SMD992-1826● RL	0.44	0.40	0.35	0.32	0.30
500mA	SMD992-1834● RL	0.44	0.40	0.35	0.32	0.30
1A	SMD992-1850● RL	0.44	0.40	0.35	0.32	0.30
2A	SMD992-1877● RL	0.44	0.40	0.35	0.32	0.30

Slow Blow

Slimline 1206 Package - 468 Series



- Time delay withstands high inrush currents preventing nuisance openings
- Package is visually distinct from fast acting version
- Top side marking of amperage value
- UL recognised and CSA approved

H = 0.58, W = 3.18, D = 1.52mm

Breaking Capacity - 500 mA to 1.5 A
 Breaking Capacity - 2 A to 2.5 A
 Breaking Capacity - 3 A
 Operating temperature

50 A @ 63V ac/dc
 35 A @ 63V ac, 50 A @ 63V dc
 50 A @ 32V ac/dc
 -55 to 90°C

Mfrs. List No. = 468 + Rating

233675

Order Multiple=10	Order Code	10+	100+	250+	500+	1K+
1A	SMD992-1788● RL	1.29	1.07	0.96	0.86	0.68
1.5A	SMD992-1796● RL	1.29	1.07	0.96	0.86	0.68
2A	SMD992-1800● RL	1.29	1.07	0.96	0.86	0.68

Very Fast Acting - 451 series

Nanofuse - 125V ac/dc



- Compact high speed ceramic chip fuses.
- Wide range of current rating available
- Wide temperature operating range
- Low temperature de-rating
- UL Recognised and CSA approved.

H = 2.69, W = 6.10, D = 2.69mm
 Supplied on 12mm embossed tape (reel=1K pcs)

Breaking capacity 100A @ 125V ac, 300A @ 125V dc
 Mfrs. List No. 451 + Value
 Operating temperature -55°C to +125°C

204438

Order Multiple=10	Order Code	10+	100+	250+	500+	1K+
62mA	SMD992-2121● RL	1.04	0.92	0.83	0.79	0.76
125mA	SMD992-2130● RL	1.04	0.92	0.83	0.79	0.76
250mA	SMD992-2140● RL	0.34	0.33	0.32	0.31	0.30
500mA	SMD992-2156● RL	0.34	0.33	0.32	0.31	0.30
1A	SMD992-2164● RL	0.34	0.33	0.32	0.31	0.30
2A	SMD992-2172● RL	0.34	0.33	0.32	0.31	0.30
3A	SMD992-2180● RL	0.34	0.33	0.32	0.31	0.30
5A	SMD992-2190● RL	0.34	0.33	0.32	0.31	0.30
10A	SMD992-2202● RL	0.34	0.33	0.32	0.31	0.30

Slow Blow

Nanofuse - 125Vac/dc



L=6.10
 B=2.54
 H=2.54

Meets IEC 60127-4 standard for Universal Modular Fuse-links, UMF 125V.


Breaking Capacity 50A @ 125V ac or dc
 Mfrs. List No. Operating Temperature -55°C to 125°C
 = 452 + Rating

204461

Order Multiple=10	Order Code	10+	100+	250+	500+
375mA	SMD992-2318● RL	0.44	0.40	0.36	0.34
500mA	SMD992-2326● RL	0.44	0.40	0.36	0.34
750mA	SMD992-2334● RL	0.44	0.40	0.36	0.34
1A	SMD992-2342● RL	0.44	0.40	0.36	0.34
1.5A	SMD992-2350● RL	0.44	0.40	0.36	0.34
2A	SMD992-2369● RL	0.44	0.40	0.36	0.34
2.5A	SMD992-2377● RL	0.44	0.40	0.36	0.34
3A	SMD992-2385● RL	0.44	0.40	0.36	0.34
3.5A	SMD992-2393● RL	0.44	0.40	0.36	0.34
4A	SMD992-2407● RL	0.44	0.40	0.36	0.34
5A	SMD992-2415● RL	0.44	0.40	0.36	0.34

Fuse and Fuseholder Combinations

Nanofuse - 125V ac/dc & Omni Block



700 products added online every week



See our pick of the hottest products and latest technologies in 'What's New?' at www.farnell.co.uk


The Omni Block fuseholder permits quick and easy replacement of nanofuses. The fuse holder is pre-installed with a nanofuse and can be placed on the PCB in one operation. The surface mount fuse can then be replaced without the normal problems of SMD rework. The supplied fuse has silver plated contacts to prevent it soldering into the holder when reflow soldered. **UL** Recognised and **CSA** approved.

Fuse holder rated at 7A Voltage rating 125V ac/dc
Fuse holder thermoplastic to UL94V-0 Operating temperature -55°C to +125°C
Mfrs. List No. 154 + Rating. Add suffix H for strip of 100 & T for antisurge

FUS264/220502

Order Multiple=10					
Fuse Fitted	Order Code	10+	50+	100+	500+
Quick Blow (F)					
62mA	994-3595●	2.02	1.87	1.67	1.51
125mA	994-3609●	2.02	1.87	1.67	1.51
250mA	994-3617●	1.32	1.21	1.09	1.00
500mA	994-3625●	1.32	1.21	1.09	1.00
1A	994-3633●	1.32	1.21	1.09	1.00
2A	994-3641●	1.32	1.21	1.09	1.00
3A	994-3650●	1.30	1.19	1.08	0.99
5A	994-3668●	1.32	1.21	1.09	1.00
Antisurge (T)					
375mA	994-3676●	1.33	1.24	1.10	1.00
500mA	994-3684●	1.35	1.25	1.11	1.01
750mA	994-3692●	1.35	1.25	1.11	1.01
1A	994-3706●	1.35	1.25	1.11	1.01
1.5A	994-3714●	1.35	1.25	1.11	1.01
2A	994-3722●	1.35	1.25	1.11	1.01
2.5A	994-3730●	1.33	1.24	1.10	1.00
3A	994-3749●	1.35	1.25	1.11	1.01
3.5A	994-3757●	1.35	1.25	1.11	1.01
4A	994-3765●	1.33	1.24	1.10	1.00
5A	994-3773●	1.35	1.25	1.11	1.01

Telecom Nanofuse - 250V 461 Series



Meets **UL 1950** third edition (formerly UL 1459) power cross requirements. Designed to allow compliance with Bellcore/Telcordia GR 1089-CORE and FCC 47 part 68 Surge Specifications.

Interrupting Ratings 60A @ 600 Vac
Operating temperature -55°C to +125°C
Electrical Characteristics 100% Amp rating - 4 Hours min.
250% Amp rating - 1 sec min, 120 sec max.

Current Rating A	Resistance Cold. Ohms	Mfrs. List No.	Order Code
0.5	0.56	461.500RA000	994-3358
1.25	0.11	461.125RA000	994-3366
2	0.05	461002.RA000	994-3374

233673

Order Code	10+	100+	250+	500+	1K+
SMD-994-3358● RL	1.35	1.26	1.13	1.02	0.96
SMD-994-3366● RL	1.35	1.26	1.13	1.02	0.96
SMD-994-3374● RL	1.33	1.25	1.12	1.01	0.95

Fast Acting - 456 Series Nano2 fuse - 125V ac



- Surface mount high current fuses
- **UL** Recognised

H = 3.12, W = 10.1, D = 3.12mm

Breaking capacity 100A @ 125V ac, 300A @ 65V ac Operating temperature -55 to 125°C

492594

Order Multiple=10		Price Each				
Rating Mfrs. List No.	Order Code	10+	100+	250+	500+	1K+
20A 0456020.ER	 SMD-151-0910	0.73	0.69	0.64	0.60	0.54
30A 0456030.ER	SMD-151-0911	0.73	0.69	0.64	0.60	0.54

Type TF 600 Time-lag Telcordia GR - 1089



- Directly solderable onto PCB's
- Protects against fault conditions up to 60 Amps
- Non-resettable
- **UL** Recognised

H = 3.22, W = 3.22, D = 10.1mm

Standards: IEC 60127-4, UL 248 - 14, CSA C22.2 no. 248.14, Telcordia GR - 1089, UL 60950/IEC 60950, ITU - T K.20 and K.21 & TIA - 689 - A.

Voltage rating (Vn) 600V Material, case Ceramic - UL94V-1
Breaking capacity 60A Ambient temperature -55°C to 125°C

Mfrs. List No.	Order Code	Mfrs. List No.	Order Code
2000.0010	122-1081	2000.0012	122-1083
2000.0011	122-1082		

439793

Order Multiple=10					
Rating	Order Code	10+	50+	100+	250+
0.5A	SMD-122-1081●	0.64	0.55	0.44	0.33
1.25A	SMD-122-1082●	0.64	0.55	0.44	0.33
2A	SMD-122-1083●	0.64	0.55	0.44	0.33

Type UMT 250 Time-lag IEC 60127 - 4



- Directly solderable onto PCB's
- Protects against fault conditions up to 200 Amps
- Non-resettable
- **VDE** Approved, **UL** Recognised

H = 3, W = 3, D = 10.1mm

Standards: IEC 60127 - 4, UL 248 - 14 & CSA C22.2 no. 248.14

Voltage rating (Vn) 250V, 125V Material Case Ceramic - UL 94V - 1
Breaking capacity 200A Ambient temperature -55°C to 125°C

439794

Order Multiple=10					
Rating Mfrs. List No.	Order Code	10+	50+	100+	250+
0.08A 3403.0155	NEW SMD-163-7548●	0.84	0.76	0.64	0.48
0.1A 3403.0156	NEW SMD-163-7549●	0.84	0.76	0.64	0.48
0.125A 3403.0157	NEW SMD-163-7550●	0.84	0.76	0.64	0.48
0.16A 3403.0158	NEW SMD-163-7552●	0.84	0.76	0.64	0.48
0.2A 3403.0159	NEW SMD-163-7553●	0.84	0.76	0.64	0.48
0.25A 3403.016	NEW SMD-163-7554●	0.84	0.76	0.64	0.48
0.315A 3403.0161	SMD-122-1084●	0.45	0.40	0.34	0.26
0.5A 3403.0163	SMD-122-1087●	0.86	0.78	0.65	0.49
0.8A 3403.0165	SMD-122-1089●	0.45	0.40	0.34	0.26
1A 3403.0166	SMD-122-1090●	0.86	0.78	0.65	0.49
1.25A 3403.0167	SMD-122-1091●	0.45	0.40	0.34	0.26
1.6A 3403.0168	SMD-122-1092●	0.45	0.40	0.34	0.26
2A 3403.0169	SMD-122-1093●	0.45	0.40	0.34	0.26
3.15A 3403.0171	SMD-122-1095●	0.45	0.40	0.34	0.26
4A 3403.0172	SMD-122-1096●	0.86	0.78	0.65	0.49
5A 3403.0173	NEW SMD-151-0871●	0.84	0.76	0.64	0.48
6.3A 3403.0174	NEW SMD-151-0872●	0.84	0.76	0.64	0.48
8A 3403.0175	NEW SMD-163-7555●	0.84	0.76	0.64	0.48
10A 3403.0176	NEW SMD-163-7556●	0.84	0.76	0.64	0.48

Type OMT 125 Time-lag



- Directly solderable on printed circuit boards or plugable into surface mount fuseholder
- Protects against fault conditions up to 100 Amps
- Non-resettable
- **UL** Recognised
- Lead-free

H = 2.6, W = 7.4,
D = 3.1mm

Voltage rating (Vn) 125 V Ambient temperature -40°C to 85°C
Breaking capacity 100A / 125V AC/DC

Mfrs. List No.	Order Code	Mfrs. List No.	Order Code
3404.0112.11	444-7918	3404.0117.11	444-7967
3404.0113.11	444-7920	3404.0118.11	444-7979
3404.0114.11	444-7931		
3404.0115.11	444-7943	3404.0120.11	444-7992
3404.0116.11	444-7955	3404.0121.11	444-8005

311843

Order Multiple=10					
Rating	Order Code	10+	50+	100+	250+
500mA	SMD-444-7918●	0.39	0.36	0.33	0.30
750mA	SMD-444-7920●	0.37	0.34	0.32	0.29
1A	SMD-444-7931●	0.39	0.36	0.33	0.30
1.5A	SMD-444-7943●	0.37	0.34	0.32	0.29
2A	SMD-444-7955●	0.36	0.33	0.31	0.28
2.5A	SMD-444-7967●	0.39	0.36	0.33	0.30
3A	SMD-444-7979●	0.37	0.34	0.32	0.29
4A	SMD-444-7992●	0.39	0.36	0.33	0.30
5A	SMD-444-8005●	0.39	0.36	0.33	0.30

Quick Acting (F)



Surface Mount - Type 172876



- Directly solderable onto Printed Circuit Boards
- **CSA** Approved, **UL** Recognised

L = 7, Dia. = 2mm

Pad = 3.1 x 4mm (times 2, gap = 2.7mm)

Breaking capacity 300A @ 125V/V dc Operating temperature -55 to 85°C

429018

Order Multiple = 10			Price Each			
Mfrs. List No.	Rating	Order Code	10+	50+	100+	250+
7010.9760.63	125mA	 SMD-116-2765	1.85	0.66	0.41	0.29
7010.9790.63	500mA	 SMD-116-2766	0.61	0.45	0.34	0.29
7010.9810.63	1A	 SMD-116-2768	0.48	0.36	0.31	0.27
7010.9850.63	3A	 SMD-116-2770	0.55	0.41	0.32	0.29

Over 480,000 products online



Surface Mount Fuses - continued

Type FST 5 X 20 Time-lag



- Directly solderable onto printed circuit boards
- Withstands reflow and wave soldering temperatures to 260°C / 10s

- Low breaking capacity L
- Glass tube
- Non-resettable

Voltage rating (Vn) 250 V
 Breaking capacity 35A / 250V ac
 Ambient temperature -40°C to 125°C

Mfrs. List No.	Order Code	Mfrs. List No.	Order Code
0034.5611.11	444-8029	0034.5619.11	444-8108
0034.5612.11	444-8030	0034.5620.11	444-8110
		0034.5621.11	444-8121
		0034.5622.11	444-8133
0034.5614.11	444-8054	0034.5623.11	444-8145
0034.5615.11	444-8066	0034.5624.11	444-8157
0034.5616.11	444-8078	0034.5625.11	444-8169
0034.5617.11	444-8080	0034.5626.11	444-8170
0034.5618.11	444-8091	0034.5627.11	444-8182

311847

Order Multiple=10	Order Code	10+	100+	500+	1K+
0.315A	SMD 444-8030	0.30	0.26	0.24	0.20
0.5A	SMD 444-8054	0.31	0.27	0.25	0.22
0.8A	SMD 444-8078	0.30	0.26	0.24	0.20
1A	SMD 444-8080	0.31	0.27	0.25	0.22
1.25A	SMD 444-8091	0.31	0.27	0.25	0.22
1.6A	SMD 444-8108	0.30	0.26	0.24	0.20
2A	SMD 444-8110	0.31	0.27	0.25	0.22
2.5A	SMD 444-8121	0.30	0.26	0.24	0.20
3.15A	SMD 444-8133	0.31	0.27	0.25	0.22
4A	SMD 444-8145	0.31	0.27	0.25	0.22
5A	SMD 444-8157	0.31	0.27	0.25	0.22
6.3A	SMD 444-8169	0.31	0.27	0.25	0.22
8A	SMD 444-8170	0.30	0.26	0.24	0.20
10A	SMD 444-8182	0.31	0.27	0.25	0.22

Type SPT 5 X 20 Time-lag



- Directly solderable on printed circuit boards
- Withstands reflow and wave soldering temperatures to 260°C / 10s

- High breaking capacity H
- Non-resettable
- Ceramic tube

Voltage rating (Vn) 250V
 Breaking capacity IEC: 1500A / 250V ac
 UL: 10000A / 250V
 Ambient temperature -40°C to 125°C

Mfrs. List No.	Order Code	Mfrs. List No.	Order Code
0001.2704.11	444-8327	0001.2710.11	444-8388
		0001.2711.11	444-8390
		0001.2712.11	444-8406
0001.2706.11	444-8340		
0001.2707.11	444-8352		
0001.2708.11	444-8364	0001.2714.11	444-8420
0001.2709.11	444-8376		

311849

Order Multiple=10	Order Code	10+	100+	500+	1K+
1A	SMD 444-8327	0.30	0.26	0.24	0.20
1.6A	SMD 444-8340	0.31	0.27	0.25	0.22
2A	SMD 444-8352	0.31	0.27	0.25	0.22
3.15A	SMD 444-8376	0.31	0.27	0.25	0.22
4A	SMD 444-8388	0.31	0.27	0.25	0.22
5A	SMD 444-8390	0.31	0.27	0.25	0.22
6.3A	SMD 444-8406	0.31	0.27	0.25	0.22
10A	SMD 444-8420	0.31	0.27	0.25	0.22

20 x 5mm Fuses

Ultra Rapid (FF) Ceramic

70-001-40 Series



Ceramic sand filled fuses with very short cut-off time, one tenth of a cycle at 10 times overload, designed to protect thyristors, rectifiers and any semiconductors sensitive to overload. UL recognised up to 5A

Voltage rating (Vn) 250V ac
 Breaking capacity 1500A @ 6.3A & above 300kA up to 5A

Mfrs. List No. 70-001-40 + Rating

FUS2X/204497

Order Multiple=10	Order Code	10+	100+	500+	1K+
500mA	117-5126	0.82	0.74	0.66	0.63
1A	117-5127	0.82	0.74	0.66	0.63
1.6A	117-5136	0.82	0.74	0.66	0.63
2A	117-5128	0.82	0.74	0.66	0.63
2.5A	117-5137	0.82	0.74	0.66	0.63
3.15A	117-5131	0.82	0.74	0.66	0.63

Order Multiple=10

Rating	Order Code	10+	100+	500+	1K+
4A	117-5138	0.82	0.74	0.66	0.63
5A	117-5132	0.82	0.74	0.66	0.63
6.3A	117-5133	0.82	0.74	0.66	0.63
8A	117-5134	0.82	0.74	0.66	0.63
10A	117-5135	0.82	0.74	0.66	0.63

Quick Blow(F) Ceramic
MCF04C Series

- Complies with IEC 127, DIN41660 and BS4265
- UL Recognised

Voltage rating 250V Breaking capacity 1500A @ 250V

Mfrs. List No. MCF04C + Rating

FUS287/204484

Order Multiple=10

Current Rating	Order Code	10+	100+	500+	1K+	3K+
100mA	112-3145	0.360	0.320	0.310	0.300	0.290
125mA	112-3147	0.290	0.260	0.250	0.240	0.220
200mA	112-3150	0.360	0.320	0.310	0.300	0.290
250mA	112-3151	0.360	0.320	0.310	0.300	0.290
500mA	112-3158	0.570	0.500	0.490	0.470	0.450
800mA	112-3162	0.570	0.500	0.490	0.470	0.450
1A	112-3148	0.105	0.094	0.089	0.084	0.078
1.25A	112-3143	0.098	0.088	0.082	0.080	0.075
2A	112-3152	0.180	0.163	0.154	0.143	0.135
2.5A	112-3149	0.192	0.173	0.165	0.160	0.149
3.15A	112-3153	0.185	0.166	0.155	0.149	0.138
4A	112-3157	0.180	0.163	0.154	0.148	0.135
5A	112-3159	0.180	0.163	0.154	0.148	0.135
6.3A	112-3160	0.190	0.171	0.163	0.158	0.147
8A	112-3163	0.230	0.210	0.197	0.191	0.178
10A	112-3146	0.230	0.210	0.197	0.191	0.178

Quick Blow (F) Ceramic
20 x 5mm Fuses - 216P Series

- Designed to International (IEC) Standards for global use
- Meets the IEC 60127-2, Sheet 1 specification for Fast Acting Fuses

- High breaking capacity
- Improved I²t
- CSA, METI, CCC, K-Mark, Semko and VDE Approvals
- UL Recognised

Voltage rating (Vn) 250V ac
 Interrupting Rating - 50mA to 8A 1500A @ 250V ac, PF = 0.7 to 0.8
 Interrupting Rating - 16A 750A @ 250V ac, PF = 1.0
 Operating Temperature -55 to 125°C

Manufacturers Part Number = 216. followed by Value and then P

467707

Order Multiple=10

Rating	Order Code	10+	100+	500+	1K+
50mA	135-4524	0.790	0.690	0.670	0.640
63mA	135-4525	0.480	0.380	0.370	0.360
80mA	135-4526	0.480	0.380	0.370	0.360
100mA	135-4527	0.380	0.320	0.310	0.300
200mA	135-4532	0.380	0.320	0.310	0.300
250mA	135-4533	0.380	0.320	0.310	0.300
400mA	135-4535	0.380	0.320	0.310	0.300
500mA	135-4536	0.380	0.320	0.310	0.300
800mA	135-4538	0.380	0.320	0.310	0.300
1A	135-4539	0.194	0.160	0.148	0.137
1.6A	135-4542	0.194	0.160	0.148	0.137
2A	135-4543	0.194	0.160	0.148	0.137
2.5A	135-4544	0.194	0.160	0.148	0.137
3.15A	135-4545	0.194	0.160	0.148	0.137
4A	135-4546	0.194	0.160	0.148	0.137
5A	135-4547	0.194	0.160	0.148	0.137
6.3A	135-4548	0.194	0.160	0.148	0.137
8A	135-4549	0.194	0.160	0.148	0.137
16A	135-4551	0.194	0.160	0.148	0.137

5x20mm Fuseholders from page 328

Quick Blow (F) HRC Ceramic
20 x 5mm Fuses S501 Series

- Complies with IEC127:Standard Sheet I
- Approved to SEMKO (500mA to 5A)

Voltage rating (Vn) 250V ac
 Breaking capacity 1500A @ Vn, Cos φ = 0.7 to 0.8
 Mfrs. List No. S501 - Value

204522

Order Multiple=10		Price Each			
Rating	Order Code	10+	100+	500+	1K+
50mA	NEW 161-5141●	0.830	0.720	0.690	0.670
63mA	NEW 161-5143●	0.830	0.720	0.690	0.670
80mA	NEW 161-5144●	0.830	0.720	0.690	0.670
100mA	112-3097●	0.320	0.290	0.270	0.260
125mA	NEW 161-5145●	0.450	0.410	0.390	0.370
160mA	NEW 161-5146●	0.450	0.410	0.390	0.370
200mA	NEW 161-5147●	0.450	0.410	0.390	0.370
250mA	112-3101●	0.370	0.330	0.320	0.310
315mA	NEW 161-5148●	0.410	0.360	0.350	0.340
400mA	NEW 161-5149●	0.410	0.360	0.350	0.340
500mA	112-3106●	0.470	0.420	0.410	0.390
800mA	112-3110●	0.470	0.420	0.410	0.390
1A	112-3100●	0.192	0.180	0.167	0.160
1.25A	NEW 161-5150●	0.210	0.200	0.187	0.179
1.6A	NEW 161-5151●	0.210	0.200	0.187	0.179
2A	112-3102●	0.163	0.147	0.140	0.133
2.5A	NEW 161-5152●	0.184	0.166	0.158	0.151
3.15A	112-3103●	0.163	0.147	0.140	0.133
4A	112-3104●	0.163	0.147	0.140	0.133
5A	112-3107●	0.164	0.151	0.143	0.135
6.3A	112-3108●	0.164	0.151	0.143	0.135
8A	112-3111●	0.170	0.155	0.144	0.137
10A	112-3098●	0.163	0.146	0.139	0.132

Type SP 5 x 20mm Quick Acting (F)



- IEC standard fuse
- High breaking capacity
- Ceramic tube
- VDE Approved, **UL** Recognised

Voltage rating 250V ac Breaking capacity (IEC) - 0.1A to 10A 1500A @ 250V ac
Ambient temperature -55 to 125°C Breaking capacity (IEC) - 12.5A and 16A 1000A @ 250V ac

Mfrs. List No.	Order Code	Mfrs. List No.	Order Code	Mfrs. List No.	Order Code
0001.1001	136-0825	0001.1008	136-0833	0001.1013	136-0841
0001.1004	136-0829	0001.1009	136-0835	0001.1014	136-0842
0001.1005	136-0830	0001.1010	136-0836	0001.1015	136-0843
0001.1006	136-0831	0001.1011	136-0837	0001.1016	136-0844
0001.1007	136-0832	0001.1012	136-0839		

472686

Order Multiple=10		Price Each				
Rating	Order Code	10+	100+	500+	1K+	3K+
0.5A	136-0825●	0.430	0.340	0.290	0.270	0.250
1A	136-0829●	0.188	0.151	0.140	0.129	0.110
1.25A	136-0830●	0.188	0.151	0.140	0.129	0.110
1.6A	136-0831●	0.188	0.151	0.140	0.129	0.110
2A	136-0832●	0.188	0.151	0.140	0.129	0.110
2.5A	136-0833●	0.188	0.151	0.140	0.129	0.110
3.15A	136-0835●	0.188	0.151	0.140	0.129	0.110
4A	136-0836●	0.188	0.151	0.140	0.129	0.110
5A	136-0837●	0.188	0.151	0.140	0.129	0.110
6.3A	136-0839●	0.188	0.151	0.140	0.129	0.110
8A	136-0841●	0.188	0.151	0.140	0.129	0.110
10A	136-0842●	0.188	0.151	0.140	0.129	0.110
12.5A	136-0843●	0.188	0.151	0.140	0.129	0.110
16A	136-0844●	0.188	0.151	0.140	0.129	0.110

Quick Blow (F) Glass 20 x 5mm Fuses MCF05G



- Complies with IEC127 Part 2 Sheet II, DIN41661 and BS4265
- **UL** Recognised

Mfrs. List No. MCF05G + Rating

Voltage rating (Vn) 250V ac
Breaking capacity 100mA to 31.5A = 35A @ 250V, 4A to 10A = 10 X In @ 250V

204485

Order Multiple=10		Price Each				
Current Rating	Order Code	10+	100+	500+	1K+	3K+
100mA	112-3167●	0.510	0.470	0.460	0.450	0.420
125mA	112-3169●	0.510	0.470	0.460	0.450	0.420
160mA	112-3170●	0.290	0.280	0.270	0.260	0.250
200mA	112-3173●	0.390	0.360	0.350	0.340	0.320
250mA	112-3174●	0.390	0.360	0.350	0.340	0.320
315mA	112-3177●	0.390	0.360	0.350	0.340	0.320
400mA	112-3179●	0.083	0.075	0.068	0.062	0.048
500mA	112-3182●	0.152	0.141	0.125	0.114	0.086
630mA	112-3185●	0.152	0.141	0.125	0.114	0.086
800mA	112-3186●	0.083	0.075	0.068	0.062	0.048
1A	112-3171●	0.106	0.098	0.086	0.079	0.060
1.25A	112-3164●	0.106	0.098	0.086	0.079	0.060
1.6A	112-3165●	0.106	0.098	0.086	0.079	0.060
2A	112-3175●	0.106	0.098	0.086	0.079	0.060
2.5A	112-3172●	0.106	0.098	0.086	0.079	0.060
3.15A	112-3176●	0.106	0.098	0.086	0.079	0.060
4A	112-3181●	0.106	0.098	0.086	0.079	0.060
5A	112-3183●	0.106	0.098	0.086	0.079	0.060
6.3A	112-3184●	0.106	0.098	0.086	0.079	0.060
8A	112-3187●	0.106	0.098	0.086	0.079	0.060
10A	112-3168●	0.106	0.098	0.086	0.079	0.060

Quick Blow (F) Glass 20 x 5mm Fuses - 217P Series



- Designed to International (IEC) Standards for global use
- Meets the IEC 60127-2, Sheet 1 specification for Fast Acting Fuses
- High breaking capacity
- Improved I² t
- CSA, METI, CCC, K-Mark, Semko and VDE Approvals
- **UL** Recognised

Voltage rating (Vn) 250V ac
Interrupting Rating 35A @ 250V ac
or 10 x rated current (whichever is greater) to a max. of 100A
Operating Temperature -55 to 125°C

Manufacturers Part Number = 217, followed by Value and then P

467733

Order Multiple=10		Price Each			
Rating	Order Code	10+	100+	500+	1K+
50mA	135-4555●	0.490	0.460	0.430	0.410
63mA	135-4556●	0.430	0.370	0.350	0.340
80mA	135-4557●	0.430	0.370	0.350	0.340
100mA	135-4558●	0.430	0.370	0.350	0.340
160mA	135-4560●	0.430	0.370	0.350	0.340
200mA	135-4561●	0.430	0.370	0.350	0.340
250mA	135-4562●	0.430	0.370	0.350	0.340
315mA	135-4563●	0.430	0.370	0.350	0.340
400mA	135-4564●	0.114	0.104	0.103	0.092
500mA	135-4567●	0.114	0.104	0.103	0.092
630mA	135-4568●	0.114	0.104	0.103	0.092
800mA	135-4569●	0.114	0.104	0.103	0.092
1A	135-4570●	0.114	0.104	0.103	0.092
1.25A	135-4571●	0.114	0.104	0.103	0.092
1.6A	135-4572●	0.114	0.104	0.103	0.092
2A	135-4573●	0.114	0.104	0.103	0.092
2.5A	135-4574●	0.114	0.104	0.103	0.092
3.15A	135-4575●	0.114	0.104	0.103	0.092
4A	135-4576●	0.114	0.104	0.103	0.092
5A	135-4578●	0.114	0.104	0.103	0.092
6.3A	135-4579●	0.114	0.104	0.103	0.092
10A	135-4580●	0.114	0.104	0.103	0.092
15A	135-4581●	0.114	0.104	0.103	0.092

Quick Blow (F) Glass 20 x 5mm Fuses S500 Series*



- Complies with IEC127, BS4265, Standard Sheet II
- Approved to SEMKO, BSI, VDE, IMQ
- **UL** recognised* except 8A and 10A which are not approved

Voltage rating (Vn) 250V ac Mfrs. List No.
Breaking capacity 35A @ Vn 50mA to 6.3A S500 + Rating,
8A, 10A* TDC641 + Rating

204592

Rating		Price Each			
Order Code		10+	100+	500+	1K+
NEW 161-5153●		0.880	0.770	0.670	0.570
NEW 161-5155●		0.880	0.770	0.670	0.570
112-3089●		0.390	0.360	0.340	0.310
112-3093●		0.290	0.270	0.250	0.230
112-3095●		0.380	0.350	0.320	0.310
112-3074●		0.270	0.250	0.240	0.220
112-3077●		0.270	0.250	0.220	0.200
112-3078●		0.250	0.240	0.220	0.210
112-3081●		0.116	0.105	0.099	0.093
112-3082●		0.106	0.095	0.089	0.084
112-3085●		0.097	0.086	0.080	0.074
112-3086●		0.116	0.110	0.100	0.093
112-3088●		0.089	0.080	0.074	0.068
112-3092●		0.106	0.101	0.087	0.079
112-3094●		0.082	0.071	0.068	0.064
112-3079●		0.082	0.073	0.068	0.064
112-3072●		0.082	0.071	0.068	0.064
112-3073●		0.082	0.072	0.068	0.064
112-3083●		0.082	0.073	0.068	0.064
112-3080●		0.082	0.071	0.068	0.064
112-3084●		0.082	0.072	0.068	0.064
NEW 161-5156●		0.093	0.081	0.078	0.075
112-3090●		0.082	0.072	0.069	0.064
112-3091●		0.082	0.072	0.069	0.064
112-3096●		0.084	0.079	0.070	0.067
112-3076●		0.086	0.078	0.074	0.070

Type FSF 5 x 20mm Quick Acting (F)



- IEC standard fuse
- Low breaking capacity
- Glass tube
- VDE Approved, **UL** Recognised

Voltage rating 250V ac Breaking capacity - 0.1A to 3.15A 35A @ 250V ac
Ambient temperature -55 to 125°C Breaking capacity - 4A to 10A 10 x I_n @ 250V ac

Mfrs. List No.	Order Code	Mfrs. List No.	Order Code	Mfrs. List No.	Order Code
0034.1506	136-0771	0034.1507	136-0773	0034.1509	136-0776
0034.1506	136-0771	0034.1508	136-0774	0034.1510	136-0778



20 x 5mm Fuses - continued

Type FSF 5 x 20mm - continued

Quick Acting (F) - continued

Mfrs. List No.	Order Code	Mfrs. List No.	Order Code	Mfrs. List No.	Order Code
0034.1511	136-0779	0034.1517	136-0786	0034.1522	136-0791
0034.1512	136-0780	0034.1518	136-0787	0034.1523	136-0792
0034.1513	136-0781	0034.1519	136-0788	0034.1524	136-0793
0034.1514	136-0782	0034.1520	136-0789	0034.1525	136-0794
0034.1515	136-0783	0034.1521	136-0790	0034.1526	136-0795
0034.1516	136-0785				

472612

Order Multiple=10	Rating	Order Code	10+	100+	500+	1K+	3K+
0.1A	136-0771●	0.114	0.104	0.098	0.091	0.084	
0.125A	136-0773●	0.114	0.104	0.098	0.091	0.084	
0.16A	136-0774●	0.114	0.104	0.098	0.091	0.084	
0.2A	136-0776●	0.114	0.104	0.098	0.091	0.084	
0.25A	136-0778●	0.114	0.104	0.098	0.091	0.084	
0.315A	136-0779●	0.114	0.104	0.098	0.091	0.084	
0.4A	136-0780●	0.114	0.104	0.098	0.091	0.084	
0.5A	136-0781●	0.114	0.104	0.098	0.091	0.084	
0.63A	136-0782●	0.114	0.104	0.098	0.091	0.084	
0.8A	136-0783●	0.114	0.104	0.098	0.091	0.084	
1A	136-0785●	0.114	0.104	0.098	0.091	0.084	
1.25A	136-0786●	0.114	0.104	0.098	0.091	0.084	
1.6A	136-0787●	0.114	0.104	0.098	0.091	0.084	
2A	136-0788●	0.114	0.104	0.098	0.091	0.084	
2.5A	136-0789●	0.114	0.104	0.098	0.091	0.084	
3.15A	136-0790●	0.114	0.104	0.098	0.091	0.084	
4A	136-0791●	0.114	0.104	0.098	0.091	0.084	
5A	136-0792●	0.114	0.104	0.098	0.091	0.084	
6.3A	136-0793●	0.167	0.149	0.139	0.130	0.117	
8A	136-0794●	0.167	0.149	0.139	0.130	0.117	
10A	136-0795●	0.167	0.149	0.139	0.130	0.117	

Medium Blow (M) Glass/Ceramic

20 x 5mm Fuses - 234 Series



- Designed to UL/CSA/ANCE 248 Standard
- METI, CSA, K-Mark, and CE Approvals
- UL Recognised

Voltage rating (Vn)
Interrupting Rating - 1A
Interrupting Rating - 1.25A to 3.5A
Interrupting Rating - 4A to 10A
Operating Temperature

250V ac
35A @ 250V ac, PF = 0.7 to 0.8
100A @ 250V ac, PF = 0.7 to 0.8
200A @ 250V ac, PF = 0.7 to 0.8
-55 to 125°C

Manufacturers Part Number = 234. followed by Value

467758

Order Multiple=10	Rating	Order Code	10+	100+	500+	1K+
Glass Body						
1A	135-4582●	0.126	0.114	0.105	0.104	
1.25A	135-4583●	0.126	0.114	0.105	0.104	
1.6A	135-4584●	0.126	0.114	0.105	0.104	
2A	135-4585●	0.126	0.114	0.105	0.104	
2.5A	135-4586●	0.126	0.114	0.105	0.104	
3A	135-4587●	0.126	0.114	0.105	0.104	
3.15A	135-4588●	0.126	0.114	0.105	0.104	
3.5A	135-4591●	0.126	0.114	0.105	0.104	
Ceramic Body						
4A	135-4592●	0.126	0.114	0.105	0.104	
5A	135-4593●	0.126	0.114	0.105	0.104	
6A	135-4594●	0.126	0.114	0.105	0.104	
6.3A	135-4595●	0.126	0.114	0.105	0.104	
8A	135-4596●	0.126	0.114	0.105	0.104	
10A	135-4597●	0.126	0.114	0.105	0.104	

Medium Blow (M) Glass

TDC 210 Series



- Conforms to DIN 41.75 T2

Voltage rating 250V ac
Construction 1A - Glass tube
1.6A and above - glass tube
with extinguishing agent

Breaking capacity @ 250V

1A = 80A
1.6A to 6.3A = 1000A
8A to 10A = 300A

Mfrs. List No. 210 + Rating

FUS312/204511

Order Multiple=10	Rating	Order Code	10+	50+	250+	1K+
1A	120-2374●	0.109	0.102	0.086	0.071	
1.6A	120-2375●	0.109	0.102	0.086	0.071	
2A	120-2377●	0.109	0.102	0.086	0.071	
2.5A	120-2378●	0.109	0.102	0.086	0.071	
3.15A	120-2379●	0.109	0.102	0.086	0.071	
4A	120-2380●	0.109	0.102	0.086	0.071	
5A	120-2381●	0.109	0.102	0.086	0.071	
6.3A	120-2382●	0.109	0.102	0.086	0.071	
8A	120-2384●	0.109	0.099	0.085	0.075	
10A	120-2383●	0.109	0.099	0.085	0.075	

Antisurge (T) HRC Ceramic

20 x 5mm Fuses MCF03C Series



- Complies with IEC127, DIN41662 and BS4265
- UL Recognised

Voltage rating 250V Breaking capacity 1500A @ 250V

Mfrs. List No. MCF03C + Rating

204487

Order Multiple=10	Current Rating	Order Code	10+	100+	500+	1K+	3K+
500mA	112-3136●	0.420	0.390	0.370	0.350	0.310	
800mA	112-3140●	0.420	0.390	0.370	0.350	0.310	
1A	112-3131●	0.220	0.200	0.187	0.179	0.160	
1.25A	112-3126●	0.220	0.200	0.187	0.179	0.160	
1.6A	112-3127●	0.220	0.200	0.187	0.179	0.160	
2A	112-3133●	0.220	0.200	0.187	0.179	0.160	
2.5A	112-3132●	0.220	0.200	0.187	0.179	0.160	
3.15A	112-3134●	0.220	0.200	0.187	0.179	0.160	
4A	112-3135●	0.240	0.230	0.210	0.200	0.181	
5A	112-3137●	0.240	0.230	0.210	0.200	0.181	
6.3A	112-3138●	0.290	0.270	0.250	0.240	0.220	
8A	112-3141●	0.290	0.270	0.250	0.240	0.220	
10A	112-3128●	0.290	0.270	0.250	0.240	0.220	

Time Lag (T) Ceramic

20 x 5mm Fuses - 215P Series



- Designed to International (IEC) Standards for global use
- Meets the IEC 60127-2, Sheet 5 specification for Time Lag Fuses
- High breaking capacity
- Improved I² t
- CSA, METI, CCC, K-Mark, Semko and VDE Approvals
- UL Recognised

Voltage rating (Vn) 250V ac
Interrupting Rating 1500A @ 250V ac, PF = 0.7 to 0.8
Operating Temperature -55 to 125°C

Manufacturers Part Number = 215. followed by Value and then P

467755

Order Multiple=10	Rating	Order Code	10+	100+	500+	1K+
200mA	135-4598●	0.250	0.220	0.171	0.150	
250mA	135-4599●	0.250	0.220	0.171	0.150	
315mA	135-4600●	0.250	0.220	0.171	0.150	
400mA	135-4601●	0.250	0.220	0.171	0.150	
500mA	135-4602●	0.250	0.220	0.171	0.150	
630mA	135-4603●	0.250	0.220	0.171	0.150	
800mA	135-4604●	0.250	0.220	0.171	0.150	
1A	135-4605●	0.250	0.220	0.171	0.150	
1.25A	135-4606●	0.250	0.220	0.171	0.150	
1.6A	135-4608●	0.250	0.220	0.171	0.150	
2A	135-4609●	0.250	0.220	0.171	0.150	
2.5A	135-4610●	0.250	0.220	0.171	0.150	
3.15A	135-4611●	0.250	0.220	0.171	0.150	
4A	135-4613●	0.250	0.220	0.171	0.150	
5A	135-4614●	0.250	0.220	0.171	0.150	
6.3A	135-4615●	0.250	0.220	0.171	0.150	
8A	135-4616●	0.250	0.220	0.171	0.150	
10A	135-4617●	0.250	0.220	0.171	0.150	
12A	135-4618●	0.250	0.220	0.171	0.150	

Antisurge(T) HRC Ceramic

S505 Series



- Complies with IEC127, Standard Sheet V
- Approved to VDE (2A to 5A), SEMKO (1.6A to 4A)

Voltage rating (Vn) 250V ac
Breaking capacity 1500A @ Vn

Mfrs. List No. Single: S505 + Rating

204611

Order Multiple=10	Rating	Order Code	10+	100+	500+	1K+
500mA	112-3121●	0.310	0.290	0.280	0.270	
800mA	112-3124●	0.220	0.210	0.200	0.199	
1A	112-3115●	0.184	0.165	0.158	0.146	
1.25A	112-3112●	0.144	0.130	0.122	0.118	
1.6A	112-3113●	0.183	0.164	0.154	0.150	
2A	112-3118●	0.184	0.166	0.158	0.146	
2.5A	112-3116●	0.184	0.165	0.158	0.146	
3.15A	112-3119●	0.184	0.166	0.158	0.146	
4A	112-3120●	0.184	0.165	0.158	0.146	
5A	112-3122●	0.184	0.165	0.158	0.146	
6.3A	112-3123●	0.184	0.165	0.158	0.146	
8A	112-3125●	0.184	0.165	0.158	0.146	
10A	112-3114●	0.184	0.165	0.158	0.146	

Over 480,000 products online



Type SPT 5 x 20mm

Time Lag (T)



- IEC standard fuse
- High breaking capacity
- Ceramic tube
- VDE Approved (1A to 10A)
- UL Recognised

Voltage rating 250V ac Breaking capacity (IEC) - 0.5A to 6.3A 1500A @ 250V ac
Ambient temperature -55 to 125°C Breaking capacity (IEC) - 8A and 10A 1000A @ 250V ac

Mfrs. List No.	Order Code	Mfrs. List No.	Order Code	Mfrs. List No.	Order Code
0001.2501	136-0845	0001.2506	136-0850	0001.2511	136-0859
0001.2502	136-0846	0001.2507	136-0852	0001.2512	136-0860
0001.2503	136-0847	0001.2508	136-0854	0001.2513	136-0861
0001.2504	136-0848	0001.2509	136-0855	0001.2514	136-0862
0001.2505	136-0849	0001.2510	136-0857		

472708

Order Multiple=10	Order Code	10+	100+	500+	1K+	3K+
0.5A	136-0845	0.520	0.470	0.420	0.380	0.350
0.63A	136-0846	0.520	0.470	0.420	0.380	0.350
0.8A	136-0847	0.520	0.470	0.420	0.380	0.350
1A	136-0848	0.240	0.200	0.170	0.141	0.134
1.25A	136-0849	0.240	0.200	0.170	0.141	0.134
1.6A	136-0850	0.240	0.200	0.170	0.141	0.134
2A	136-0852	0.240	0.200	0.170	0.141	0.134
2.5A	136-0854	0.240	0.200	0.170	0.141	0.134
3.15A	136-0855	0.240	0.200	0.170	0.141	0.134
4A	136-0857	0.240	0.200	0.170	0.141	0.134
5A	136-0859	0.240	0.200	0.170	0.141	0.134
6.3A	136-0860	0.240	0.200	0.170	0.141	0.134
8A	136-0861	0.240	0.200	0.170	0.141	0.134
10A	136-0862	0.240	0.200	0.170	0.141	0.134

Antisurge (T) Glass

20 x 5mm Fuses MCF06G Series



- Complies with IEC127, DIN41662 and BS4265
- UL Recognised

Mfrs. List No. MCF06G + rating

Voltage rating 250V
Breaking capacity 32MA to 3.15A, 35A @ 250V, 4A to 6.3A 10 x IN @ 250V

204488

Order Multiple=10	Order Code	10+	100+	500+	1K+	3K+
Current Rating						
32mA	112-3202	1.330	1.220	1.090	0.870	0.820
40mA	112-3204	1.330	1.220	1.090	0.870	0.820
50mA	112-3207	0.830	0.760	0.680	0.550	0.510
63mA	112-3213	0.830	0.760	0.680	0.550	0.510
80mA	112-3215	0.430	0.400	0.330	0.270	0.250
100mA	112-3190	0.830	0.760	0.680	0.550	0.510
125mA	112-3193	0.280	0.250	0.220	0.172	0.164
160mA	112-3194	0.350	0.320	0.280	0.220	0.210
200mA	112-3197	0.320	0.290	0.260	0.194	0.183
250mA	112-3198	0.220	0.197	0.176	0.135	0.125
315mA	112-3201	0.179	0.160	0.143	0.108	0.102
400mA	112-3203	0.095	0.086	0.077	0.059	0.055
500mA	112-3206	0.112	0.100	0.089	0.068	0.064
630mA	112-3212	0.106	0.095	0.085	0.064	0.060
800mA	112-3214	0.112	0.100	0.089	0.068	0.064
1A	112-3195	0.138	0.123	0.110	0.084	0.078
1.25A	112-3188	0.120	0.107	0.095	0.072	0.068
1.6A	112-3189	0.120	0.107	0.095	0.072	0.068
2A	112-3199	0.120	0.107	0.095	0.072	0.068
2.5A	112-3196	0.106	0.095	0.085	0.064	0.060
3.15A	112-3200	0.106	0.095	0.085	0.064	0.060
4A	112-3205	0.120	0.109	0.097	0.072	0.067
5A	112-3209	0.135	0.123	0.110	0.084	0.077
6.3A	112-3211	0.154	0.140	0.125	0.096	0.088
10A	112-3192	0.154	0.140	0.125	0.096	0.088

FOR MORE INFORMATION & CHOICE

Product Search

TR5 Fuse



RoHS Compliant Items Only | Advanced Search

Antisurge (T) Glass

Enhanced Breaking Capacity



Voltage rating 250V ac Breaking capacity 150A @ 250V ac
Mfrs. List No. 219 + Rating

FUS268X/204463

Designed to meet the new IEC 127 Part 2, sheet 6 requirements for enhanced breaking capacity glass fuses. A cost effective alternative to ceramic fuses in applications that require a fuse with a breaking capacity of 150A

Order Multiple=10	Order Code	10+	100+	500+	1K+
Rating					
1A	992-2458	0.126	0.114	0.103	0.091
1.25A	992-2466	0.126	0.114	0.103	0.091
1.6A	992-2474	0.126	0.114	0.103	0.091
2A	992-2482	0.126	0.114	0.103	0.091
2.5A	992-2490	0.126	0.114	0.103	0.091
3.15A	992-2504	0.126	0.114	0.103	0.091
4A	992-2512	0.126	0.114	0.103	0.091
5A	992-2520	0.126	0.114	0.103	0.091
6.3A	992-2539	0.126	0.114	0.103	0.091

Time Lag (Slo-Blo) - Glass

5 x 20mm, 218P Series



- Designed to international (IEC) standards
- Meets IEC 60127-2, sheet 3 specification for Time Lag Fuses
- Voltage rating 250V ac
- Interrupting rating 1500A @ 250V ac, unity power factor
- CCC, CSA, SEMKO, BSI Approved, UL Recognised

Mfrs. List No. = 218P + Rating

446659

Order Multiple=10	Order Code	10+	100+	500+	1K+
Rating (I _g)					
80mA	127-1650	0.160	0.148	0.137	0.126
100mA	127-1681	0.171	0.160	0.148	0.137
250mA	127-1685	0.137	0.126	0.115	0.114
315mA	127-1688	0.093	0.086	0.078	0.067
400mA	127-1629	0.091	0.080	0.069	0.058
500mA	127-1689	0.093	0.086	0.078	0.067
630mA	127-1630	0.103	0.091	0.080	0.069
800mA	127-1631	0.091	0.080	0.070	0.069
1A	127-1682	0.091	0.081	0.080	0.070
1.25A	127-1679	0.103	0.092	0.091	0.080
1.6A	127-1680	0.103	0.092	0.091	0.080
2A	127-1686	0.091	0.081	0.080	0.069
2.5A	127-1683	0.126	0.114	0.103	0.091
3.15A	127-1687	0.091	0.081	0.080	0.069
4A	127-1632	0.093	0.086	0.078	0.067
5A	127-1690	0.091	0.081	0.080	0.069
6.3A	127-1633	0.210	0.183	0.160	0.137
10A	127-1634	0.093	0.086	0.078	0.067

Antisurge (T) Glass - Spiral Element

213 Series



- Complies with IEC 60127-2, Sheet 3 and BSI KM41462
- Approved to VDE, SEMKO, CCC, PSE and BSI
- UL Recognised

Voltage rating (V_n): 250Vac
Breaking Capacity: 250mA to 3.15A, 35A @ V_n, 40A @ V_n

Mfrs. List No.: 213 + Rating

204439

Order Multiple=10	Order Code	10+	100+	500+	1K+
Rating					
250mA	992-2210	0.148	0.137	0.126	0.103
315mA	992-2229	0.148	0.137	0.126	0.103
500mA	992-2237	0.148	0.137	0.126	0.103
1A	992-2245	0.148	0.137	0.126	0.103
1.25A	992-2253	0.148	0.137	0.126	0.103
1.6A	992-2261	0.148	0.137	0.126	0.103
2A	992-2270	0.148	0.137	0.126	0.103
2.5A	992-2288	0.148	0.137	0.126	0.103
3.15A	992-2296	0.148	0.137	0.126	0.103
4A	992-2300	0.148	0.137	0.126	0.103

Antisurge (T) Glass - Plated Wire

20 x 5mm Fuses S506 Series



- Complies with IEC127, BS4265, Standard Sheet III
- Approved to VDE, BSI, SEMKO (not 5A) and IMQ (1A to 6.3A)

Voltage rating (V_n) 250V ac Mfrs. List No. S506 + Rating
Breaking capacity 35A @ V_n

204379

Order Multiple=10	Order Code	10+	100+	500+	1K+
Rating					
32mA	NEW 161-5157	0.880	0.770	0.670	0.570
40mA	NEW 161-5158	0.880	0.770	0.670	0.570
50mA	124-1958	0.192	0.179	0.166	0.153
63mA	124-1959	0.192	0.179	0.166	0.153
80mA	124-1960	0.149	0.138	0.126	0.113
100mA	124-1961	0.153	0.139	0.126	0.113
125mA	124-1962	0.210	0.197	0.183	0.161
160mA	124-1963	0.210	0.197	0.183	0.161
200mA	124-1964	0.210	0.197	0.183	0.161
250mA	124-1966	0.133	0.119	0.115	0.109
315mA	124-1967	0.133	0.119	0.115	0.109
400mA	124-1968	0.192	0.180	0.167	0.147
500mA	112-3239	0.156	0.144	0.134	0.124
630mA	112-3240	0.156	0.144	0.134	0.124
800mA	124-1969	0.156	0.146	0.136	0.120
1A	112-3241	0.155	0.140	0.134	0.127
1.25A	112-3242	0.156	0.146	0.136	0.120



20 x 5mm Fuses - continued

Antisurge (T) Glass - Plated Wire - continued

20 x 5mm Fuses S506 Series - continued

Order Multiple=10		Price Each			
Rating	Order Code	10+	100+	500+	1K+
1.6A	112-3243●	0.156	0.144	0.134	0.124
2A	112-3244●	0.167	0.151	0.144	0.134
2.5A	112-3246●	0.136	0.125	0.118	0.111
3.15A	112-3247●	0.133	0.119	0.114	0.108
4A	NEW 161-5159●	0.162	0.151	0.138	0.127
5A	112-3248●	0.177	0.158	0.151	0.141
6.3A	112-3249●	0.169	0.152	0.146	0.139
8A	NEW 161-5160●	0.162	0.151	0.138	0.127
10A	NEW 161-5161●	0.162	0.151	0.138	0.127
12.5A	NEW 161-5162●	0.162	0.151	0.138	0.127

Type FST 5 x 20mm

Time Lag (T)



- IEC standard fuse
- Low breaking capacity
- Glass tube
- VDE Approved, UL Recognised

Voltage rating	250V ac	Breaking capacity - 0.1A to 3.15A	35A @ 250V ac
Ambient temperature	-55 to 125°C	Breaking capacity - 4A to 10A	10 x I _n @ 250V ac
Storage temperature	0 to 60°C	Breaking capacity - 12.5A and 16A	125A @ 250V ac

Mfrs. List No.	Order Code	Mfrs. List No.	Order Code	Mfrs. List No.	Order Code
0034.3107	136-0798	0034.3116	136-0809	0034.3123	136-0817
0034.3109	136-0801	0034.3117	136-0810	0034.3124	136-0818
0034.3110	136-0803	0034.3118	136-0811	0034.3125	136-0819
0034.3111	136-0804	0034.3119	136-0812	0034.3126	136-0821
0034.3112	136-0805	0034.3120	136-0813	0034.3127	136-0822
0034.3113	136-0806	0034.3121	136-0815	0034.3128	136-0823
0034.3114	136-0807	0034.3122	136-0816	0034.3129	136-0824
0034.3115	136-0808				

472632

Order Multiple=10		Price Each				
Rating	Order Code	10+	100+	500+	1K+	3K+
0.1A	136-0798●	0.490	0.440	0.400	0.360	0.320
0.16A	136-0801●	0.340	0.310	0.280	0.250	0.220
0.2A	136-0803●	0.300	0.270	0.240	0.210	0.193
0.25A	136-0804●	0.300	0.270	0.240	0.210	0.193
0.315A	136-0805●	0.156	0.144	0.130	0.114	0.105
0.4A	136-0806●	0.146	0.129	0.115	0.102	0.094
0.5A	136-0807●	0.146	0.129	0.115	0.102	0.094
0.63A	136-0808●	0.146	0.129	0.115	0.102	0.094
0.8A	136-0809●	0.146	0.129	0.115	0.102	0.094
1A	136-0810●	0.146	0.129	0.115	0.102	0.094
1.25A	136-0811●	0.146	0.129	0.115	0.102	0.094
1.6A	136-0812●	0.146	0.129	0.115	0.102	0.094
2A	136-0813●	0.146	0.129	0.115	0.102	0.094
2.5A	136-0815●	0.146	0.129	0.115	0.102	0.094
3.15A	136-0816●	0.146	0.129	0.115	0.102	0.094
4A	136-0817●	0.146	0.129	0.115	0.102	0.094
5A	136-0818●	0.146	0.129	0.115	0.102	0.094
6.3A	136-0819●	0.146	0.129	0.115	0.102	0.094
8A	136-0821●	0.177	0.163	0.146	0.131	0.119
10A	136-0822●	0.177	0.163	0.146	0.131	0.119
12.5A	136-0823●	0.198	0.182	0.164	0.145	0.134
16A	136-0824●	0.198	0.182	0.164	0.145	0.134

20 x 5mm Panel Mount Fusesolders

Bayonet Release

20 x 5mm Panel Mount



- Moulded in black PBT UL94-V0
- Low profile mounting
- Combined solder / 4.8mm quick connect terminal
- Anti rotation D fixing
- IEC 127-6
- SEMKO, CSA, VDE and CE Approved, UL Recognised

Length 45.7, Dia (bezel) = 16.0 Single flat = 12.0,
Depth behind panel = 40.2
Panel cut-out = 12.7 dia

Rating	10A @ 250V ac	Contact resistance	≤5mohm
Power dissipation	2.5W	Insulation resistance	≥100Mohm

484522

Order Multiple=5		Price Each				
Mfrs. List No.	Order Code	5+	25+	100+	250+	500+
MCHTC-70M	143-7177●	1.05	0.89	0.78	0.71	0.67

Over 480,000 products online



Screw Cap/Finger Release

20 x 5mm Panel Mount



- Finger release screw carrier
- Anti-rotation key fixing
- Combined solder / 2.8mm quick connect terminals
- IEC 1427-6
- SEMKO & CE Approved, UL Recognised

L (OA) = 34.2, D = 16, D (Cut-out) = 13, Key = 1.8 x 1mm

Rating	6.3A, 250Vac	Contact resistance	≤5mohm
Power rating	2.5W	Insulation resistance	≥100Mohm

484534

Mfr. List No.	Order Code	5+	25+	100+	250+	500+
MCHTC-30M	143-7178●	0.81	0.65	0.54	0.48	0.43

Screw Cap/Finger Release

20 x 5mm Panel Mount



- Screw driver release, screw carrier
- Anti-rotation D fixing
- Combined solder / 2.8mm quick connect terminals
- IEC 1427-6
- SEMKO, CSA & VDE Approvals. UL Recognised

L (OA) = 37.5, D = 16, D (Cut-out) = 12.7,
D (Flat cut-out) = 12mm

Rating	6.3A, 250Vac	Contact resistance	≤5mohm
Power rating	2.5W	Insulation resistance	≥100Mohm

484537

Mfr. List No.	Order Code	5+	25+	100+	250+	500+
MCHTC-35M	143-7179●	1.00	0.80	0.68	0.59	0.53

Front Mount - Sealed Option

FPG-1 Series



Body L 41.5 (Finger release 46.5), Dia. Bezel=15, Depth behind panel=34.5
Panel hole dia=13, Panel hole - 1 flat=12.7 x 12, Panel hole - 2 flat=12.7 x 11.7
Panel thickness=6 max

- Available with screwdriver or finger release carriers
- IP67 sealed option available
- Solder/quick connect terminals
- Bayonet cap carriers
- Compact design
- UL recognised, VDE, SEV, SEMKO and CSA approved
- Shocksafe category PC2

Rating	10A @ 250V - VDE, SEMKO and SEV	Contact resistance	≤5mΩ @ 20mV
	16A @ 250V - UL and CSA	Operating temp.	-25°C to +85°C
Materials	PBTP thermoplastic UL94V-0	Contacts	Copper alloy
Mfrs. List No:	3101.0010 = 113-4122, 3101.0015 = 113-4123	3101.0110 = 108-1794, 3101.0115 = 113-4124	

204506

Order Multiple=5		Price Each			
	Order Code	5+	50+	100+	
Unsealed (IP40)					
Screwdriver release	113-4122●	1.24	1.14	1.10	
Finger release	113-4123●	1.01	0.93	0.85	
Sealed (IP67)					
Screwdriver release	108-1794●	1.26	1.17	1.04	
Finger release	113-4124●	1.15	1.05	0.95	

Rear Mount

FPG2 Series



L Overall=41.5 (Finger release 46.5), Dia Bezel=16.1, Depth behind panel=28
Panel hole dia=13, Panel hole - 1 flat=12.7 x 12
Panel hole - 2 flats=12.7 x 11.7, Panel thickness=8 max

- Panel rear mount - allows pre-wiring
- Available with screwdriver or finger release
- Solder/quick connect terminals 4.8 x 0.5
- Compact design
- Bayonet cap carriers
- Shocksafe category PC2
- UL recognised, VDE, SEV, SEMKO and CSA approved

Rating 10A @ 250V
Materials PBTP thermoplastic **UL94V-0**
Operating temperature -40°C to +85°C

Contact resistance <5mΩ @ 20mV
Contacts Copper alloy

Mfrs. List No: 3101.0020 = 113-4125, 3101.0025 = 108-1795

204507

Order Multiple=5

	Order Code	5+	50+	100+
Screwdriver release	113-4125●	0.86	0.80	0.76
Finger release	108-1795●	0.97	0.89	0.86

Snap-In-Bayonet Cap

FPG3 Series

SCHURTER
ELECTRONIC COMPONENTS



- Screw driver or finger release
- Solder/quick connect terminals 4.8 x 0.5
- Two types for choice of panel thickness
- Schocksafe category **PC2**
- **UL** recognised, **VDE** approved

Length Overall=40 (finger release=45),
Dia Bezel=15
Depth behind panel=34.5, Panel hole dia=13
Panel hole - 1 flat=13 x 12.35,
Panel hole - 2 flats=13 x 11.7

Rating 16A @ 250V - **UL**

Materials PBTP thermoplastic **UL94V-0**
Operating Temp. -40 to +85°C

Mfrs. List No: 3101.0030 = 116-2736 3101.0035 = 117-5704,
3101.0031 = 117-5705 3101.0036 = 117-5706

Contact resistance <5mΩ @ 20mV
Max power dissipation **UL/CSA** 2.5W @ 40°C
Contacts Copper alloy

204505

Order Multiple=5

	Order Code	5+	50+	100+
Panel Thickness 1.0 to 1.8				
Screwdriver release	116-2736●	0.75	0.68	0.65
Finger release	117-5704●	0.75	0.68	0.65
Panel Thickness 2.0 to 3.0				
Screwdriver release	117-5705●	0.76	0.66	0.59
Finger release	117-5706●	0.81	0.72	0.64

PCB Through Hole Mount

FPG6 Series

SCHURTER
ELECTRONIC COMPONENTS



- 5 x 20mm fuseholders
- Solder terminals
- Slot release
- IP 40 and IP 67 versions available
- Meets requirements of IEC 60335-1 Ed. 4.0
- **VDE** & **K-Mark** Approved, **UL** Recognised

New

Body - L = 26.5mm. Panel
Cutout - Dia. = 12.7mm

Power Rating 2.5W / 10A @ 23°C
Rated Current 10A (VDE), 16A (UL/CSA)
Rated Voltage 250V ac

Shocksafe Category **PC2**
Materials Black Thermoset - **UL 94V-0**
Operating temperature -40°C to +85°C

522141

Description	Mfrs. List No.	Order Code	5+	50+	100+	+	+
IP 40	3101.0060	163-7557●	1.43	1.32	1.26	--	--
IP 67	3101.0160	163-7558●	1.85	1.64	1.49	--	--

Bayonet Cap-Panel Mount

Littelfuse



- Bayonet fixings, black **UL94V-0** body and cap, panel mountable.
- Both parts required for complete fuseholder
- Approved to **SEMKO**, **VDE** and **CSA**, **UL** Recognised

Body Length 32 Max: Dia 15
Panel Cut-out - 2 Flats 12.7 11.7

Rating 16A @ 250Vac (UL/CSA)
Operating temperature -25°C to +70°C

Breakdown voltage 4kV @ 50Hz
Admissible fuse power dissipation 4W @ 40°C

Mfrs. List No.
820

Order Code
124-3036

Mfrs. List No.
835

Order Code
124-3037

204472

	Order Code	1+	50+	100+	250+	500+
Holder	124-3036●	0.54	0.50	0.48	0.46	0.43
Cap	124-3037●	0.54	0.50	0.48	0.46	0.43

Help us to help the environment



This catalogue has been printed on paper certified from a sustainable source.
Please recycle after use.



Finger Release/Screw Cap

BULGIN



- Moulded in black glass filled nylon, the knurled cap with slot is easily removed by hand or using a small coin.
- Solder tab terminations.

L (overall)=36.9, Dia (Bezel)=15.9
Depth behind panel=27.8, Panel cut-out=12.9
Panel keyway=2.6 x 1.1, Panel thickness=3.2 max

Rating 6.3A @ 250V ac
Breakdown voltage 2.5kV ac @ 50Hz

Operating temperature -20°C to +100°C
Mfrs. List No. FX0296

204532

Order Code	1+	100+	Price Each 250+	500+	1K+
319-351●	1.36	1.21	1.13	1.09	1.05

Screw Cap - Low Profile

Dialight
BLP



Moulded in flame retardant polyester which meets the safety requirements of **BS415**, **IEC257** and is proof against test pin to **BS4042**. The cap with slot is easily removed using a small coin.
SEMKO, **VDE**, **CSA** approved and **UL** Recognised. Solder tab terminations.

L (overall)=34.7, Dia. (bezel)=14.6
Depth behind panel=32.7, Panel cutout=12.9
Panel keyway=1.7 x 1.1, Panel thickness=0.9 to 3.6

Rating 6.3A @ 250V ac
Breakdown voltage ≥4kV dc

Operating temperature -55°C to +70°C

Mfrs. List No. L2002

204554

Order Code	1+	50+	Price Each 200+	500+	1K+
319-399●	2.42	2.25	2.11	2.07	1.96

Touchproof® Snap Fit

FX Series, 20 x 5mm

BULGIN



FX 0367/2

FX 0458/2

FX 0369/1

- Designed for 20mm x 5mm Fuses
- Snap Fit into Panel
- Screw & Bayonet Cap release

- Touchproof Category **PC2**, **IEC127-6**
- Approvals: **VDE**, **CSA** & **SEMKO**, **UL** Recognised

Rating 16A @ 250V to **UL**
Materials Body - Polyester **UL94V-0** rated
Cap - Nylon **UL94V-0** rated

Contact resistance <10mohm
Max power dissipation 2.5W @ 23°C
Contacts Copper, Silver plated
Terminations 2.8mm x 0.8mm

Panel Size	Shape	Order Code
1.0 to 1.5mm	Round	351-0372
1.0 to 1.5mm	Round	351-0414
1.0 to 1.5mm	Square	351-0396

Panel Size	Shape	Order Code
2.0 to 3.0mm	Round	351-0384
2.0 to 3.0mm	Round	351-0426
2.0 to 3.0mm	Square	351-0402

242084

Mfrs. List No.	Order Code	1+	25+	Price Each 100+	250+
Bayonet Cap					
FX0367/1	351-0372●	1.06	1.01	0.95	0.91
FX0367/2	351-0384●	1.06	0.82	0.69	0.64
FX0369/1	351-0396●	1.06	1.01	0.95	0.91
FX0369/2	351-0402●	1.06	0.82	0.69	0.64
Screw Cap					
FX0458/1	351-0414●	1.12	0.87	0.72	0.67
FX0458/2	351-0426●	1.12	0.87	0.72	0.67

Touchproof® Screw Cap

Panel Mount, IP67

BULGIN



5 x 20mm

Designed for user safety, touchproof category **PC2** with polyester moulded body and nylon cap/end bung. The screw cap can be either screwdriver or hand released. Contacts are silver plated brass.

Approved to **CSA**, **VDE** and **SEMKO**. **UL** Recognised

Mfrs. List No. FX0462=963-0198

Fuse Size 5 x 20mm
Terminations 2.8mm x 0.5mm
Max. Rating: 10A @ 250V

Max. Power Dissipation 16A @ 250V **UL** & **CSA**
Operating Temperature 2.5W @ 23°C
-20 to 85°C

468668

Fuse Type	Order Code	1+	25+	Price Each 100+	250+
5 x 20mm	963-0198●	1.15	1.04	0.98	0.92

5 x 20 mm Panel Mount Fusesolders - continued

Touchproof® - Screw Cap

High and Low Profile Styles
20 x 5mm Panel MountL (overall)=44.1 Dia. (bezel)=15.9
Depth behind panel=41.7Panel cutout keyway=12.8 dia, 2.4 x 1.15
Panel cutout 'D' type (single flat) 12.0 x 12.8 dia
Panel thickness=8.7 max Tabs=2.8

- Panel mounting fuseholder with polyester body
- Available in 'D' type or key-way fixing styles

Rating 10A @ 250V ac
Breakdown voltage 7kV ac @ 50Hz

Operating temperature -20°C to +100°C

Mfrs. List No. FX0454 = 248-447, FX0455 = 319-405, FX0454S = 248-459, FX0455S = 319-375

204555

L (overall) = 44.1 Dia. (Bezel) = 15.9
Depth behind panel = 31.8Panel cutout keyway = 12.8 dia, 2.4 x 1.15
Panel cutout 'D' type (single flat) 12.0 x 12.8 dia
Panel thickness=5.6 max Tabs=2.8

- Approved to VDE, SEMKO and CSA, UL Recognised
- Designed to conform with BT172D

Fixing	Order Code	1+	100+	Price Each 250+	500+	1K+
Low Profile						
D' type	319-405●	1.28	1.26	1.13	0.93	0.89
Key-way	248-447●	1.28	1.26	1.13	0.93	0.89
High Profile						
D' type	319-375●	1.28	1.26	1.13	0.93	0.89
Key-way	248-459●	1.28	1.26	1.13	0.93	0.89

Touchproof®/Bayonet Cap - Low Profile

L (overall)=42.1 Dia (bezel)=15.9
Depth behind panel=39.7Panel cutout (single flat)=12.0 x 12.8 dia.
Panel thickness=8.7 max Tabs=2.8L (overall)=44.1 Bezel=15.91 x 15.91
Depth behind panel=39.7Panel cutout (single flat)=12.0 x 12.8 dia
Panel thickness=8.7max Tabs=2.8

'D' type panel mounting fuseholders moulded in polyester to BS3042. Approved to SEMKO, CSA, VDE and conforms to IEC257. UL Recognised

Rating 10A @ 250V ac
Breakdown voltage 7kV ac @ 50Hz

Operating temperature -20°C to +100°C

Mfrs. List No. FX0357 = 319-417, FX0359 = 319-429,

FOR MATCHING VOLTAGE SELECTOR SWITCH
ORDER CODE 149-288 & 150-362 SEE SWITCHES SECTION

204556

Order Code	1+	50+	Price Each 250+	500+	1K+
Round Bezel					
319-417●	1.27	1.25	1.13	0.93	0.89
Square Bezel					
319-429●	1.27	1.25	1.13	0.93	0.89

Insulating Cover



- A black PVC insulating cover for use with 319-375, 319-405, 319-417, 248-459, 248-447 and 319-429.

L=38.1, O/S Dia=13.5

204401

Order Multiple=5	5+	100+	Price Each 250+	500+	1K+
Order Code					
152-231●	0.29	0.27	0.26	0.25	0.21

IP66 Sealed - Screwdriver Slot or Finger Release

20 x 5mm Panel Mount

L (overall)=45.3
Dia. (bezel)=17.1
Depth behind panel=27.8
Panel cut-out (single flat)=12.0 x 12.9 dia.
Panel thickness=7.1 max.
Tabs=2.8L (overall) = 44.5
Dis. (bezel) = 20.6
Depth behind panel = 27.8
Panel cut-out (single flat) = 12.0 x 12.9 dia
Panel thickness = 7.1 max.
Tabs = 2.8

'D' type panel mounting fuseholder to BS5490, moulded from glass filled nylon. The IP66 sealing is retained even with the cap removed since the fuseholder is both panel and barrier sealed.

Warning: Tab positions on fuseholder must not be adjusted.Rating 6.3A @ 250V ac
Breakdown voltage 3.5kV @ 50Hz
Insulation resistance ≥1000MΩ @ 500V dcMohm
Operating temperature -20°C to +85°C
Insertion resistance ≤10mΩ

Mfrs. List No. FX0345 Screwdriver release, FX0365 Finger release

204580

	Order Code	1+	100+	Price Each 250+	500+	1K+
Screwdriver Release	319-430●	3.63	3.45	3.29	3.05	2.99
Finger Release	319-442●	3.63	3.45	3.29	3.05	2.99

Screw Cap - Low Profile-Snap-in



Anti-rotational, snap-in fixing, moulded in black nylon 66 and IEC257, VDE, CSA and SEMKO approved, UL Recognised. Cap with slot is easily removed using a small coin. Solder tab terminations.

'D' type mounting, Cut out (single flat) 12.0 x 12.8
L (overall)=37 Dia (bezel)=16, Depth behind panel=35
Panel thickness=0.8 to 2.0, Panel keyway=1.8 x 1.2
Panel cutout=12.8Rating 6.3A @ 250V ac
Operating temperature -55°C to +70°C

Mfrs. List No. T0340RA = 148-827, T0340RD = 147-910,

204575

Order Code	1+	100+	Price Each 250+	500+	1K+
Key-Way Mounting					
148-927●	1.23	1.06	1.03	0.97	0.93
D' Type Mounting					
147-910●	1.14	1.06	0.90	0.73	0.69

Bayonet Cap

L (overall)=45.7
Dia (bezel)=15.0
Dia (body)=12.7
Depth behind panel=40.2Panel cutout (double flat)=11.7 x 12.7
Panel cutout (single flat)=12 x 12.7
Panel Thickness=9.0 max
Tabs=4.8

- Black thermoplastic construction
- UL94V-0
- Approved to IEC257, VDE, SEMKO and CSA, UL Recognised

- Sealed to IP40
- Fuse body and individual carriers are ordered separately to offer choice of 20 x 5mm or 1/4" x 1/4" fuses

Rating 16A @ 250V ac UL, CSA
10A @ 250V ac VDE, SEMKO
Mfrs. List No. 81100000005
80000000005
800 01Order Code 951-6409
951-6395
127-1649Operating temperature -25°C to +70°C
Breakdown voltage 4kV @ 50HzMfrs. List No. 81500000005
81600000005
Order Code 951-6417
951-6425

204584

Order Multiple=5	Order Code	5+	50+	100+	500+
Fuse Body					
Fuse body, Vertical PCB	951-6409●	0.92	0.83	0.71	0.50
Fuse body, Panel	951-6395●	0.92	0.83	0.76	0.54
Fuseholder 6.3 x 32mm	127-1649●	0.84	0.76	0.70	0.64
Fuse Carrier					
20 x 5 mm Carrier	951-6417●	0.72	0.65	0.61	0.56
1/4" x 1/4" Carrier	951-6425●	0.77	0.70	0.55	0.41

5 x 20 mm PCB Mount Fuseholders

Finger Release Bayonet Cap



Horizontal and Vertical Styles



- Moulded in black polycarbonate
- Feature a nylon finger release bayonet cap with screwdriver slot
- CSA, SETI and SEMKO approved, UL Recognised

Length (body and cap)=33.1,
Length (body only)=28.1
Diameter=12 with 11.7 flat, Cap diameter=10.0
Operating temperature 218°C max.

Rating 6.3A @ 250V ac

Operating temperature

218°C max.

Mfrs. List No. MCHTC45M (vertical), MCHTC50M (horizontal)

204503

Order Multiple=5


	Order Code	5+	50+	100+	500+	1K+
Horizontal	149-185●	0.63	0.57	0.55	0.53	0.48
Vertical	149-187●	0.81	0.71	0.61	0.53	0.48

Vertical and Horizontal Mount

EPG4 and FPG5 Series



Length overall = 32
(Finger release 37)
Height above PCB=12.7
Drilling plan



Height overall=37.8 (finger release 42.8)
Height above PCB=32.6 (Finger release 37.6)
Base 12.5 x 12.5, Drilling 4 holes 7.62 x 5.08 x 1.3 dia

- Vertical or horizontal pcb mount
- Available in screw driver or finger release
- Bayonet cap carriers
- Compact design
- Shock safe category PC2
- UL recognised, VDE, SEV, SEMKO and CSA approved


Rating	10A @ 250V - VDE, SEMKO and SEV	Contact resistance	≤5mΩ @ 20mV/mohm
	16A @ 250V - UL and CSA	Max. power dissipation	2.5W @ 40°
Materials	PBTP thermoplastic UL94V-0		
Operating Temp.	-40 to +85°C	Contacts	Copper Alloy
Mfrs. List No.	3101.0040 = 122-2690 3101.0045 = 122-2691		
	3101.0050 = 122-2692 3101.0055 = 122-2693		

204495

Order Multiple=5	Order Code	5+	Price Each	50+	100+
Vertical Mount (FPG4)					
Screwdriver release	122-2690●	0.83	0.77	0.72	
Finger release	122-2691●	0.83	0.77	0.72	
Horizontal Mount (FPG5)					
Screwdriver release	122-2692●	0.83	0.77	0.72	
Finger release	122-2693●	0.83	0.77	0.72	

Vertical Fuse Holder

For 5 x 20 mm fuses



Vertical mounting fuse holder for printed circuit board mounting with 10 mm grid connections.

Rated Voltage: 250V
Rated Current: 6.3A
Test Voltage: 3000V
IP rating: IP40


Holder - H = 27, W = 13, D = 12mm
Cap - H = 18.5, Dia. = 11mm

381331

Description	Mfrs. List No.	Order Code	1+	Price Each	10+	50+	100+
Fuse holder	598	127-1670●	1.65	1.36	1.16	1.04	
Cap	585	127-1668●	1.00	0.83	0.73	0.62	

Touchproof® Bayonet Cap - Horizontal

20 x 5mm PCB Mount



Designed to BS3042 for user safety with black polyester moulded body and nylon cap/end bung. Contacts are silver plated brass. Approved to CSA, VDE, SEMKO, UL Recognised and conforms to IEC257.

Rating 10A @ 250V ac Operating temperature -20°C to +100°C
Breakdown voltage 4kV @ 50Hz

Mfrs. List No. FX0457 = 149-920, FX0456 = 149-919


204583

Order Code	1+	100+	Price Each	250+	500+	1K+
Horizontal						
149-920●	1.47	1.43	1.21	1.18	1.16	
Vertical						
149-919●	1.47	1.43	1.21	1.18	1.16	

Finger Release/Screw Cap - Horizontal



H=13.1
L (overall)=31.7
Dia (bezel)=12.7
Dia (cap)=10.3
Depth behind panel=25
Panel cutout=12.7
Panel thickness=7.1 max



PCB drilling plan

Moulded in a glass filled nylon. The body fixes direct to the PCB whilst the fuse carrier knob protrudes through a circular panel hole.

Rating 6.3A @ 250V ac
Operating temperature -20°C to +100°C

Mfrs. List No. FX0330A

204582

Order Code	1+	100+	Price Each	250+	500+	1K+
149-865●	1.97	1.29	1.05	0.90	0.88	

PCB Through Hole Mount

FUP Series



- High Current Capacity
- Horizontal Style
- Standards - IEC 60127-6, UL 512 & CSA C22.2 no. 39
- VDE Approved, UL Recognised

H = 19.5, Dia. (Head) 19, D= 54.8mm


Power Rating 4W @ 16A - 23°C Rated Current 16A @ 250V (VDE), 16A (UL/CSA)
Materials Thermoplastic - IP 40 Contacts Copper Alloy
Operating temperature -40°C to +85°C Fuse Sizes 20 x 5mm & 32 x 6.3mm

Mfrs. List No: 0031.2510 = 122-1098 0031.2520 = 122-1099

439792

Screwdriver release	Order Code	1+	Price Each	10+	50+
Fuse Size					
20 x 5mm	122-1098●	8.31	7.90	7.49	
32 x 6.3mm	122-1099●	8.31	7.90	7.49	

Fuse Clips



PCB drilling plan

Hot tin dipped, hard brass fuse clips. Each clip has two mounting lugs suitable for 0.1" matrix board use.

Rating 6.3A (dependent on track size of PCB)

Mfrs. List No. HTC210M

204588

200 Per Pack	Order Code	1+	50+	Price Per Pack	125+	250+	500+	1K+
Order Code								
926-851●	4.39	3.97	3.63	3.24	3.03	2.87		

Type 520/521

5x20 mm



Fuse clips for 5x20 mm fuses, 520 Series with standard pinning - 521 Series with pins offset through 90°.

Pin pitch: 4.8/4.6mm
Pins: 1.3x1.2mm
Material: Copper alloy, tinned
Rated Voltage: 250V
Rated Current: 6.3A

347358

Mfrs. List No.	Order Code	1+	Price Per Pack (100 pcs.)	10+	25+	+
520.	127-1651●	6.920	6.170	5.560	--	--
521	127-1652●	4.616	4.511	4.411	--	--

Typ OGD



- Combined fuse holder - Accepts 5 x 20 or 6.3 x 32mm fuse links
- Impossible to insert two fuse links at the same time
- Insulated walls to reduce the risk of electric shock
- Terminals tin plated for optimized soldering on PCB
- "Kicked" terminal and SMD versions available
- Clip ends prevent axial fuse link movement

Pin layout = 5 x 20mm, hole Ø = 1.4mm
H = 12.7, W = 38, D = 10.9mm

Rated voltage	250V (UL 500V)	Contact resistance	2.5≤mohm
Materials: socket	Thermoplastic, UL94V-0	Insulation resistance	kV3 @ 50Hz, 1min.
Clips	Copper-alloy, tin plated	Solderability	235°C/2s
Rated current	10A	Approvals	VDE/CSA/SEV
Operating temperature	-25°C to 85°C		UL Recognised



5 x 20 mm PCB Mount Fuseholders - continued

Typ OGD - continued

240358

Mfrs. List No.	Order Code	1+	10+	50+	100+
	116-2725 ●	0.38	0.35	0.34	0.30
	SMD 113-9748 ●	0.41	0.33	0.29	0.25
Cover	117-6775 ●	0.39	0.35	0.31	0.30

PCB Through Hole Mount
FUA SeriesSCHURTER
ELECTRONIC COMPONENTS

H = 61.1, Dia. = 19mm

- 500V ac approved at VDE
- High power rating - 4W @ 16A @ 23°C
- Vertical Style
- Slot release
- IP 40
- Standards - IEC 60127-6, UL 512 & CSA C22.2 no. 39
- Meets requirements of glow wire tests according to IEC 60695-2-11 to 13
- VDE Approved, UL Recognised

New

Power Rating 4W / 16A @ 23°C Shocksafe Category PC2
 Rated Current 16A (VDE), 30A (UL/CSA) Materials Black Thermoset - UL 94V-0
 Rated Voltage 500V ac (VDE), 250V ac (UL/CSA) Operating temperature -40°C to +85°C

522141

Fuse Size	Mfrs. List No.	Order Code	1+	10+	50+	100+	+
5 x 20mm	0031.2560	163-7513 ●	5.88	5.52	5.17	4.70	--
6.3 x 20mm	0031.2570	163-7515 ●	5.88	5.52	5.17	4.70	--

Fuse Clip - PCB Mount
For 6.3 x 32mm Fuses

Littelfuse

Pin spacing 7.6mm
 Dimensions - Solder pins 0.5 x 1.5mm
 Material Copper alloy, tinned
 Voltage rating 500V
 Current - Max. 10A

347207

Mfrs. List No.	Order Code	1+	10+	50+	100+
10207101009	118-5356 ●	0.47	0.46	0.42	0.35

Typ OGN

SCHURTER
ELECTRONIC COMPONENTS

- Low profile with insulated walls
- "Kicked" tin plated PCB terminals
- Screw or rivet fixing

PCB hole Ø = 1.3mm

Rated voltage 250V Contact resistance 5≤mohm
 Material: socket Thermoplastic, UL94V-0 Dielectric strength kV6 @ 50Hz, 1min.
 Clips Copper alloy, tin plated Solderability 235°C/2s
 Rated current 10A Approvals CSA
 Operating temperature -40 to 85°C UL Recognised

240367

Mfrs. List No.	Pin Spacing	Order Code	1+	10+	50+	100+
0031.8201	22.5mm	116-2740 ●	0.194	0.172	0.151	0.141
0031.8211	25mm	116-2741 ●	0.340	0.240	0.184	0.172
Transparent cover						
0853.0551		117-6774 ●	0.200	0.149	0.130	0.103

Open with Cover
20 x 5mm PCB Mount

multicomp

146-123
 Fuseholder
 H=15, W=9.0, D=23
 F.C.=22.3 x 1.5
 Fixing hole=2.9



146-124
 Cover
 H=15, W=9.0, D=26.5

Manufactured in a glass filled thermoplastic with central fixing hole. A plastic cover is available, transparent to allow visual inspection.

UL Recognised

Rating 6.3A @ 250V
 Breakdown voltage 2.5kV
 Operating temperature 75°C max (holder)
 75°C max (cover)

Mfrs. List No. Holder MCHTE15M
 Transparent cover MCHTC150M

204589

Order Multiple=10

	Order Code	10+	100+	500+	1K+
Holder	146-123 ●	0.121	0.080	0.067	0.065
Transparent cover	146-124 ●	0.053	0.039	0.037	0.036

Open

Dialight
BLP

Open fuseholder with a synthetic resin bonded paper base.

Rating 6.3A Operating temperature -40°C to +40°C
 Breakdown voltage >3kV

H=9.5, W=6.4, D=23.8
 Fixing centres=22.9 x 2.0

204593

Mfrs. List No.	Order Code	1+	125+	500+	1K2+
L1426	319-508 ●	1.81	1.52	1.25	1.15

Open

20 x 5mm PCB Mount

BULGIN



Open fuseholder with a glass filled nylon base and matching clear cover.

Fuse Holder	Fuse Cover	Mfrs. List No.	FX0321 = 319-491
H=14.3, W=6.4, D=23.4 Fixing centres=22.9 x 2.0	H=10.9, W=9.6, D=29.0		12760 = 471-677
Rating 6.3A @ 250V ac	Operating temperature 0°C to +90°C		

204591

Order Multiple=5	Order Code	5+	100+	Price Each	250+	500+	1K+
Fuse Holder	319-491 ●	0.520	0.480	0.460	0.440	0.420	
Fuse Cover	471-677 ●	0.198	0.181	0.163	0.145	0.133	

Semi-Enclosed

20 x 5mm PCB Mount

multicomp



Moulded in black glass filled nylon with a small window which allows easy visual inspection of the fuse.

UL Recognised

Rating 5A @ 250V
 Operating temperature -40°C to +110°C

Mfrs. List No. MCHTC-100M

H=11.4, W=9.4, D=24.4,
 F.C.=22.6 pins x 0.5 x 1.2

204590

Order Multiple=10	Order Code	10+	50+	Price Each	100+	500+	2K5+
	976-120 ●	0.24	0.23	0.22	0.21	0.20	

5 x 20mm Fuse Holder

Open

multicomp



- Moulded in beige polyphenylene oxide
- Features a central countersunk fixing hole
- UL Recognised

Length (overall)=39.8
 Length (Body)=22.0, Height=13.5, Width=10.3

Rating 6.3A @ 250V ac Operating temperature 150°C max.

204591

Order Multiple=5	Order Code	5+	25+	Price Each	100+	250+	500+
Mfrs. List No. MCHTC-10M	899-240 ●	0.510	0.340	0.270	0.210	0.188	

Open

BULGIN



Open fuseholder with glass filled nylon paper base and central fixing hole.

FOR SUITABLE CLEAR PLASTIC FUSEHOLDER
 COVER 471-677

H=11.1, W=6.4, D=23.4, Fixing hole=2.3 Tabs=2.8

Rating 250V @ 6.3A Operating temperature 0°C to +90°C

220506


Mfrs. List No.	Order Code	1+	100+	Price Each	500+	1K+
FX0267	319-510●	0.89	0.71	0.66	0.60	0.57

Open



Open fuseholder with glass filled nylon base and central countersunk fixing hole.

H=15.4, W=8.2,
D=23.4
Tabs=2.8




Rating 6.3A @ 250V Operating temperature 0°C to +90°C

204603

Mfrs. List No.	Order Code	1+	100+	Price Each	500+	1K+
FX0360	439-733●	0.63	0.59	0.56	0.53	0.48

5 x 20mm In-Line Fuseholders

Bayonet Fit



Moulded from black nylon with a bayonet locking action.

L=43.2, Dia.=14.2
Wire dia=4.0 max.

Rating 5A @ 50V Operating temperature +85°C max.
Breakdown voltage 2kV Mfrs. List No. A003300

204586

Order Multiple=5	Order Code	5+	50+	Price Each	100+	250+	500+
	152-233●	0.58	0.55	0.50	0.43	0.34	

Screw Fit



Standard
L=50.4, Dia.=15.9,
Wire dia.=4.0 max.

IP66 Sealed
L=78.9, Dia.=16.5
Wire dia.=1.0 to 1.4mm, 1.5 to 1.9mm,
2.0 to 2.64mm dependent
where 3 section grommet is cut.

Moulded from clear polybutene with nickel plated brass grub screw terminations, available in either standard or IP66 sealed versions.

Rating 10A @ 250V Mfrs. List No. FX0380 = 319-480
Operating temperature -20°C to +70°C FX0385 = 272-176

Note: When assembled current must not flow through the spring
250V rated in equipment, otherwise 50V ac/dc

204432

	Order Code	1+	50+	Price Each	100+	250+	500+	1K+
Standard	319-480●	1.24	1.19	1.10	1.04	0.97	0.95	
IP66 Sealed	272-176●	1.90	1.87	1.63	1.53	1.37	1.25	

6.3 x 32mm (1/4" x 1 1/4") (3AG) Fuses and Fuseholders

Ultra Rapid (FF) Ceramic

70-125-40 Series



Ceramic sand filled fuses with very short cut-off time, one tenth of a cycle at 10 times overload, designed to protect thyristors, rectifiers and any semiconductors sensitive from overload.

UL recognised (except 16A)

Voltage Rating (Vn) 700V ac up to 2A Mfrs. List No. 70-125-40 + Rating
Breaking capacity 700V ac 2.5A & above

204383

Order Multiple=10	Order Code	10+	100+	Price Each	500+	1K+
Rating						
1A	117-5102●	1.51	1.35	1.12	0.98	
1.6A	117-5112●	2.20	1.99	1.78	1.70	
2A	117-5103●	2.20	1.99	1.78	1.70	
2.5A	117-5113●	2.20	1.99	1.78	1.70	
3.15A	117-5104●	2.20	1.99	1.78	1.70	
4A	117-5114●	2.20	1.99	1.78	1.70	
5A	117-5106●	2.20	1.99	1.78	1.70	
6.3A	117-5107●	1.26	1.15	1.02	0.98	
8A	117-5108●	1.26	1.15	1.02	0.98	
10A	117-5109●	1.26	1.15	1.02	0.98	
12.5A	117-5110●	1.26	1.15	1.02	0.98	
16A	117-5111●	1.26	1.15	1.02	0.98	

Quick Blow (F) Ceramic

MCF07C Series



- Ceramic cartridge, nickel plated end caps
- Breaking capacity 1000A
- To IEC 127
- Sand filled
- UL Recognised

484464

Order Multiple=10	Order Code	10+	100+	Price Each	500+	1K+
Rating	Mfrs. List No.					
500mA	MCF07C-500MA	143-7133●	0.29	0.28	0.26	0.21
1A	MCF07C-1A	143-7134●	0.29	0.28	0.26	0.21
2A	MCF07C-2A	143-7135●	0.29	0.28	0.26	0.21
3A	MCF07C-3A	143-7137●	0.29	0.28	0.26	0.21
5A	MCF07C-5A	143-7138●	0.29	0.28	0.26	0.21
6A	MCF07C-6A	143-7139●	0.29	0.28	0.26	0.21
8A	MCF07C-8A	143-7140●	0.29	0.28	0.26	0.21
10A	MCF07C-10A	143-7141●	0.29	0.28	0.26	0.21
12A	MCF07C-12A	143-7142●	0.29	0.28	0.26	0.21
15A	MCF07C-15A	143-7143●	0.29	0.28	0.26	0.21
20A	MCF07C-20A	143-7144●	0.34	0.32	0.28	0.24

For 6.3x32mm Fuseholders see page 335

Quick Blow (F) Ceramic

L693 Series



Complies with DEF-59-96

Voltage Rating 440V ac/230V dc
Breaking capacity 33000A @ Vn cos φ = 0.3
Mfrs. List No. L693 + rating

204389

Order Multiple=10	Order Code	10+	100+	Price Each	500+	1K+
Rating						
250mA	968-8064●	1.86	1.49	1.22	0.91	
500mA	968-8072●	1.86	1.49	1.22	0.91	
1A	968-8080●	1.87	1.49	1.22	0.91	
2A	968-8099●	1.86	1.49	1.22	0.91	
3A	968-8102●	1.86	1.49	1.22	0.91	
5A	968-8110●	1.86	1.49	1.22	0.91	
7A	968-8129●	1.86	1.49	1.22	0.91	
10A	968-8137●	1.86	1.49	1.22	0.91	

Quick Blow (F) HRC Ceramic

70-065-63 Series



UL Recognised (up to 6.3A)

Voltage Rating (Vn) 500V ac
Breaking capacity 1500A @ Vn
Mfrs. List No. 70-065-63 + rating

204388

Order Multiple=10	Order Code	10+	100+	Price Each	500+	1K+
Rating						
500mA	117-5115●	0.40	0.37	0.32	0.28	
1A	117-5116●	0.40	0.37	0.32	0.28	
1.25A	143-6838●	0.40	0.37	0.32	0.28	
2A	117-5118●	0.40	0.37	0.32	0.28	
3A	117-5119●	0.40	0.37	0.32	0.28	
4A	143-6839●	0.40	0.37	0.32	0.28	
5A	117-5120●	0.40	0.37	0.32	0.28	
6.3A	117-5124●	0.38	0.35	0.31	0.27	
7A	117-5121●	0.40	0.37	0.32	0.28	
10A	117-5122●	0.40	0.37	0.32	0.28	
12.5A	143-6840●	0.40	0.37	0.32	0.28	
16A	117-5123●	0.40	0.37	0.32	0.28	
20A	143-6841●	0.40	0.37	0.32	0.28	

Quick Blow (F) Glass

MCF01G Series



- Glass cartridge, nickel plated end caps
- To IEC 127
- Axially centred element
- UL Recognised

Breaking capacity @ 250V - 35A (500mA - 1A), 100A (2A - 3A), 200A (4A - 10A)

484503

Order Multiple=10	Order Code	10+	100+	Price Each	500+	1K+
Rating	Mfrs. List No.					
500mA	MCF01G-500MA	143-7145●	0.114	0.102	0.091	0.086
1A	MCF01G-1A	143-7146●	0.114	0.102	0.091	0.086
2A	MCF01G-2A	143-7147●	0.114	0.102	0.091	0.086
3A	MCF01G-3A	143-7149●	0.114	0.102	0.091	0.086
4A	MCF01G-4A	143-7151●	0.114	0.102	0.091	0.086
5A	MCF01G-5A	143-7152●	0.114	0.102	0.091	0.086
6A	MCF01G-6A	143-7153●	0.114	0.102	0.091	0.086
10A	MCF01G-10A	143-7154●	0.114	0.102	0.091	0.086



6.3 x 32mm (1/4" x 1 1/4") (3AG) Fuses and Fuseholders - continued

Quick Blow (F) Glass
TDC10 Series**Bussmann**

Complies with BS2950A

Voltage rating (Vn):	60mA - 250mA 500mA	1000V ac 750V ac	1.5A - 5A 7.5A 10A	350V ac 150V ac 100V ac
Breaking capacity	1A - 1.25A 10 x In @ Vn	350V ac	12A - 25A Mftrs. List No.	32V ac TDC10 + Rating

204395

Order Multiple=10				Price Each	
Rating	Order Code	10+	100+	500+	1K+
60mA	534-869	0.580	0.520	0.480	0.470
100mA	534-870	0.600	0.520	0.490	0.480
150mA	534-882	0.520	0.470	0.440	0.410
250mA	534-894	0.143	0.128	0.123	0.118
500mA	534-900	0.143	0.128	0.123	0.118
1A	534-924	0.116	0.107	0.099	0.095
2A	534-950	0.122	0.110	0.104	0.100
3A	534-973	0.122	0.110	0.104	0.100
5A	534-985	0.122	0.110	0.104	0.100
7.5A	534-997	0.122	0.110	0.104	0.100
10A	535-000	0.122	0.110	0.104	0.100
12A	535-011	0.143	0.120	0.110	0.099
15A	535-023	0.122	0.110	0.104	0.100
20A	535-035	0.143	0.120	0.110	0.099
25A	535-047	0.170	0.143	0.131	0.118

Time Delay (T) Ceramic
MCF08C Series**multicomp**

- Ceramic cartridge, nickel plated end caps
- Breaking capacity 1000A

- To IEC 127
- Sand filled
- UL Recognised

484508

Order Multiple=10			Price Each			
Rating	Mftrs. List No.	Order Code	10+	100+	500+	1K+
1A	MCF08C-1A	143-7156●	0.33	0.30	0.28	0.26
2A	MCF08C-2A	143-7157●	0.33	0.30	0.28	0.26
4A	MCF08C-4A	143-7158●	0.33	0.30	0.28	0.26
5A	MCF08C-5A	143-7159●	0.33	0.30	0.28	0.26
6A	MCF08C-6A	143-7160●	0.33	0.30	0.28	0.26
7A	MCF08C-7A	143-7162●	0.33	0.30	0.28	0.26
10A	MCF08C-10A	143-7163●	0.33	0.30	0.28	0.26
15A	MCF08C-15A	143-7164●	0.33	0.30	0.28	0.26
20A	MCF08C-20A	143-7165●	0.33	0.30	0.28	0.26

6.3mm x 32mm (1/4" x 1-1/4") Fuses

Ceramic - Time Delay

Bussmann

- Time delay fuses
- Ceramic tube, nickel-plated brass endcap
- CSA Approved, UL Recognised

New

515121

Order Multiple = 10				Price Each	
Rating (A)	Mftrs. List No.	Order Code	10+	100+	1K+
0.5	MDA-1/2-R	161-5121●	0.40	0.35	0.31
1	MDA-1-R	161-5122●	0.40	0.35	0.31
1.5	MDA-1-1/2-R	161-5123●	0.40	0.35	0.31
2	MDA-2-R	161-5124●	0.40	0.35	0.31
3	MDA-3-R	161-5125●	0.40	0.35	0.31
4	MDA-4-R	161-5126●	0.40	0.35	0.31
5	MDA-5-R	161-5127●	0.40	0.35	0.31
6	MDA-6-R	161-5128●	0.40	0.35	0.31
8	MDA-8-R	161-5131●	0.40	0.35	0.31
10	MDA-10-R	161-5132●	0.40	0.35	0.31
12	MDA-12-R	161-5133●	0.40	0.35	0.31
15	MDA-15-R	161-5134●	0.40	0.35	0.31
20	MDA-20-R	161-5135●	0.40	0.35	0.31
25	MDA-25-R	161-5136●	0.40	0.35	0.31
30	MDA-30-R	161-5137●	0.40	0.35	0.31

Antisurge (T), Ceramic
70-065-65 Series**SIBA**

- UL Recognised up to 16A

Voltage Rating (V)	500V ac (up to 10A)	Maximum voltage drop	800-150mV
--------------------	---------------------	----------------------	-----------

Please note that when using 8A or over, consideration should be given to heat dissipation

Mftrs. List No. 70-065-65 + Rating

204524

Order Multiple=10		Price Each				
Rating	Order Code	10 +	100+	500+	1K+	3K+
500mA	117-5139●	0.38	0.35	0.33	0.32	0.31
1A	117-5140●	0.38	0.35	0.33	0.32	0.31
1.6A	143-6842●	0.38	0.35	0.33	0.32	0.31
2A	117-5141●	0.38	0.35	0.33	0.32	0.31
2.5A	117-5143●	0.38	0.35	0.33	0.32	0.31
3.15A	117-5144●	0.38	0.35	0.33	0.32	0.31
4A	117-5145●	0.38	0.35	0.33	0.32	0.31
5A	117-5146●	0.38	0.35	0.33	0.32	0.31
6.3A	117-5147●	0.38	0.35	0.33	0.32	0.31
8A	117-5148●	0.38	0.35	0.33	0.32	0.31
10A	117-5149●	0.38	0.35	0.33	0.32	0.31
12.5A	117-5150●	0.38	0.35	0.33	0.32	0.31
16A	117-5151●	0.38	0.35	0.33	0.32	0.31
20A	117-5152●	0.92	0.84	0.80	0.77	0.67
25A	117-5153●	1.07	0.96	0.89	0.85	0.77
32A	117-5155●	1.45	1.31	1.20	1.15	1.04

Time Delay (T) Glass

multicomp

MCF02G Series



- Glass cartridge, nickel plated end caps
- To IEC 127
- Axially centred element
- UL Recognised

Breaking capacity @ 250V - 35A (125mA - 1A), 100A (2A - 3A), 200A (4A - 10A)

484517

Order Multiple=10			Price Each			
Rating	Mftrs. List No.	Order Code	10+	100+	500+	1K+
125mA	MCF02G-125MA	143-7166●	0.210	0.194	0.181	0.170
500mA	MCF02G-500MA	143-7167●	0.210	0.194	0.181	0.170
1A	MCF02G-1A	143-7168●	0.210	0.194	0.181	0.170
2A	MCF02G-2A	143-7169●	0.210	0.194	0.181	0.170
3A	MCF02G-3A	143-7170●	0.210	0.194	0.181	0.170
4A	MCF02G-4A	143-7171●	0.210	0.194	0.181	0.170
5A	MCF02G-5A	143-7172●	0.210	0.194	0.181	0.170
6A	MCF02G-6A	143-7174●	0.210	0.194	0.181	0.170
8A	MCF02G-8A	143-7175●	0.210	0.194	0.181	0.170
10A	MCF02G-10A	143-7176●	0.210	0.194	0.181	0.170

Antisurge (T) Glass - Spring Element

Bussmann

TDC11 Series



Voltage Rating (Vn) 1000V ac
Breaking capacity 10 x In @ Vn
Mftrs. List No. TDC11 + rating

204415

Order Multiple=10				Price Each	
Rating	Order Code	10+	100+	500+	1K+
250mA	539-983	0.47	0.43	0.41	0.39
500mA	539-995	0.47	0.43	0.41	0.39
750mA	540-018	0.45	0.41	0.39	0.37
1A	540-031	0.45	0.41	0.39	0.37
1.25A	540-043	0.63	0.58	0.55	0.52
1.5A	540-055	0.72	0.66	0.62	0.59
2A	540-067	0.71	0.65	0.62	0.59
2.5A	540-079	0.72	0.66	0.62	0.59
3A	540-080	0.72	0.66	0.62	0.59
5A	540-092	0.70	0.64	0.61	0.58

Finger Release/Screw Cap

Dialight BLP

L (overall) = 58.8
Dia. (Bezel) = 17.4
Depth behind panel = 46.8
Panel cutout (single flat) = 11.5 x 12.7 dia
Panel thickness = 7.9
Tabs = 6.3 x 0.8

'D' type panel mounting fuseholder moulded in black phenolic.

Rating	10A	Operating temperature	-55°C to +70°C
Breakdown voltage	>4kV dc		
Mftrs. List No.	L1744A		

204600

Order Code	1+	50+	200+	500+	1K+
968-7807●	5.66	4.59	3.85	3.32	2.93

Screw Cap

Dialight BLP

Moulded in black phenolic, with screw cap with slot which is easily removed using a small coin. Solder tab terminations.

L (overall) = 58.1
Dia. (Bezel) = 16.5
Depth behind panel = 50.8
Panel cutout (double flat) = 14.7 x 16.3
Panel keyway = 3.6 x 1.2
Panel thickness = 10

Rating	7A (15A @ 55°C max ambient)	Breakdown voltage	>9kV dc
		Operating temperature	-25°C to +100°C

Mfrs. List No.	Order Code	1+	50+	250+	500+
L1348C	968-7793●	5.52	4.62	4.01	2.73

Finger Release/Screw Cap



Moulded in black phenolic and conforming to **BT136F1** and **DEF59-100**. Solder tab terminations.

L (overall) = 54
Dia. (Bezel) = 21.9
Depth behind panel = 38.1
Panel cutout (double flat) = 14.7 x 16.1
Panel thickness = 4 max.
Tabs = 6.3 x 0.8

Rating 7A (15A @ 55°C max ambient)
Breakdown voltage >10kV dc
Operating temperature -55°C to +70°C

Mfrs. List No.	Order Code	1+	50+	200+	500+
L1382	319-600●	23.06	19.65	15.91	13.17

Coin Slot Release
Size 0 Fuse Link

This fuseholder is designed for use with size 0 fuse links. It is fully finger proof having a special inner sleeve, which prevents accidental contact when the fuse link is inserted. It has been designed to meet the safety requirements of IEC 257 and BS 415. Mounting on the panel is by a single hole shaped to engage the anti-swivel flats on the fuseholder. Connection is achieved by either 6.3 x 0.81mm or 4.75 x 0.81mm solderless snap on connectors. Supplied with a removable snap on black bezel, which fits over the front flange. **UL Recognised, CSA, SEMKO and VDE Approved.**

L (body) = 40.5mm
Depth in-front of panel = 13.5mm
L (overall) finger = 19.1
Breakdown voltage >4kV
Mfrs. List No. L2004A = 120-7148

Panel cutout = 14.8mm across flats, 16.2mm Max.
Bezel = 19.1 x 19.1mm
Max. Panel thickness = 4mm
Operating temperature -25°C to +85°C

Order Code	1+	50+	200+	500+	+
120-7148●	5.90	5.62	5.04	4.91	--

20A - Touchproof™



- Low profile panel mounting Touchproof™ fuseholder to **IEC 127/6** category **PC2**
- Screw cap, screwdriver release
- 6.3mm fast-on tags

L (overall) = 58, Dia. (Bezel) = 19.1
Depth behind panel = 54.9, Panel cut-out = 16
Panel thickness = 1 to 8

Rating @ 250V 16A SEMKO, VDE 20A UL, CSA
Breakdown voltage >2kV
Max power dissipation 2.5W
Mfrs. List No. FX0417

Order Code	1+	50+	100+	250+	500+
Screwdriver release 535-953●	2.79	2.64	2.39	1.99	1.95

Touchproof™ - Screw Cap



L (overall) = 65.9, Dia. (Bezel) = 19.1
Depth behind panel = 54.4
Panel cut-out = 16
Panel keyway = 2.5 x 1.2
Panel thickness = 0.8 to 5.5, Tabs = 4.8

L (overall) = 60.4, Dia. (Bezel) = 19.1
Depth behind panel = 54.4
Panel cut-out = 16
Panel keyway = 2.54 x 1.3
Panel thickness = 0.8 to 5.5, Tabs = 4.8

Moulded in glass filled nylon, **UL Recognised**, and conforming to **IEC257**.

Rating 13A @ 250V ac
Breakdown voltage 4kV ac @ 50Hz
Mfrs. List No. FX0415 = 319-570 FX0415/S = 319-582

Order Code	1+	100+	250+	500+	1K+
319-570●	2.09	1.97	1.89	1.81	1.72
319-582●	2.05	1.93	1.85	1.77	1.68

Touchproof® Screw Cap
Panel Mount, IP67

Designed for user safety, touchproof category PC2 with polyester moulded body and nylon cap/end bung. The screw cap can be either screwdriver or hand released. Contacts are silver plated brass. Approved to **CSA, VDE, SEMKO. UL Recognised**

6.3 x 32mm
Fuse Size 6.3 x 32mm
Terminations 6.35mm x 0.8mm
Max. Rating: 16A @ 250V
Mfrs. List No. FX0419=963-0180

Max. Power Dissipation 20A @ 250V UL
Operating Temperature 4W @ 23°C
-20 to 85°C

Fuse Type	Order Code	1+	25+	100+	250+
6.3 x 32mm	963-0180●	2.45	2.33	2.21	2.08

Snap-In - Keyway Panel Mounting



Anti-rotational, snap-in fixing moulded in black Nylon 66. Cap with slot is easily removed using a small coin. **UL Recognised, CSA and SEMKO approved.**

L (overall) = 54.1
Dia. (Bezel) = 19.5
Depth behind panel = 51.1
Panel thickness = 0.8 to 2
Panel cutout = 16.05
Panel keyway = 2.5 x 1.3
Tabs = 6.3 x 0.8

Order Code	1+	100+	250+	500+	1K+
149-862●	1.94	1.71	1.36	1.03	1.01

Typ OGD



- Combined fuse holder - Accepts 5 x 20 or 6.3 x 32mm fuse links
- Impossible to insert two fuse links at the same time
- Insulated walls to reduce the risk of electric shock
- Terminals tin plated for optimized soldering on PCB
- "Kicked" terminal and SMD versions available
- Clip ends prevent axial fuse link movement

Pin layout = 5 x 20mm, hole Ø = 1.4mm
H = 12.7, W = 38, D = 10.9mm

Rated voltage 250V (UL 500V)
Materials: socket Thermoplastic, UL94V-0
Clips Copper-alloy, tin plated
Rated current 10A
Operating temperature -25°C to 85°C

Contact resistance 2.5≤mohm
Insulation resistance kV3 @ 50Hz, 1min.
Solderability 235°C/2s
Approvals VDE/CSA/SEV
UL Recognised

Mfrs. List No.	Order Code	1+	10+	50+	100+
0031.8241	116-2725●	0.38	0.35	0.34	0.30
Cover	113-9748●	0.41	0.33	0.29	0.25
	117-6775●	0.39	0.35	0.31	0.30

PCB Through Hole Mount
FUP Series

- High Current Capacity
- Horizontal Style
- Standards - **IEC 60127-6, UL 512 & CSA C22.2 no. 39**
- **VDE Approved, UL Recognised**

H = 19.5, Dia. (Head) 19, D = 54.8mm

Power Rating 4W @ 16A - 23°C
Materials Thermoplastic - IP 40
Operating temperature -40°C to +85°C
Mfrs. List No: 0031.2510 = 122-1098 0031.2520 = 122-1099

Rated Current 16A @ 250V (VDE), 16A (UL/CSA)
Contacts Copper Alloy
Fuse Sizes 20 x 5mm & 32 x 6.3mm

Screwdriver release Fuse Size	Order Code	1+	10+	50+
20 x 5mm	122-1098●	8.31	7.90	7.49
32 x 6.3mm	122-1099●	8.31	7.90	7.49

1/4" x 1-1/4" Fuseblocks
S - 8000 Series

- Designed for 1/4" x 1-1/4" Fuses (6.35mm x 31.8mm)
- Bolt-in mounting
- Clips made from spring bronze
- Anti-rotational pin
- Flame retardant thermoplastic UL 94 V0
- Voltage Rating 300V ac/dc
- Temperature Rating (RTI) 130°C



6.3 x 32mm (1/4" x 1 1/4") (3AG) Fuses and Fuseholders - continued

1/4" x 1-1/4" Fuseblocks - continued

S - 8000 Series - continued

Poles	Description	Terminal Method	Dimensions (mm)			Mfrs. List No.	Order Code
			H	W	D		
1	Straight	6.35mm x 0.8mm	14.3	12.7	54.8	S-8201-1-R	161-5106
2	Straight	6.35mm x 0.8mm	14.3	28.6	54.8	S-8201-2-R	161-5107
3	Straight	6.35mm x 0.8mm	14.3	44.4	54.8	S-8201-3-R	161-5108
10	Straight	6.35mm x 0.8mm	14.3	155.6	54.8	S-8201-10-R	161-5109
1	40° Angle	6.35mm x 0.8mm	14.3	12.7	50.8	S-8202-1-R	161-5110
2	40° Angle	6.35mm x 0.8mm	14.3	28.6	50.8	S-8202-2-R	161-5111
3	40° Angle	6.35mm x 0.8mm	14.3	44.4	50.8	S-8202-3-R	161-5112
10	40° Angle	6.35mm x 0.8mm	14.3	155.6	50.8	S-8202-10-R	161-5113
1	Screw		14.3	12.7	55.6	S-8301-1-R	161-5114
2	Screw		14.3	28.6	55.6	S-8301-2-R	161-5115
3	Screw		14.3	44.4	55.6	S-8301-3-R	161-5116
10	Screw		14.3	155.6	55.6	S-8301-10-R	161-5118

515076

Poles No. of	Mfrs. List No.	Order Code	1+	10+	100+
1	S-8201-1-R	161-5106●	2.04	1.91	1.63
2	S-8201-2-R	161-5107●	3.87	3.63	3.08
3	S-8201-3-R	161-5108●	5.45	5.13	4.37
10	S-8201-10-R	161-5109●	20.12	18.92	16.10
1	S-8202-1-R	161-5110●	1.55	1.46	1.23
2	S-8202-2-R	161-5111●	3.92	3.67	3.13
3	S-8202-3-R	161-5112●	5.83	5.47	4.66
10	S-8202-10-R	161-5113●	19.22	18.06	15.38
1	S-8301-1-R	161-5114●	5.78	5.42	4.62
2	S-8301-2-R	161-5115●	12.32	11.58	9.86
3	S-8301-3-R	161-5116●	18.03	16.95	14.43
10	S-8301-10-R	161-5118●	49.34	46.38	39.47

Open



Rating 13A @ 250V ac
Breakdown voltage >5kV @ 50Hz

Manufactured from black phenolic with tin plated phosphor bronze contact clips.



Centre fixing hole = 3.2 dia.
Outer pin locating holes = 3.5 dia. Tabs = 6.35
Operating temperature -40°C to +70°C
Mfrs List No. FX0326

204605

Order Code	1+	100+	Price Each	250+	500+	1K+
149-918●	1.00	0.93	0.89	0.85	0.76	

Bayonet Fit



Rating 5A @ 50V Mfrs List No.

Moulded from natural colour nylon, conforming to UL94V-2.

L = 58.2
Dia = 15.2
Wire dia. = 4.0 max.

A003500AAB

204602

Order Multiple = 5	Order Code	5+	50+	Price Each	100+	250+	500+	1K+
149-866●		0.46	0.44	0.43	0.39	0.36	0.31	

Screw Fit - Black



Rating 10A @ 250V ac
Operating temperature -20°C to +50°C



Moulded in black polythene with grub screw terminations of nickel plated brass.

L = 61.9 Dia. = 15.9 Wire dia. = 4.0 max.

Mfrs List No. FX0180/BK

204604

Order Code	1+	50+	Price Each	100+	250+	500+	1K+
319-624●	1.93	1.41	1.08	0.89	0.78	0.71	

Screw Fit



Standard
L = 61.9, Dia. = 15.9,
Wire dia. = 4.0 max.

IP66 Sealed
L = 90.6, Dia = 15.5
Wire dia. = 1.0 to 1.4mm, 1.5 to 1.9mm,
Wire dia. = 2.0 to 2.64mm dependent
where grommet is cut.

Moulded from clear polybutene with nickel plated brass grub screw terminations and available in either standard or IP66 sealed versions.

Rating 10A @ 250V ac Mfrs. List No.
Operating temperature -20°C to +70°C (319-612) FX0180 = (319-612)
Operating temperature -20°C to +70°C (272-188) FX0185 = (272-188)

Note: When assembled current must not flow through the spring
250V rating in equipment, otherwise 50V ac/dc

204431

	Order Code	1+	50+	Price Each	100+	250+	500+
Standard	319-612●	1.18	1.13	1.03	0.98	0.94	
IP66 Sealed	272-188●	1.74	1.65	1.48	1.33	1.30	

1/4" x 1-1/4" Fuseholder Waterproof - In-Line



161-5103



161-5104

Rugged Version resistant to:

- Salt Spray
- Ultraviolet Light

- Designed for 1/4" x 1-1/4" Fuses (6.35mm x 31.8mm)
- Flammability rating UL 94 HB

- Ozone
- Many organic solvents

- Rigorous Shock and Vibration

515058

Description	Rating	Mfrs. List No.	Order Code	1+	Price Each	50+	250+
Black	20A @ 250V	HFA-R	161-5103●	11.06	9.73	8.38	
Rugged - Yellow	30A @ 32V ac	HFB-R	161-5104●	3.68	3.24	2.79	

Fuse Boxes



L1045C3
H = 34.2, W = 61.9, D = 20.6
Fixing centres = 9.5 x 4.0 dia.

L1033C4
H = 35.7, W = 35.7, D = 63.5
Fixing centres = 13.5 x 4 dia.

Moulded in black phenolic, the fuses are held in the lid and automatically isolated from the circuit when the lid is raised. Screw terminations.

Rating 10A
Breakdown voltage 4kV dc (to chassis)
Operating temperature -40°C to +85°C

Mfrs. List No.

L1045/C3 = 319-650

L1033/C4 = 319-661

204607

	Order Code	1+	25+	Price Each	100+	250+
Single fuse box	319-650●	14.24	11.94	10.22	8.65	
Double fuse box	319-661●	20.91	18.67	15.53	13.43	

6.35 x 25.4mm (1" x 1/4") Fuses and Fuseholders

Mains Quick Blow Ceramic TDC180 Series



- Available in bulk pack of 1000 fuses

Voltage Rating (Vn) 250V ac
Breaking capacity 6000A @ Vn

Mfrs. List No. Single: TDC180 + Rating
Bulk: BK/TDC180 + Rating



Complies with
BS1362: 1973
ASTA Certified -
2A to 13A.

204381

Rating	Order Code	Price Each			
		10+	100+	500+	1K+
1A	112-3029●	0.240	0.220	0.210	0.200
2A	112-3032●	0.153	0.136	0.130	0.125
3A	112-3033●	0.153	0.136	0.130	0.125
5A	112-3034●	0.153	0.136	0.130	0.125
7A	112-3035●	0.153	0.136	0.130	0.125
10A	112-3030●	0.153	0.136	0.130	0.125
13A	112-3031●	0.153	0.136	0.130	0.125
Bulk Packs		Price Per Pack			
Rating		1+	2+	3+	
1A	112-3021●	89.020	84.830	83.500	
3A	112-3025●	82.440	78.580	77.330	
5A	112-3027●	82.440	78.580	77.330	
7A	112-3028●	80.110	76.360	75.150	
13A	112-3023●	82.440	78.580	77.330	

Finger or Tool release

Mains 13A Rated - Screw Cap




Accepts standard (BS1362) plug-top fuses to 13A. The fuse sleeve is of black phenolic whilst the body and cap are glass filled nylon. UL Recognised and conforms to IEC257.

L (overall) Tool = 60.4	L (overall) finger = 65.9	Dia. (Bezel) = 19.1
Depth behind panel = 54.4	Panel cutout = 16	Panel thickness = 0.8 to 5.5, Tabs = 4.8
Breakdown voltage	4kV @ 50Hz	Operating temperature -20°C to +100°C
Mfrs. List No.	FX0416 = 152-232	FX0416S = 319-557

204402

	Order Code	Price Each			
		1+	100+	250+	500+
Finger release	152-232●	2.35	2.03	1.66	1.25
Tool release	319-557●	2.34	1.99	1.64	1.37

Fuse Clips



Tin plated phosphor bronze fuse clips. Each clip has two mounting lugs and ear stops.

204416

100 Per Pack	Order Code	Price Per Pack			
		1+	25+	100+	250+
	117-5125●	5.31	5.16	4.99	4.85

PCB Through Hole Mount

FUP Series



- High Current Capacity
- Horizontal Style
- Standards - IEC 60127-6, UL 512 & CSA C22.2 no. 39
- VDE Approved, UL Recognised

H = 19.5, Dia. (Head) 19, D = 54.8mm

Power Rating	4W @ 16A - 23°C	Rated Current	16A @ 250V (VDE), 16A (UL/CSA)
Materials	Thermoplastic - IP 40	Contacts	Copper Alloy
Operating temperature	-40°C to +85°C	Fuse Sizes	20 x 5mm & 32 x 6.3mm
Mfrs. List No:	0031.2510 = 122-1098	0031.2520 = 122-1099	

439792

Screwdriver release	Order Code	Price Each		
		1+	10+	50+
Fuse Size				
20 x 5mm	122-1098●	8.31	7.90	7.49
32 x 6.3mm	122-1099●	8.31	7.90	7.49

Screw Fit



Standard
L = 54.5, Dia. = 15.5, Wire dia. = 4.0

IP66 Sealed
L = 85.2, Dia. = 15.9,
Wire dia. = 1.0 to 1.4mm, 1.5 to 1.9mm,
2.0 to 2.64mm dependant where grommet is cut.

Moulded from clear polybutene with nickel plated grub screw terminations available in either standard or IP66 sealed versions.

Rating	10A @ 250V ac	Mfrs. List No.	FX280 = 287-120
Operating temperature	-20°C to +70°C		FX285 = 287-131

Note: 250V rating in equipment, otherwise 50V ac/dc

204436

	Order Code	Price Each				
		1+	50+	100+	250+	500+
Standard	287-120●	1.37	1.22	1.17	1.06	1.04
IP66 Sealed	287-131●	1.72	1.69	1.47	1.26	1.24

4.7 x 15.9mm (5/8" x 3/16") (Size 00) Fuses and Fuseholders

Quick Blow Glass

L562 Series



Voltage rating (Vn)	up to 500mA	250V ac
Breaking capacity	1A, 2.5A	150V ac
Mfrs. List No.	4A - 7A	60V ac
	35A @ Vn	
	L562 + Rating	

204380

Order Multiple=10	Rating	Order Code	Price Each			
			10+	100+	500+	1K+
	50mA	968-7971●	1.38	1.15	1.01	0.82
	100mA	968-7980●	2.06	1.41	1.29	1.11
	250mA	968-7998●	1.61	1.47	1.29	1.09
	500mA	968-8005●	1.13	0.96	0.82	0.70
	1A	968-8013●	1.13	0.98	0.84	0.77
	2.5A	968-8021●	1.13	0.98	0.84	0.77
	4A	968-8030●	1.13	0.98	0.84	0.77
	5A	968-8048●	1.20	1.02	0.90	0.83
	7A	968-8056●	1.29	1.09	0.91	0.79

Miniature PCB Mount

HRC Ceramic - Slow Blow



Dia. = 4.7, W = 16.6, Height (Above PCB) = 6.3mm

These fuse links are designed for direct mounting into printed circuit boards. The HRC ceramic fuselinks protect against high prospective overload currents and are therefore suited for applications within hazardous environments such as those encountered in the petro-chemical and mining industries. The fuse rating is marked on the body in such a position to be visible when the fuselink is mounted on the PCB.

Breaking capacity	4000A @ 0.4 power factor, 250V ac, 230V dc
Operating temperature	-60°C to +85°C

Mfrs. List No.	L754/PCB/.050 = 120-7149	Mfrs. List No.	L754/PCB/.500 = 120-7152
	L754/PCB/.100 = 120-7150		L754/PCB/1 = 120-7153
	L754/PCB/.250 = 120-7151		L754/PCB/2 = 120-7154

436573

Rating	Order Code	Price Each			
		10+	100+	500+	1K+
50mA	120-7149●	1.70	1.55	1.42	1.28
100mA	120-7150●	1.70	1.55	1.42	1.28
500mA	120-7152●	1.70	1.55	1.42	1.28
1A	120-7153●	1.70	1.55	1.42	1.28
2A	120-7154●	1.30	1.18	1.08	0.98



Open fuse holder with a synthetic resin bonded paper base.



H = 9.5, W = 6.4, D = 18.7
Fixing centres = 17.8 x 2.0

Rating	2A	Operating temperature	-40°C to +90°C
Breakdown voltage	>3kV dc		

204596

Mfrs. List No.	Order Code	Price Each			
		1+	125+	500+	1K2+
L1383	319-545●	2.24	1.91	1.52	1.22

5 x 25mm Fuses

Quick Blow (F) HRC Ceramic

70-010-04 Series



- Conforms to DIN 41 572 Part 1
- Colour coded

Voltage Rating	250V	Breaking capacity	1500A @ 250V
----------------	------	-------------------	--------------

Mfrs. List No. 70-010-04 + Rating



Fuses & Circuit Breakers

5 x 25mm Fuses - continued

Quick Blow (F) HRC Ceramic - continued

70-010-04 Series - continued

204544

Rating	Colour Code	Order Code	1+	5+	10+	50+
1.6A	Orange	117-5156●	2.39	2.31	2.23	2.16
2A	Blue	117-5157●	2.17	1.98	1.88	1.80
3.15A	Black	117-5158●	2.17	1.98	1.88	1.80
4A	Brown	117-5159●	2.17	1.98	1.88	1.80
5A	White	117-5160●	2.17	1.98	1.88	1.80
6.3A	Green	117-5161●	2.17	1.98	1.88	1.80
8A	Grey	117-5162●	2.17	1.98	1.88	1.80
10A	Red	117-5163●	2.17	1.98	1.88	1.80

Medium Blow (M) HRC Ceramic

70-010-05 Series



- Conforms to DIN 41 576 Part 2 except 10A
- Colour coded

Voltage Rating 250V Breaking capacity 1500A @ 250V

Mfrs. List No. 70-010-05 + Rating

204545

Rating	Colour Code	Order Code	1+	5+	10+	50+
500mA	White	117-5164●	2.65	2.41	2.30	2.18
1A	Red	117-5165●	2.65	2.41	2.30	2.18
2A	Blue	117-5167●	1.99	1.82	1.74	1.66
4A	Brown	117-5168●	1.99	1.82	1.74	1.66
5A	White	117-5169●	1.99	1.82	1.74	1.66
6.3A	Green	117-5170●	1.99	1.82	1.74	1.66
10A	Red	117-5171●	1.99	1.82	1.74	1.66

Fuse Kits

20 x 5mm Fuse Kit



- A range of 18, 20 x 5mm quick blow and antisurge fuses supplied in a compartment storage box.
- The kit can be restocked when required.

H = 50, W = 260, D = 165

Kit contains 10 of each of the following:

Antisurge (ceramic) S 505 Series 2A, 3.15A, 5A
 Quick blow (glass) S 500 Series 500mA, 1A, 2A, 3.15A, 5A, 6.3A
 Antisurge (glass) S 506 Series 315mA, 500mA, 630mA, 1A, 1.25A, 1.6A, 2A, 3.15A, 6.3A

204398

	Order Code	1+	5+	10+
20 x 5mm Kit	120-2373●	26.61	23.75	21.25

Assorted Fuse Kit



A range of 18 quick blow, antisurge and mains fuses in 20mm, 1" and 1 1/4" lengths supplied in an 18 compartment storage box. The kit can be restocked when required.

Kit contains 10 each of the following:
 20 x 5mm quick blow fuses (glass) - 1A, 2A, 3.15A, 5A.
 20 x 5mm antisurge fuses (glass) - 1A, 2A, 3.15A.
 1" mains quick blow fuses (ceramic) - 1A, 2A, 3A, 5A, 13A.
 1 1/4" x 1/4" quick blow fuses (glass) - 1A, 2A, 5A, 10A, 15A.
 1 1/4" x 1/4" antisurge fuses (ceramic) - 10A.

H = 50, W = 260, D = 165

Mfrs. List No. FUSEKIT E

204403

	Order Code	1+	5+	10+
Assorted Fuse Kit	151-655	30.03	27.43	25.64

TR5 Fuse Kit



Selection kit containing popular values from the TR5 fuse range and the PCB mounting socket. The kit can be restocked when required.

H = 20, W = 211, D = 105

Kit contains 10 each of the following:

19370K Series (Quick blow)
 19372K Series (Antisurge)

250mA, 1A, 1.25A, 1.6A, 2A
 160mA, 200mA, 315mA, 500mA, 630mA, 800mA,
 1A, 1.6A, 2A, 2.5A, 3.15A, 4A

19559 PCB Socket

204410

Order Code	1+	5+	10+
581-434	60.80	57.76	54.70

Fuse Kits



Selection kits containing popular values of the ATO series and Mini blade series, fast acting blade style automotive fuses. Complete with complementary fuse puller. The kits can be restocked when required.

ATO Kit Contains:

15 each 10A, 15A, 30A
 10 each 5A, 7.5A, 20A
 5 each 1A, 2A, 3A, 4A, 25A

Mini Blade Kit Contains:

1 each Fuse puller
 10 each 2A, 3A, 4A, 5A, 7.5A, 10A, 15A, 20A, 25A, 30A
 1 each Fuse puller

204399

	Order Code	1+	5+	10+
ATO Kit	117-5176●	19.59	18.03	16.09
Mini Blade Kit	994-3781●	17.85	16.44	14.58

Wire Ended Fuses

TR5 Fuses



- European TR5 fuse is available with either quick blow (F) or antisurge (T) characteristics.
- The fuses can be either soldered directly into a printed circuit board or alternatively plugged into a two pin socket (951-6360).
- This socket can in turn be soldered into a printed circuit board.
- A panel mounting and PCB fuseholder with clear plastic cover is also available (951-6387, 951-6379).

H = 8, Dia = 8.5
 Lead pitch = 5
 Lead length = 4.3
 Lead dia = 0.6

Rated Voltage 250V ac
 Breaking capacity 35A @ Vn or 10 X In @ Vn, whichever is greater.
 Mfrs. List No. Quick blow = 19370K + rating
 Antisurge = 19372K + rating


Complies with IEC127-3.
 Approved to VDE and SEMKO.

UL Recognised

204382

Order Multiple=10	Order Code	10+	50+	100+	500+
Quick Blow (F)					
50mA	951-5887●	1.65	1.51	1.32	1.10
63mA	135-4621●	1.95	1.85	1.78	1.68
80mA	135-4622●	1.95	1.85	1.78	1.68
100mA	951-5895●	0.51	0.43	0.37	0.32
125mA	951-5909●	0.51	0.43	0.37	0.32
160mA	951-5917●	0.51	0.43	0.37	0.32
200mA	951-5925●	0.51	0.43	0.37	0.32
250mA	951-5933●	0.51	0.43	0.37	0.32
315mA	951-5941●	0.38	0.31	0.28	0.24
400mA	135-4623●	0.58	0.46	0.42	0.35
500mA	951-5950●	0.51	0.43	0.37	0.32
630mA	135-4624●	0.58	0.46	0.42	0.35
800mA	135-4625●	0.58	0.46	0.42	0.35
1A	951-5968●	0.51	0.43	0.37	0.32
1.25A	951-5976●	0.51	0.43	0.37	0.32
1.6A	951-5984●	0.51	0.43	0.37	0.32
2A	951-5992●	0.51	0.43	0.37	0.32
2.5A	951-6000●	0.51	0.43	0.37	0.32
3.15A	951-6018●	0.51	0.43	0.37	0.32
4A	951-6026●	0.51	0.43	0.37	0.32
Antisurge (T)					
50mA	951-6034●	0.84	0.64	0.52	0.46
63mA	135-4626●	0.78	0.59	0.48	0.42
80mA	135-4627●	0.63	0.50	0.45	0.38
100mA	951-6042●	0.52	0.47	0.40	0.34
125mA	951-6050●	0.52	0.47	0.40	0.34
160mA	951-6069●	0.52	0.47	0.40	0.34
250mA	951-6085●	0.52	0.47	0.40	0.34
315mA	951-6093●	0.52	0.47	0.40	0.34
400mA	135-4628●	0.56	0.45	0.40	0.34
500mA	951-6107●	0.52	0.47	0.40	0.34
630mA	951-6115●	0.52	0.47	0.40	0.34
800mA	951-6123●	0.52	0.47	0.40	0.34
1A	951-6131●	0.52	0.47	0.40	0.34
1.25A	951-6140●	0.52	0.47	0.40	0.34
1.6A	951-6158●	0.52	0.47	0.40	0.34
2A	951-6166●	0.52	0.47	0.40	0.34
2.5A	951-6174●	0.52	0.47	0.40	0.34
3.15A	951-6182●	0.52	0.47	0.40	0.34
4A	951-6190●	0.52	0.47	0.40	0.34
5A	951-6204●	0.52	0.47	0.40	0.34
Fuse Holder PCB	118-5363●	0.42	0.37	0.30	0.22

Radial Lead - (TRS Style)



- Fast-Acting and Slow Blow fuses
- 35A or 10 x Rated current (Whichever is greater) @ 250V ac Interrupt rating
- Operating temperature -55°C to +125°C
- Tin plated alloy leads.
- Black thermoplastic, UL 94-V0 body
- UL Recognised, VDE, CSA, SEMKO, CCC and KTL Approved

Body - Dia. = 8.35, H = 7.7mm
Leads - Dia. = 0.62, L = 22, Pitch = 5.08mm

Mfrs. List No. Fast-Acting: MCMET + Rating

Slow Blow: MCMET + Rating

505664

Order Multiple=10 Rating (A)	Order Code	10+	50+	100+	500+	1K+
Fast-Acting						
0.8A	156-6051●	0.300	0.290	0.280	0.250	0.220
1A	156-6053●	0.300	0.290	0.280	0.250	0.220
1.25A	156-6054●	0.300	0.290	0.280	0.250	0.220
1.6A	156-6055●	0.300	0.290	0.280	0.250	0.220
2A	156-6056●	0.300	0.290	0.280	0.250	0.220
2.5A	156-6057●	0.300	0.290	0.280	0.250	0.220
3.15A	156-6058●	0.300	0.290	0.280	0.250	0.220
4A	156-6059●	0.300	0.290	0.280	0.250	0.220
5A	156-6060●	0.300	0.290	0.280	0.250	0.220
6.3A	156-6061●	0.300	0.290	0.280	0.250	0.220
Slow Blow						
0.16A	156-6062●	0.270	0.250	0.240	0.220	0.194
0.2A	156-6063●	0.270	0.250	0.240	0.220	0.194
0.25A	156-6065●	0.270	0.250	0.240	0.220	0.194
0.315A	156-6066●	0.270	0.250	0.240	0.220	0.194
0.4A	156-6067●	0.270	0.250	0.240	0.220	0.194
0.5A	156-6068●	0.270	0.250	0.240	0.220	0.194
0.63A	156-6069●	0.270	0.250	0.240	0.220	0.194
0.8A	156-6070●	0.270	0.250	0.240	0.220	0.194
1A	156-6071●	0.270	0.250	0.240	0.220	0.194
1.25A	156-6072●	0.270	0.250	0.240	0.220	0.194
1.6A	156-6073●	0.270	0.250	0.240	0.220	0.194
2A	156-6074●	0.270	0.250	0.240	0.220	0.194
2.5A	156-6075●	0.270	0.250	0.240	0.220	0.194
3.15A	156-6077●	0.270	0.250	0.240	0.220	0.194
4A	156-6078●	0.270	0.250	0.240	0.220	0.194

TR5 Fuseholders and Sockets



951-6360 PCB Socket
H = 7.4, Dia = 10
Lead length = 3.8
Lead pitch = 7.18



111-6371+111-6373
Panel mount
H = 18, Dia = 15
Depth behind panel = 7
Panel cut-out = 12.7



111-6371+111-6372
PCB mount
H = 18, Dia = 15
Lead length = 5
Lead pitch = 7.62

PCB mounting two pin socket and choice of fuseholder with either panel mounting with solder tab terminations or PCB mounting pins. Images show Fuseholder and Cap assembled, these are ordered separately. The clear cover will fit either fuseholder, allowing the fuse to be visible.

204384

	Mfrs. List No.	Order Code	1+	25+	50+	100+
PCB Socket	55900000001	951-6360●	0.40	0.36	0.34	0.29
Clear Cap	57500000001	111-6371●	0.31	0.30	0.22	0.18
Panel Mount Fuseholder	57000000001	111-6373●	0.96	0.79	0.57	0.41
PCB Mount Fuseholder	57100000001	111-6372●	0.88	0.74	0.63	0.48

TR5 Fuse Kit



Selection kit containing popular values from the TR5 fuse range and the PCB mounting socket. The kit can be restocked when required.

H = 20, W = 211, D = 105

Kit contains 10 each of the following:

19370K Series (Quick blow) 250mA, 1A, 1.25A, 1.6A, 2A
19372K Series (Antisurge) 160mA, 200mA, 315mA, 500mA, 630mA, 800mA,
1A, 1.6A, 2A, 2.5A, 3.15A, 4A

19559 PCB Socket

204410

Order Code	1+	Price Each	10+
581-434	60.80	57.76	54.70

Radial Lead Micro Fuse



- Fast acting or time delay versions available
- Can be soldered directly into a print circuit board or plugged into a fuseholder (303-1780)
- SEMKO and VDE approved except for 5A
- UL recognised and CSA approved
- Complies with IEC60127-3

H = 7.7 Dia. = 8.4 Lead pitch = 5
Lead length = 4.3 Lead dia. = 0.6

Voltage rating 250V ac
Breaking capacity 35A or 10 times rated current (whichever is the greater)

Mfrs. List No. Fast Acting = BK/EFF + rating
Time Delay = BK/ETF + rating

204549

Order Multiple=10 Rating	Order Code	10+	50+	100+	500+
Fast Acting					
250mA	303-0015●	0.56	0.44	0.39	0.34
500mA	303-0040●	0.56	0.44	0.39	0.34
1A	303-0076●	0.47	0.39	0.34	0.31
2A	303-0106●	0.47	0.39	0.34	0.31
5A	303-0143●	0.47	0.39	0.34	0.31
Time Delay					
80mA	302-9864●	0.67	0.53	0.43	0.38
100mA	302-9876●	0.59	0.47	0.42	0.36
250mA	302-9890●	0.46	0.37	0.33	0.28
315mA	302-9906●	0.59	0.47	0.42	0.36
500mA	302-9920●	0.56	0.44	0.39	0.34
800mA	302-9931●	0.47	0.39	0.34	0.31
1A	302-9943●	0.47	0.39	0.34	0.31
2A	302-9979●	0.47	0.39	0.34	0.31
2.5A	302-9980●	0.47	0.39	0.34	0.31
3.15A	302-9992●	0.47	0.39	0.34	0.31
4A	303-0003●	0.47	0.39	0.34	0.31

Radial Lead Micro Fuseholder



TR5 Style Fuses



- Precision turned, anti wicking pin design
- Twist free, low profile construction
- High retention design to prevent fuse walkout during heavy vibrations
- Side and end stackable
- UL94-V0 moulding
- 200 operations minimum life
- UL Recognised

W = 7.62, D = 2.54, Lead pitch = 5.08mm

Current rating 3A
Contact resistance ≤4mohm
Insulation resistance 1000MR @ 100V
Operating temperature -55 to 125°C

484545

Order Multiple=10 Mfrs. List No.	Order Code	10+	50+	100+	500+
MCBK/PCS	143-7180●	0.26	0.25	0.24	0.23

FOR MORE INFORMATION & CHOICE

Product Search



☐ RoHS Compliant Items Only | [Advanced Search](#)

Quick Blow - F

Type MSF - 250V



- Low breaking capacity
- Directly solderable into printed circuit boards
- Conform to IEC 60127-3/3, EN 60127-3/3, UL 248-14, CSA C22.2 No. 248.14
- Approvals: CSA, SEMKO, SEV & VDE, UL Recognised

Body: Dia. = 8.5, H = 8.5
Pin: Dia. = 0.64, L = 4.3, Pitch = 5.08mm

Rated Voltage 250V
Breaking capacity 35A @ Vn or 10 X In @ Vn,

Operating temperature -25 to 85°C

Mfrs. List No.	Order Code	Mfrs. List No.	Order Code
0034.6000	121-4674	0034.6011	121-4681
0034.6001	121-4675	0034.6012	121-4682
0034.6004	121-4677	0034.6014	121-4683
0034.6005	121-4678	0034.6017	121-4686
0034.6010	121-4680	0034.6019	121-4687
		0031.7601	121-4707



Wire Ended Fuses - continued

Quick Blow - F - continued

Type MSF - 250V - continued

244693

Order Multiple = Pack	Order Code	1+	5+	10+
Rating				
40mA	121-4674●	4.50	3.90	3.67
50mA	121-4675●	4.50	3.90	3.67
100mA	121-4677●	4.50	3.90	3.67
125mA	121-4678●	3.03	2.65	2.44
400mA	121-4680●	4.04	3.53	3.25
500mA	121-4681●	4.04	3.53	3.25
630mA	121-4682●	3.23	2.82	2.60
1A	121-4683●	4.04	3.53	3.25
2A	121-4686●	4.04	3.53	3.25
3.15A	121-4687●	4.04	3.53	3.25
Fuse Holder	121-4707●	3.68	3.21	3.03

Time - Lag (T)

MXT 250 Series



- High breaking capacity
- Directly solderable on PCB
- Tin plated copper leads
- 5.08mm pin pitch
- Approved according to IEC 60127-3/4
- VDE, CCC Approved. UL Recognised

Breaking capacity 100A
 Rated Voltage 250V ac
 Operating Temperature Range -55°C to 125°C

Body - H = 8.5, Dia. = 8.5mm
 Pins - L = 8.5, Dia. = 0.64mm

522359

Order Multiple=10	Mfrs. List No.	Order Code	10+	50+	100+	500+
0.8A	0034.6914	163-7534●	0.35	0.32	0.29	0.25
1A	0034.6915	163-7535●	0.35	0.32	0.29	0.25
1.25A	0034.6916	163-7536●	0.35	0.32	0.29	0.25
1.6A	0034.6917	163-7537●	0.35	0.32	0.29	0.25
2A	0034.6918	163-7539●	0.35	0.32	0.29	0.25
2.5A	0034.6919	163-7541●	0.35	0.32	0.29	0.25
3.15A	0034.6920	163-7542●	0.35	0.32	0.29	0.25
4A	0034.6921	163-7543●	0.35	0.32	0.29	0.25
5A	0034.6922	163-7544●	0.35	0.32	0.29	0.25
6.3A	0034.6923	163-7545●	0.35	0.32	0.29	0.25
8A	0034.6924	163-7546●	0.35	0.32	0.29	0.25
10A	0034.6925	163-7547●	0.35	0.32	0.29	0.25

Two Pin Socket



A two pin socket adaptor suitable for the PC-Tron™, TE5 or TR5 European fuse, for mounting on a PC board. (N.B. Fuse leads to be reduced in length to fit the PC-Tron™ and TE5)

Body L = 7.62, W = 2.54, D = 2.54
 Pins: L = 2.92, Dia = 0.51, Pitch = 5.08

204454

Order Code	10+	50+	100+	500+
108-7070●	0.33	0.27	0.25	0.23

Axial Lead, Very Fast Acting

Pico Fuse - 250V ac



L = 7.6, Dia. = 3.7, Lead dia. = 0.64 Supplied in Ammo pack (pack = 100)

- Solder coated axial leads
 - UL recognised and CSA approved
- Breaking capacity 50A @ 250V ac
 Operating temperature -55°C to +125°C

Mfrs. List No. 263 + Rating

204552

Order Multiple=10	Order Code	10+	100+	500+	1K+
Rating					
62mA	992-1630●	1.08	0.84	0.75	0.64
125mA	992-1648●	1.08	0.84	0.75	0.64
250mA	992-1656●	1.08	0.84	0.75	0.64
375mA	992-1664●	0.62	0.49	0.43	0.37
500mA	992-1672●	1.08	0.84	0.75	0.64
750mA	992-1680●	1.08	0.84	0.75	0.64
1A	992-1699●	1.08	0.84	0.75	0.64
1.5A	992-1702●	0.62	0.49	0.43	0.37
2A	992-1710●	1.07	0.84	0.73	0.63
2.5A	992-1729●	1.08	0.84	0.75	0.64
3A	992-1737●	1.08	0.84	0.75	0.64
3.5A	992-1745●	1.08	0.84	0.75	0.64
4A	992-1753●	1.07	0.84	0.73	0.63
5A	992-1761●	1.08	0.84	0.75	0.64

Axial Lead - 2.8mm Diameter



Body - Dia. = 2.8, L = 7.6mm
 Leads - Dia. = 0.64, L = 38.1mm

- Very Fast-Acting and Slow Blow fuses
- Very Fast-Acting DC Interrupt rating - 300A @ 125V dc
- Slow Blow DC Interrupt rating - 50A @ 125V dc
- Operating temperature -55°C to +125°C
- Solder coated copper wire leads.
- Encapsulated, epoxy-coated body
- UL Recognised

Mfrs. List No. Very Fast-Acting: MCPFP + Rating

Slow Blow: MCPSP + Rating

505662

Order Multiple=10	Order Code	10+	50+	100+	500+	1K+
Rating (A)						
Very Fast-Acting						
0.1A	156-6023●	0.30	0.28	0.25	0.22	0.21
0.125A	156-6024●	0.30	0.28	0.25	0.22	0.21
0.25A	156-6025●	0.30	0.28	0.25	0.22	0.21
0.5A	156-6026●	0.30	0.28	0.25	0.22	0.21
1A	156-6028●	0.30	0.28	0.25	0.22	0.21
1.5A	156-6029●	0.30	0.28	0.25	0.22	0.21
2A	156-6030●	0.30	0.28	0.25	0.22	0.21
2.5A	156-6031●	0.30	0.28	0.25	0.22	0.21
3A	156-6032●	0.30	0.28	0.25	0.22	0.21
3.15A	156-6033●	0.30	0.28	0.25	0.22	0.21
3.5A	156-6034●	0.30	0.28	0.25	0.22	0.21
4A	156-6035●	0.30	0.28	0.25	0.22	0.21
5A	156-6036●	0.30	0.28	0.25	0.22	0.21
6.3A	156-6037●	0.30	0.28	0.25	0.22	0.21
7A	156-6038●	0.30	0.28	0.25	0.22	0.21
8A	156-6041●	0.30	0.28	0.25	0.22	0.21
10A	156-6042●	0.30	0.28	0.25	0.22	0.21
Slow Blow						
0.5A	156-6043●	0.40	0.38	0.36	0.34	0.31
1A	156-6044●	0.40	0.38	0.36	0.34	0.31
1.5A	156-6045●	0.40	0.38	0.36	0.34	0.31
2A	156-6046●	0.40	0.38	0.36	0.34	0.31
2.5A	156-6047●	0.40	0.38	0.36	0.34	0.31
3A	156-6048●	0.40	0.38	0.36	0.34	0.31
4A	156-6049●	0.40	0.38	0.36	0.34	0.31
5A	156-6050●	0.40	0.38	0.36	0.34	0.31

Axial Lead Quick Blow (F) Washable

Microtron® - 125V ac/dc



L = 7.49, Dia. = 3.0, Lead length = 31.7, Lead dia. = 0.64
 Supplied bandoliered on tape (reel = 2K5 pcs).

The Microtron® subminiature fuse is hermetically sealed and manufactured from high temperature plastic, allowing board washing. Black markings are etched on a gold background with flammability to **UL94V-0**, CSA approved, UL Recognised.

Voltage Rating 125V ac/dc Interrupt rating -dc 300
 Interrupt rating - ac 50A Mfrs. List No. MCR + rating

204425

Order Multiple=10	Order Code	10+	100+	500+
Rating				
125mA	112-3043●	0.73	0.64	0.58
250mA	112-3042●	0.52	0.46	0.42
375mA	112-3049●	0.49	0.43	0.39
500mA	112-3041●	0.73	0.64	0.58
1A	112-3036●	0.73	0.64	0.58
1.5A	112-3037●	0.73	0.64	0.58
2A	112-3045●	0.58	0.51	0.47
2.5A	112-3046●	0.73	0.64	0.58
3A	112-3047●	0.73	0.64	0.58
4A	112-3050●	0.73	0.64	0.58
5A	112-3052●	0.39	0.34	0.31
7A	112-3053●	0.49	0.43	0.39
10A	112-3044●	0.73	0.64	0.58

Subminiature - Axial Lead

Fast Acting, Washable - 125V ac/dc



Length: Body = 7.1mm, Lead = 38mm Dia: Body = 3.18mm

- Hermetically sealed
- Manufactured from high temperature epoxy plastic
- Tin-lead plated copper lead wires
- Interrupt 50A at 125V ac/dc
- Flammability rated to **UL94V-0**
- CSA approved and UL Recognised.

Voltage Rating 125V ac/dc Interrupt rating -dc 300A
 Interrupt rating - ac 50A Mfrs. List No. BK1/MCRW + rating

407009

Order Multiple=10		Price Each		
Rating	Order Code	1+	100+	500+
100mA	120-2387●	0.81	0.73	0.63
125mA	120-2389●	0.58	0.53	0.45
200mA	120-2392●	0.58	0.53	0.45
250mA	120-2393●	0.58	0.53	0.45
500mA	120-2395●	0.58	0.53	0.45
1A	120-2397●	0.58	0.53	0.45
1.5A	120-2398●	0.58	0.53	0.45
2A	120-2399●	0.58	0.53	0.45
2.5A	120-2400●	0.32	0.29	0.25
3A	120-2401●	0.58	0.53	0.45
4A	120-2402●	0.58	0.53	0.45
5A	120-2403●	0.58	0.53	0.45
7A	120-2404●	0.58	0.53	0.45
10A	120-2405●	0.58	0.53	0.45
12A	120-2407●	0.58	0.53	0.45
15A	120-2408●	0.58	0.53	0.45

Axial Lead - Quick Blow (F)

Type 172322



- Subminiature size
- CSA Approved, UL Recognised

L (body) = 8mm, L (lead) = 39mm
Dia. (body) = 2.36mm, Dia. (lead) = 0.62mm

Breaking capacity 50A @ 125V Operating temperature -55 to 85°C

428994

Order Multiple=10		Price Each			
Mfrs. List No.	Rating	Order Code	10+	50+	250+
7010703013	250mA	116-2748●	0.68	0.49	0.40
7010707013	1A	116-2750●	0.85	0.52	0.40
70107080	1.5A	116-2742●	0.85	0.52	0.40
7010709013	2A	116-2751●	0.85	0.52	0.40
7010710013	2.5A	116-2752●	0.85	0.52	0.40
7010711013	3A	116-2753●	0.85	0.52	0.40
710712013	4A	116-2745●	0.85	0.52	0.40
7010713013	5A	116-2754●	0.85	0.52	0.40
7010714013	7A	116-2756●	0.57	0.41	0.32
701071513.	10A	116-2744●	0.71	0.44	0.34

Axial Lead - 3.18mm Diameter

50A @ 250V ac Interrupt Rating



Body - Dia. = 3.18, L = 7.6mm
Leads - Dia. = 0.64, L = 38.1mm

- Very Fast-Acting and Slow Blow fuses
- Operating temperature -55°C to +125°C
- Solder coated copper wire leads.
- Encapsulated, epoxy-coated body
- UL Recognised



Mfrs. List No. Very Fast-Acting: MCPEP + Rating Slow Blow: MCPMP + Rating

505652

Order Multiple=10		Price Each			
Rating (A)	Order Code	10+	50+	100+	500+
Very Fast-Acting					
0.1A	156-6005●	0.30	0.28	0.25	0.22
0.125A	156-6006●	0.30	0.28	0.25	0.22
0.25A	156-6007●	0.30	0.28	0.25	0.22
0.375A	156-6008●	0.30	0.28	0.25	0.22
0.5A	156-6009●	0.30	0.28	0.25	0.22
1A	156-6010●	0.30	0.28	0.25	0.22
2A	156-6011●	0.30	0.28	0.25	0.22
3A	156-6012●	0.30	0.28	0.25	0.22
4A	156-6013●	0.30	0.28	0.25	0.22
5A	156-6014●	0.30	0.28	0.25	0.22
Slow Blow					
0.5A	156-6016●	0.40	0.38	0.36	0.34
1A	156-6017●	0.40	0.38	0.36	0.34
1.25A	156-6018●	0.40	0.38	0.36	0.34
2A	156-6019●	0.40	0.38	0.36	0.34
3A	156-6020●	0.40	0.38	0.36	0.34
5A	156-6021●	0.40	0.38	0.36	0.34
7A	156-6022●	0.40	0.38	0.36	0.34

Fast Acting 491 Series



Lead dia = 0.64 L = 7.62 Dia = 2.62

- Fast acting protection from excess current
- Designed for protection of circuits on the secondary side of the transformer

Voltage Rating 60V Mfrs. List No. 491 + Rating

204518

Order Multiple=10		Price Each				
Rating	Order Code	10+	50+	100+	250+	500+
250mA	994-3919●	0.36	0.34	0.32	0.31	0.30
400mA	994-3935●	0.36	0.34	0.32	0.31	0.30
500mA	994-3943●	0.36	0.34	0.32	0.31	0.30
630mA	994-3951●	0.36	0.34	0.32	0.31	0.30
750mA	994-3960●	0.36	0.34	0.32	0.31	0.30
1A	994-3986●	0.36	0.34	0.32	0.31	0.30
2A	994-3994●	0.36	0.34	0.32	0.31	0.30
2.5A	994-4001●	0.26	0.25	0.24	0.23	0.22
3A	994-4010●	0.36	0.34	0.32	0.31	0.30
3.15A	994-4028●	0.36	0.34	0.32	0.31	0.30
4A	994-4036●	0.36	0.34	0.32	0.31	0.30
5A	994-4044●	0.26	0.25	0.24	0.23	0.22

Barrier Network Fuses



Axial barrier network fuses featuring high break capacity in a compact size. Designed for industrial applications in barrier circuits.
Available as leaded or SMD versions

L (Body) = 4.6, Dia = 3.02mm.
Length (O/A) = 8.4, Lead dia. = 0.6mm

Voltage rating (Vn) 250Vac/dc Breaking Capacity 4000A

Mfrs. List No. 242 + Rating

204462

Order Multiple=5		Price Each			
Rating	Order Code	5+	25+	50+	100+
Leaded					
50mA	118-3970●	2.46	2.07	1.76	1.44
80mA	118-3971●	2.46	2.07	1.76	1.44
100mA	118-3972●	2.46	2.07	1.76	1.44
160mA	992-2423●	1.72	1.45	1.23	1.01
200mA	992-2431●	1.20	1.02	0.86	0.71
250mA	992-2440●	2.46	2.07	1.76	1.44

Axial Lead

PicoFuse - 125V ac/dc



L = 7.1, Dia. = 2.4 (992-2067 to 992-2113 = 3.2), Lead dia. = 0.64 (992-2059 = 0.81)
Supplied bandoliered on tape (reel = 1K pcs)

Quick blow and antisurge fuses with solder coated axial leads. UL Recognised and CSA approved.

Breaking capacity 300A @ 125V dc, 300A @ 125V ac (992-1931 to 992-2040)
300A @ 32V dc, 50A @ 32V ac (992-2059)
50A @ 125V ac/dc (992-2067 to 992-2113)

Operating temperature -55°C to +125°C

Mfrs. List No. Quick Blow: 251 + Rating Antisurge: 473 + Rating


204433

Order Multiple=10		Price Each			
Rating	Order Code	10+	50+	100+	500+
Quick Blow (F)					
62mA	992-1931●	0.69	0.65	0.63	0.59
125mA	992-1940●	0.69	0.65	0.63	0.59
250mA	992-1958●	0.69	0.65	0.63	0.59
500mA	992-1966●	0.69	0.65	0.63	0.59
1A	992-1974●	0.69	0.65	0.63	0.59
1.5A	992-1982●	0.69	0.65	0.63	0.59
2A	992-1990●	0.69	0.65	0.63	0.59
3A	992-2008●	0.69	0.65	0.63	0.59
4A	992-2016●	0.69	0.65	0.63	0.59
5A	992-2024●	0.69	0.65	0.63	0.59
7A	992-2032●	0.69	0.65	0.63	0.59
10A	992-2040●	0.69	0.65	0.63	0.59
15A	992-2059●	0.69	0.65	0.63	0.59
Antisurge (T)					
500mA	992-2067●	0.85	0.82	0.78	0.75
1A	992-2075●	0.85	0.82	0.78	0.75
2A	992-2083●	0.85	0.82	0.78	0.75
3A	992-2091●	0.85	0.82	0.78	0.75
4A	992-2105●	0.88	0.84	0.80	0.77
5A	992-2113●	0.85	0.82	0.78	0.75

◆ = 32V ac/dc working voltage only

Radial Lead - Rectangular

35A @ 250V ac Interrupt Rating



- Fast-Acting and Slow Blow fuses
- 35A or 10 x Rated current (Which ever is greater) @ 250V ac Interrupt rating
- Operating temperature -55°C to +125°C
- Tin plated alloy leads.
- Black thermoplastic body
- UL Recognised, VDE, CSA, SEMKO and CCC Approved

Body - H = 7.7, W = 8.35, D = 4.3mm
Leads - Dia. = 0.62, L = 22, Pitch = 5.08mm

Mfrs. List No. Fast-Acting: MCMSF + Rating

Slow Blow: MCMST + Rating



Automotive Fuses - continued

Fuseholder

Automotive



Mini Blade Type - H = 11.2, W = 14.7, D = 4.8mm



ATO Type - H = 11.2, W = 19, D = 3.15mm



In-Line type

Fuse blocks and In-line fuseholders suitable for use with automotive blade type fuses.

509893

Current Rating	Type	Mfrs. List No.	Order Code	1+	25+	50+	100+	250+
Fuse Blocks								
15A	Mini Blade	MCCQ-122	158-6595	0.52	0.47	0.43	0.39	0.36
15A	ATO	MCCQ-121	158-6596	0.52	0.47	0.43	0.39	0.36
In-Line Fuse Holders								
20A	ATO	MCCQ-211A	158-6597	0.80	0.73	0.66	0.61	0.56
30A	ATO	MCCQ-211N	158-6598	0.80	0.73	0.66	0.61	0.56
In-Line Fuse Holders - Splashproof								
30A	Mini Blade	MCCQ-211SN	158-6599	0.80	0.73	0.66	0.61	0.56
30A	ATO	MCCQ-211CN	158-6600	0.98	0.91	0.84	0.77	0.73

Blade Fuses for Harsh Environments

FKS ATO Style




- Manufactured from thermoplastic, UL 94-V0 heat resistant
- Blade contacts, edge protected
- Breaking capacity 1000A @ 80V dc
- UL Recognised

SICHN503

Rating (A)	Colour	Mfrs. List No.	Order Code	1+	10+	50+	100+
3	Violet	166.7000.4306	309-424	1.16	0.95	0.81	0.71
5	Tan	166.7000.4506	309-473	1.16	0.95	0.81	0.71
7.5	Brown	166.7000.4756	309-620	1.16	0.95	0.81	0.71
10	Red	166.7000.5106	309-631	1.16	0.95	0.81	0.71
15	Blue	166.7000.5156	309-941	1.22	1.00	0.85	0.76
20	Yellow	166.7000.5206	309-953	1.16	0.95	0.81	0.71
25	Clear	166.7000.5256	309-965	1.14	0.93	0.79	0.70
30	Green	166.7000.5306	309-977	1.27	1.03	0.87	0.77

Fuseholder



In-line fuseholders suitable for use with automotive blade type fuses.

Maximum voltage rating 20A @ 32V, 20A @ 32V
Operating temperature -35°C to +100°C

Mfrs. List No. 01500260LXN = 994-3099 0FHAC0001LXN = 994-3382 0FHA0001LXN = 994-3110

204434


	Order Code	1+	25+	50+	100+	250+
Standard						
20A	994-3110	1.14	1.10	1.05	1.02	0.96
30A	994-3099	1.16	1.12	1.08	1.04	0.98
Splashproof						
20A	994-3382	2.32	2.23	2.14	2.03	1.93

PCB Fuseholders - ATO and Mini Blade Fuses





Interlocking PCB Mount ATO Fuseholder which can be stacked end on or side on. Horizontal and vertical mounting Mini Blade PCB fuseholders

H = 22.0 W = 21.8, D = 9.0 Lead Pitch = 9.3



PCB Drilling



204407

	Order Code	1+	25+	Price Each 50+	100+	250+
ATO Fuseholder						
Vertical	994-3510	1.27	1.14	1.02	0.91	0.84
Mini Blade Fuseholder						
Vertical	994-3790	1.77	1.58	1.41	1.27	1.16
Horizontal	994-3803	1.76	1.59	1.41	1.27	1.16

PCB Blade Fuseholder

ATO Style Fuses



- Manufactured from black thermoplastic, UL94V-0
- Leaf spring connector system
- Solder terminals for through hole soldering
- Rated voltage 80V
- Maximum contact temperature 130°C

SICHN500

Mfrs. List No.	Order Code	1+	10+	25+	50+
178.6165.0001	310-499	0.70	0.66	0.64	0.61

In-Line Panel Mount Fuseholder



- Easy mounting alternative for ATO blade fuses
- Interlocks for multiple mountings
- Supplied with crimp terminals

Maximum rating 20A Operating temperature -40°C to +85°C

204526

Type	Mfrs. List No.	Order Code	1+	10+	50+
Panel Mount	01550320ZXU	994-3102	0.97	0.83	0.72
Screw Mount	178.6152.000	310-517	1.87	1.71	1.64

MAXI Fuse - Slow Blow



- Higher current rating than MINI fuse
- Popular in automotive applications
- Colour coded
- UL recognised

Body H=21.6 W=29.2 D=8.9
Blade L=12.7 W=8.1 D=0.8

Current Rating (A)	Pre-arcing I ² t (A ² S)	Voltage Rating (V)	Colour Code	Mfrs. List No.	Order Code
20	1100	32	Yellow	0299020.ZXOCR	994-3145
25	2087	32	Grey	0299025.TXN	135-4639
30	4070	32	Green	0299030.ZXOCR	994-3153
35	6032	32	Brown	0299035.TXN	135-4640
40	8450	32	Amber	0299040.ZXNV	994-3161
50	11300	32	Red	0299050.ZXNV	994-3170
60	15300	32	Blue	0299060.ZXOCR	994-3188
70	6900	32	Tan	0299070.TXN	135-4642
80	8800	32	Clear	0299080.TXN	135-4643

204551

Rating	Order Code	1+	10+	50+	100+
20A	994-3145	1.37	1.21	1.01	0.80
25A	135-4639	1.38	1.21	1.01	0.80
30A	994-3153	1.37	1.21	1.01	0.80
35A	135-4640	1.38	1.21	1.01	0.80
40A	994-3161	1.37	1.21	1.01	0.80
50A	994-3170	1.37	1.21	1.01	0.80
60A	994-3188	1.38	1.21	1.01	0.80
70A	135-4642	1.38	1.21	1.01	0.80
80A	135-4643	1.38	1.21	1.01	0.80

Over 480,000 products online



MAXI Fuseholder



Excluding Cover
H=38, W=66, D=22

Including Cover
H=42, W=71, D=24

- Simple installation
- Translucent thermoplastic cover option
- Supplied with two M5 x 8 screws

Maximum ratings 60A Operating temperature -10°C to +80°C

204535

Mfrs. List No.	Order Code	1+	Price Each	10+
01520001.TXN940	Fuseholder 994-3129●	6.11		5.51
01520900.XX832	Cover 994-3137●	0.91		0.80

MEGA Fuse - Slow Blow



- High current circuit protection
- Ideal for battery and UPS systems
- Fuse & Holder available separately

Mfrs. List No. 298+rating

Voltage 32V dc Mini. Melt. I₂t 389000

Fixing centres 101.6 @ 6.35 Dia.
Note: Dimensions include cover
H=38, W=87.2, D=38.5mm

204538

Rating	Order Code	1+	Price Each	50+	100+
80A	135-4630●	3.71	3.25	2.69	2.18
100A	135-4631●	3.71	3.25	2.69	2.18
125A	135-4633●	3.71	3.25	2.69	2.18
150A	135-4634●	3.71	3.25	2.69	2.18
175A	135-4635●	3.71	3.25	2.69	2.18
225A	135-4637●	2.60	2.28	1.88	1.53
250A	135-4638●	3.71	3.25	2.69	2.18
Fuseholder	994-3200●	6.79	5.94	5.06	4.06

Fork Lift Truck

Fuse Holder and Fuses



L (overall)=82, L (body)=32, W=22, H=10,
Fixing centres=60, Lug spacing=11



H = 54, W = 85, D = 24, Termi-
nal Pitch = 62mmmm

A range of heavy duty 80V fuses to **DIN43560/1** specially designed for battery powered industrial trucks, fork lift etc. strong ceramic case incorporates shatterproof glass inspection window and 60mm spacing integral lugs for direct stud mounting.

Max. Working voltage 80Vdc

In	1.5In	1.8In	2.5In	4In
All	≥1hr	≥1hr	0.8-10s	0.2-2s

Mfrs. List No. 90-058-05 + Rating

204409


Rating	Order Code	1+	Price Each	100+
Fuses				
50A	607-654	3.45	2.94	2.58
80A	607-666	3.64	3.09	2.72
100A	607-678	3.64	3.09	2.72
160A	607-680	3.79	3.24	2.88
200A	607-691	3.79	3.24	2.88
250A	607-708	4.19	3.55	3.09
325A	607-710	4.40	3.70	3.09
355A	607-721	4.40	3.70	3.09
500A	607-733	4.40	3.70	3.09
Fuse Holder				
Maximum Current Rating		1+	10+	25+
425A	307-282	10.05	9.56	9.15

Fuse Strips

Battery Powered Vehicles



H=38, W=87.2, D=38.5mm



Fixing centres 101.6 @ 6.35 Dia.

Note: Dimensions include cover

Non-housed fuse strips for battery powered vehicles. Current ratings from 50A to 250A, 80V dc with 90° and straight fork type lugs.

467824

Current Rating	Mfrs. List No.	Order Code	1+	Price Each	20+	100+
50A	157.5700.5501	135-4645●	2.34	2.17	1.94	
80A	157.5700.5801	135-4646●	2.34	2.17	1.94	
100A	157.5700.6101	135-4647●	2.34	2.17	1.94	
160A	157.5700.6161	135-4648●	2.34	2.17	1.94	
200A	157.5700.6201	135-4649●	2.34	2.17	1.94	
250A	157.5700.6251	135-4651●	2.34	2.17	1.94	
Fuseholder	1775701000	307-282	10.05	9.56	9.15	

Housed Fuse Strips

Fast Acting for Battery-powered Vehicles



- Fast acting
- 90° and straight fork lugs
- Window enables visual inspection of element
- Voltage rating 80V
- **DIN 43560/1**
- UL Recognised

SICHN507


Rating (A)	Mfrs. List No.	Order Code	1+	Price Each	10+	25+	50+	100+
35	157.5701.5351	307-300●	4.44	3.70	3.17	2.77	2.35	
50	157.5701.5501	307-312●	4.35	3.62	3.10	2.71	2.30	
80	157.5701.5801	307-336●	4.38	3.64	3.13	2.73	2.32	
160	157.5701.6161	307-361●	1.97	1.79	1.73	1.63	--	
200	157.5701.6201	307-373●	1.98	1.79	1.73	1.63	--	
250	157.5701.6251	307-385●	2.10	1.95	1.85	1.74	--	
355	157.5701.6351	307-439●	1.44	1.31	1.26	1.20	--	
425	157.5701.6421	307-452●	2.36	2.14	2.06	1.96	--	
Fuse Holder	1775701000	307-282	10.05	9.56	9.15	9.07	--	

Resettable Fuses

Multifuse MF - PSMF Series



PTC - SMD 0805 Style



- Fast tripping resettable circuit protection
- Standard (0805) footprint for automated assembly
- Reduced component size and resistance

H = 0.65, W = 2.15, D = 1.35mm

Operating temperature		-40°C to +85°C		Power Dissipation (Tripped)		0.5W
Max Operating Current		40A				
(A) *	(A) **	Initial	Time	Tripped	Mfrs.	
I Hold @ 23°C	I Trip @ 23°C	Resistance (R) @ 23°C	to Trip (s) @ 23°C	Power Dissip. (W) @ 23°C	List No.	Order Code
V_{max} = 15V dc						
0.1	0.3	1.0	1.5	0.5	MF-PSMF010X-2	129-4873
V_{max} = 9V dc						
0.2	0.5	0.65	0.02	0.5	MF-PSMF020X-2	129-4874
V_{max} = 6V dc						
0.35	0.75	0.25	0.1	0.5	MF-PSMF035X-2	129-4875
0.5	1.0	0.15	0.1	0.5	MF-PSMF050X-2	129-4876
0.75	1.5	0.09	0.2	0.6	MF-PSMF075X-2	129-4877
1.1	2.2	0.06	0.3	0.6	MF-PSMF110X-2	129-4879

* I Hold - Current at which Multifuse will not trip


** I Trip - Current at which Multifuse will trip

449792

Order Multiple=5 Hold Current (A)	Order Code	5+	50+	Price Each	100+	250+	500+
0.1	SMD 129-4873●	0.26	0.23	0.20	0.18	0.17	
0.2	SMD 129-4874●	0.26	0.23	0.20	0.18	0.17	
0.35	SMD 129-4875●	0.26	0.23	0.20	0.18	0.17	
0.5	SMD 129-4876●	0.26	0.23	0.20	0.18	0.17	
0.75	SMD 129-4877●	0.26	0.23	0.20	0.18	0.17	
1.1	SMD 129-4879●	0.26	0.23	0.20	0.18	0.17	



Resettable Fuses - continued

Multifuse MF - NSMF Series
PTC - SMD 1206 Style

- Compact design to save board space - 1206 footprint
- Fast reaction time to fault events
- Symmetrical design
- Low profile
- **CSA and TüV Approved, UL Recognised**

H = 0.7, W = 3.0, D = 1.4mm (Min.)

Operating temperature -40°C to +85°C Power Dissipation (Tripped) 0.4W
Max Surface Temp. (Tripped) 125°C


V max. (V)	I Hold (A) *	I Trip (A) **	Tripped power Dissipation (W)	Mfrs. List No.	Order Code
30	0.12	0.29	0.4	MF-NSMF012	120-6715
24	0.2	0.46	0.7	MF-NSMF020	120-6716
6	0.35	0.75	0.7	MF-NSMF035	120-6717
13.2	0.5	1.0	0.7	MF-NSMF050	120-6718
6	0.75	1.5	0.7	MF-NSMF075	120-6719
6	1.1	2.2	0.7	MF-NSMF110	120-6720
6	1.5	3.0	0.7	MF-NSMF150	120-6721

* I Hold - Current at which Multifuse will not trip

** I Trip - Current at which Multifuse will trip

437711

Order Multiple=5	Order Code	5+	50+	100+	250+	500+
Hold Current (A)						
0.12	SMD120-6715 ●	0.26	0.23	0.20	0.18	0.17
0.2	SMD120-6716 ●	0.26	0.23	0.20	0.18	0.17
0.35	SMD120-6717 ●	0.26	0.23	0.20	0.18	0.17
0.5	SMD120-6718 ●	0.26	0.23	0.20	0.18	0.17
0.75	SMD120-6719 ●	0.26	0.23	0.20	0.18	0.17
1.1	SMD120-6720 ●	0.26	0.23	0.20	0.18	0.17
1.5	SMD120-6721 ●	0.26	0.23	0.20	0.18	0.17

Multifuse MF - USMF Series
PTC - SMD 1210 Style

- Fast tripping resettable circuit protection
- Standard (1210) footprint for automated assembly
- Reduced component size and resistance
- **CSA and TüV Approved, UL Recognised**

H = 0.95, W = 3.2, D = 2.57mm

Operating temperature -40°C to +85°C Power Dissipation (Tripped) 0.6W
Max Surface Temp. (Tripped) 125°C

(A) *	(A) **	I max. (A)	V max. (V)	Resistance R min. (R) @ 23°C	Time to Trip s @ 23°C	Mfrs. List No.	Order Code
0.05	0.15	10	30	2.8	1.5	MF-USMF005	129-4881
0.10	0.3	10	30	0.8	0.6	MF-USMF010	129-4882
0.2	0.4	10	30	0.4	0.02	MF-USMF020	129-4883
0.35	0.75	40	6	0.2	0.2	MF-USMF035	129-4884
0.5	1.0	40	13.2	0.18	0.1	MF-USMF050	129-4885
0.75	1.5	40	6	0.07	0.1	MF-USMF075	129-4886
1.1	2.2	40	6	0.05	1.0	MF-USMF110	129-4887
1.5	3.0	40	6	0.03	5.0	MF-USMF150	129-4888

* I Hold - Current at which Multifuse will not trip

** I Trip - Current at which Multifuse will trip

449793

Order Multiple=5	Order Code	5+	50+	100+	250+	500+
Hold Current (A)						
0.05	SMD129-4881 ●	0.26	0.23	0.20	0.18	0.17
0.10	SMD129-4882 ●	0.26	0.23	0.20	0.18	0.17
0.2	SMD129-4883 ●	0.26	0.23	0.20	0.18	0.17
0.35	SMD129-4884 ●	0.26	0.23	0.20	0.18	0.17
0.5	SMD129-4885 ●	0.26	0.23	0.20	0.18	0.17
0.75	SMD129-4886 ●	0.26	0.23	0.20	0.18	0.17
1.1	SMD129-4887 ●	0.26	0.23	0.20	0.18	0.17
1.5	SMD129-4888 ●	0.26	0.23	0.20	0.18	0.17

Multifuse MF - MSMF Series
PTC - SMD 1812 Style

- Fast tripping resettable circuit protection
- Symmetrical design
- Standard footprint for automated assembly
- Reduced component size and resistance
- Compliant with AEC-Q200 Rev. C Stress Test Qualification
- **CSA and TüV Approved, UL Recognised**

Operating temperature -40°C to +85°C Power Dissipation (Tripped) 0.8W
Max Surface Temp. (Tripped) 125°C

(A) *	(A) **	Voltage Max	Case Style	Mfrs. List No.	Order Code
I Hold	I Trip	V dc			
0.10	0.30	60	1812	MF-MSMF010-2	935-0276
0.14	0.34	60	1812	MF-MSMF014-2	935-0284
0.20	0.40	30	1812	MF-MSMF020-2	935-0292
0.3	0.6	60	1812	MF-MSMF030-2	165-2168
0.35	0.75	30	1206	MF-NSMF035-2	935-0306
0.50	1.00	15	1812	MF-MSMF050-2	935-0314
0.75	1.50	13.2	1812	MF-MSMF075-2	935-0322
0.75	1.5	24	1812	MF-MSMF075/24-2	165-2169
1.10	2.20	6.0	1812	MF-MSMF110-2	935-0330



(A) *	(A) **	Voltage Max	Case	Mfrs.	
1.1	2.2	16	1812	MF-MSMF110/16-2	165-2170
1.25	2.50	6.0	1812	MF-MSMF125-2	935-0349
1.5	3.00	6.0	1812	MF-MSMF150-2	935-0357
1.6	2.8	8	1812	MF-MSMF160-2	165-2171
2	4	8	1812	MF-MSMF200-2	165-2172
2.5	5	16	1812	MF-MSMF250/16-2	165-2174
2.6	5.2	6	1812	MF-MSMF260-2	165-2176


* I Hold - Current at which Multifuse will not trip

** I Trip - Current at which Multifuse will trip

405882

Order Multiple=5	Order Code	5+	50+	100+	250+	500+
Hold Current (A)						
0.10	SMD935-0276 ● RL	0.32	0.29	0.26	0.23	0.22
0.14	SMD935-0284 ● RL	0.41	0.37	0.34	0.33	0.32
0.20	SMD935-0292 ● RL	0.32	0.29	0.26	0.23	0.22
0.3	NEW SMD165-2168 ●	0.17	0.15	0.13	0.12	0.11
0.35 *	SMD935-0306 ● RL	0.32	0.29	0.26	0.23	0.22
0.50	SMD935-0314 ● RL	0.32	0.29	0.26	0.23	0.22
0.75	SMD935-0322 ● RL	0.34	0.31	0.27	0.25	0.23
0.75	NEW SMD165-2169 ●	0.20	0.18	0.16	0.14	0.13
1.10	SMD935-0330 ● RL	0.32	0.29	0.26	0.23	0.22
1.1	NEW SMD165-2170 ●	0.20	0.18	0.16	0.14	0.13
1.25	SMD935-0349 ● RL	0.23	0.21	0.19	0.16	0.15
1.5	SMD935-0357 ● RL	0.22	0.19	0.17	0.15	0.14
1.6	NEW SMD165-2171 ●	0.17	0.15	0.13	0.12	0.11
2	NEW SMD165-2172 ●	0.17	0.15	0.13	0.12	0.11
2.5	NEW SMD165-2174 ●	0.35	0.30	0.27	0.24	0.22
2.6	NEW SMD165-2176 ●	0.20	0.18	0.16	0.14	0.13

* 1206 Case Style

Multifuse MF - SMDF Series
PTC - SMD 2018 Style

- Very low profile
- Very fast tripping time
- High voltage
- 2018 symmetrical footprint
- **CSA and TüV Approved, UL Recognised**

MF-SMDF050 - H = 0.79, W = 4.72, D = 4.22mm (Min.)

MF-SMDF150 - H = 0.55, W = 4.72, D = 4.22mm (Min.)

Operating temperature -40°C to +85°C Max Surface Temp. (Tripped) 125°C

V max. (V)	I Hold (A) *	I Trip (A) **	Time to Trip (s)	Tripped power Dissipation (W)	Mfrs. List No.	Order Code
60	0.55	1.2	3.0	1.0	MF-SMDF050	120-6724
15	1.5	3.0	0.8	1.1	MF-SMDF150	120-6725

* I Hold - Current at which Multifuse will not trip



** I Trip - Current at which Multifuse will trip

437712

Order Multiple=5	Order Code	5+	50+	100+	250+	500+
Hold Current (A)						
0.55	SMD120-6724 ●	0.30	0.27	0.24	0.23	0.20
1.5	SMD120-6725 ●	0.30	0.27	0.24	0.23	0.20

Multifuse MF - SM Series
PTC - SMD EIA 481-2 Style

- Surface mount overcurrent devices
- Industry standard EIA 481-2 standard package
- **CSA and TüV Approved, UL Recognised**

Terminal material:
Tin-plated brass

Order Codes		9350195, 9350209	9350217, 9350225	9350233, 9350241	9350250, 9350268					
V _{max} (V)		60	30	15	15					
I _{max} (I)		40	80	100	100					
Operating temperature (all Order Codes)										
-40°C to +85°C										
(A) *	(A) **	Dimensions (mm)				Mfrs. List No.	Order Code			
I Hold	I Trip	A Max	B Max	C Max	D & E Max	F Max	G Max	H Min		
0.3	0.6	7.98	5.44	3.18	0.71	2.41	1.37	0.43	MF-SM030-2-99	935-0195
0.5	1	7.98	5.44	3.18	0.71	2.41	1.37	0.43	MF-SM050-2-99	935-0209
0.75	1.5	7.98	5.44	3.18	0.71	2.41	1.37	0.43	MF-SM075-2-99	935-0217
1.1	2.2	7.98	5.44	3	0.71	2.41	1.37	0.43	MF-SM100-2-99	935-0225
1.25	2.5	7.98	5.44	3	0.71	2.41	1.37	0.43	MF-SM125-2-99	935-0233
1.50	3.00	7.98	6.71	3	0.71	2.41	1.37	0.43	MF-SM150-2-99	935-0241
2.00	4.00	7.98	6.71	3	0.71	2.41	1.37	0.43	MF-SM200-2-99	935-0250
2.50	5.00	9.5	6.71	3	0.71	2.41	1.37	0.43	MF-SM250-2-99	935-0268

* I Hold - Current at which Multifuse will not trip

** I Trip - Current at which Multifuse will trip

* I Hold - Current at which Multifuse will not trip

** I Trip - Current at which Multifuse will trip

405903


0.25	0.5	72	40	7.4	12.7	5.1	6	RXEF025	117-5860
0.3	0.6	72	40	7.4	13	5.1	6	RXEF030	117-5861
0.4	0.8	72	40	7.6	13.5	5.1	6	RXEF040	117-5862
0.5	1	72	40	7.9	13.7	5.1	6	RXEF050	117-5864
0.65	1.3	72	40	9.7	14.5	5.1	6	RXEF065	117-5867
0.75	1.5	72	40	10.4	15.2	5.1	6	RXEF075	117-5868
0.9	1.8	72	40	11.7	15.7	5.1	6	RXEF090	117-5869
1.35	2.70	72	40	14.5	19.1	5.08	7	RXEF135	134-5961
1.60	3.20	72	40	16.3	20.8	5.08	7	RXEF160	134-5962
1.85	3.70	72	40	17.5	22.4	5.08	7	RXEF185	134-5963
2.50	5.00	72	40	20.8	25.4	10.9	7	RXEF250	134-5964
3.00	6.00	72	40	23.9	28.6	10.9	7	RXEF300	134-5966
3.75	7.50	72	40	27.2	31.8	10.9	7	RXEF375	134-5967

I_H = Hold current. The maximum current at which the device will not trip at 20°C
 I_T = Trip current. The minimum current at which the device will always trip at 20°C

204468

Order Multiple=5		Price Each				
I_H Hold (A)	Order Code	5+	50+	100+	250+	500+
0.05	134-5959	0.390	0.360	0.320	0.280	0.260
0.1	117-5857	0.360	0.320	0.290	0.260	0.240
0.17	117-5858	0.360	0.320	0.290	0.260	0.240
0.2	117-5859	0.360	0.320	0.290	0.260	0.240
0.25	117-5860	0.360	0.320	0.290	0.260	0.240
0.3	117-5861	0.280	0.250	0.210	0.189	0.177
0.4	117-5862	0.320	0.290	0.260	0.240	0.210
0.5	117-5864	0.290	0.270	0.240	0.210	0.189
0.65	117-5867	0.350	0.320	0.280	0.260	0.240
0.75	117-5868	0.310	0.280	0.250	0.220	0.199
0.9	117-5869	0.330	0.290	0.260	0.220	0.210
1.10	134-5960	0.330	0.300	0.270	0.250	0.220
1.35	134-5961	0.330	0.300	0.270	0.250	0.220
1.60	134-5962	0.330	0.300	0.270	0.250	0.220
1.85	134-5963	0.370	0.330	0.300	0.270	0.250
2.50	134-5964	0.400	0.370	0.330	0.300	0.280
3.00	134-5966	0.420	0.390	0.340	0.320	0.290
3.75	134-5967	0.420	0.390	0.340	0.320	0.290

PolySwitch - RUE Series



RUE series of high current resettable fuses designed for applications that require a hold current between 0.9 and 9.0A, and a maximum voltage of 30V

Maximum voltage 30V Maximum interrupt current 40A
 Operating temperature -40°C to +85°C Typical reset time <20s
 Case meets the requirements of UL94V-0 Max surface temperature 125°C in tripped state
 Approved to CSA, TUV, and UL Recognised

Dimensions		Price Each				
I_H (A)	I_T (A)	A Max.	B Typ.	C Min.	D Max.	E Max.
0.9	1.8	7.4	12.2	5.1	7.6	3
1.1	2.2	7.4	14.2	5.1	7.6	3
1.35	2.7	8.9	13.5	5.1	7.6	3
1.6	3.2	8.9	15.2	5.1	7.6	3
1.85	3.7	10.2	15.7	5.1	7.6	3
2.5	5	11.4	18.3	5.1	7.6	3
3	6	11.4	17.3	5.1	7.6	3
4	8	14	20.1	5.1	7.6	3
5	10	14	24.9	10.2	7.6	3
6	12	16.5	24.9	10.2	7.6	3
7	14	19.1	26.7	10.2	7.6	3
8	16	21.6	29.2	10.2	7.6	3
9	18	24.1	29.7	10.2	7.6	3

I_H = Hold current. The maximum current at which the device will not trip at 20°C
 I_T = Trip current. The minimum current at which the device will always trip at 20°C


204467

Order Multiple=5		Price Each				
I_H Hold (A)	Order Code	5+	50+	100+	250+	500+
0.9	117-5843	0.310	0.280	0.250	0.220	0.199
1.1	117-5844	0.310	0.280	0.250	0.220	0.199
1.35	117-5845	0.340	0.310	0.280	0.250	0.210
1.6	117-5846	0.350	0.320	0.280	0.260	0.240
1.85	117-5847	0.370	0.330	0.300	0.270	0.250
2.5	117-5848	0.390	0.350	0.310	0.280	0.260
3	117-5849	0.410	0.370	0.330	0.300	0.280
4	117-5850	0.440	0.400	0.360	0.320	0.280
5	117-5851	0.470	0.420	0.380	0.340	0.290
6	117-5852	0.520	0.460	0.410	0.370	0.350
7	117-5854	0.720	0.650	0.570	0.510	0.480
8	117-5855	0.560	0.500	0.450	0.410	0.380
9	117-5856	0.620	0.570	0.540	0.520	0.490

PolySwitch - LVR Series



240V ac Voltage Rating



- Maximum operating voltage of 240V ac
- Maximum interrupt voltage of 265V ac
- UL, CSA and TUV (IEC) recognised

- Solid state - Able to withstand mechanical shock and thermal stress
- Low off state resistance






Power dissipated while tripped (W)	Current		Dimensions					Mfrs. List No.	Order Code
	Hold (A)	Trip (A)	A mm	B mm	C mm	D mm	E mm		
0.7	0.05	0.12	8.3	12.9	5.8	7.6	3.8	LVR005K	117-5831
0.8	0.08	0.19	8.3	12.9	5.8	7.6	3.8	LVR008K	117-5832
1.0	0.12	0.30	8.3	12.9	5.8	7.6	3.8	LVR012K	117-5833
1.4	0.16	0.37	9.9	13.8	5.8	7.6	3.8	LVR016K	117-5834
1.5	0.25	0.56	9.6	18.8	5.8	7.6	3.8	LVR025K	117-5835
1.7	0.33	0.74	11.4	19	5.8	7.6	3.8	LVR033K	134-5912
2.0	0.40	0.90	11.5	20.9	5.8	7.6	3.8	LVR040K	117-5836
3.4	0.55	1.25	14.0	22.4	3	7.6	4.1	LVR055K	134-5913
4.5	2.0	4.0	24.9	33.8	11.4	5.1	6.1	LVR200S	134-5914

346970/406028

Order Multiple=5		Price Each				
I_H Hold (A)	Fig.	Order Code	5+	50+	100+	500+
0.05	A	117-5831	0.42	0.38	0.34	0.28
0.08	A	117-5832	0.45	0.40	0.36	0.31
0.12	A	117-5833	0.46	0.42	0.37	0.32
0.16	A	117-5834	0.48	0.43	0.39	0.33
0.25	B	117-5835	0.53	0.47	0.42	0.38
0.33	B	134-5912	0.56	0.49	0.44	0.34
0.40	B	117-5836	0.60	0.54	0.48	0.41
0.55	B	134-5913	0.62	0.53	0.47	0.43
2.0	B	134-5914	0.58	0.51	0.46	0.38

PolySwitch - RGEF Series

16V - High Temperature



The RGEF series devices are rated for 16V and have hold current ranges from 2.5A to 14A. These products have tight trip-to-hold ratios. The RGEF devices are used in many applications including computer/multimedia, industrial equipment and controls, consumer and general electronics as well as motor protection.

These devices are CSA and TUV Approved, ELV Compliant and UL Recognised.

Dimensions		Price Each				
I_H (A)	I_T (A)	V_{max} (V dc)	I_{max} (A)	A Max.	B Max.	C Nom.
2.5	4.7	16	100	8.9	12.8	5.08
3.0	5.1	16	100	7.1	11	5.08
4.0	6.8	16	100	8.9	12.8	5.08
5.0	8.5	16	100	10.4	14.3	5.08
6.0	10.2	16	100	10.7	17.1	5.08
7.0	11.9	16	100	11.2	19.7	5.08
8.0	13.6	16	100	12.7	20.9	5.08
9.0	15.3	16	100	14.0	21.7	5.08
10.0	17.0	16	100	16.5	25.2	5.08
11.0	18.7	16	100	17.5	26	5.08
12.0	20.4	16	100	17.5	28	10.9
14.0	23.8	16	100	23.5	27.9	10.9


I_H = Hold current. The maximum current at which the device will not trip at 25°C
 I_T = Trip current. The minimum current at which the device will always trip at 20°C

464451

Order Multiple=5		Price Each				
I_H Hold (A)	Order Code	5+	50+	100+	250+	500+
2.5	134-5946	0.36	0.34	0.28	0.26	0.25
3.0	134-5947	0.36	0.34	0.28	0.26	0.25
4.0	134-5948	0.37	0.35	0.29	0.27	0.25
5.0	134-5949	0.37	0.35	0.29	0.27	0.25
6.0	134-5950	0.39	0.37	0.32	0.29	0.27
7.0	134-5951	0.41	0.39	0.34	0.31	0.28
8.0	134-5952	0.45	0.42	0.37	0.34	0.32
9.0	134-5954	0.49	0.46	0.40	0.37	0.35
10.0	134-5955	0.59	0.56	0.49	0.45	0.42
11.0	134-5956	0.59	0.56	0.49	0.45	0.42
12.0	134-5957	0.63	0.60	0.52	0.48	0.45
14.0	134-5958	0.69	0.65	0.56	0.52	0.49

PolySwitch - AGRF Series

Automotive Applications



The AGRF series devices are qualified to operate in automotive environments as per the AEC-Q200 Stress Test Qualification for Passive Electronics in automotive applications. This specification requires devices to pass a rigorous test plan designed for automotive environments. Raychem Circuit Protection's document PS400.

These devices are ELV Compliant.

Maximum voltage 16V dc Operating temperature -40°C to +85°C
 Maximum interrupt current 100A Note: Devices are not designed for reflow process.

Resettable Fuses - continued

PolySwitch - AGRF Series - continued

Automotive Applications - continued

Dimensions						
I _H (A)	I _T (A)	A Max.	B Max.	C Typ	Mfrs. List No.	Order Code
4	7.6	8.90	14.1	5.08	AGRF400	134-5892
5	9.4	10.4	15.6	5.08	AGRF500	134-5893
6	10.7	10.7	18.4	5.08	AGRF600	134-5894
7	13.2	11.2	21	5.08	AGRF700	134-5895
8	15.0	12.7	22.2	5.08	AGRF800	134-5896
9	16.5	14.0	23	5.08	AGRF900	134-5897
10	18.5	16.51	25.7	5.08	AGRF1000	134-5899
11	20.3	17.5	26.5	5.08	AGRF1100	134-5900
12	22.1	17.5	28.8	10.9	AGRF1200	134-5901
14	27.3	23.5	28.7	10.9	AGRF1400	134-5902


I_H = Hold current. The maximum current at which the device will not trip at 20°C
 I_T = Trip current. The minimum current at which the device will always trip at 20°C

464175

Price Each						
Order Multiple=5 I Hold (A)	Order Code	5+	50+	100+	250+	500+
4	134-5892●	0.46	0.41	0.36	0.33	0.27
5	134-5893●	0.46	0.41	0.36	0.33	0.27
6	134-5894●	0.49	0.44	0.38	0.35	0.29
7	134-5895●	0.40	0.36	0.31	0.29	0.24
8	134-5896●	0.56	0.50	0.44	0.40	0.34
9	134-5897●	0.61	0.55	0.48	0.43	0.37
10	134-5899●	0.74	0.66	0.58	0.52	0.45
11	134-5900●	0.74	0.66	0.58	0.52	0.45
12	134-5901●	0.80	0.71	0.62	0.56	0.48
14	134-5902●	0.87	0.78	0.68	0.61	0.52

PolySwitch - TRF Series

Short duration, High voltage Protection



These products are radial leaded devices that help protect against short duration high voltage faults (250 - 600V rms). They are specifically designed to help meet the protection needs of telecommunications applications.

These devices are **CSA** and **TUV** Approved and **UL** Recognised.

Dimensions						
I _H (A)	I _T (A)	V _{max} (V dc)	I _{max} (A)	A Max.	B Max.	C Max.
0.120	0.24	60	3.0	6.5	11	4.6
0.145	0.29	60	3.0	6.5	11	4.6
0.180	0.65	100	10.0	9.0	12	3.8
0.150	0.30	60	3.0	9.0	12.5	4.6
0.160	0.32	250	3.0	16.0	12.6	6



I_H = Hold current. The maximum current at which the device will not trip at 20°C
 I_T = Trip current. The minimum current at which the device will always trip at 20°C

464683

Price Each						
Order Multiple=5 I Hold (A)	Order Code	5+	50+	100+	250+	500+
0.120	134-5980●	0.49	0.44	0.39	0.35	0.31
0.145	134-5981●	0.49	0.44	0.39	0.35	0.31
0.180	134-5982●	0.53	0.47	0.42	0.37	0.34
0.150	134-5984●	0.76	0.67	0.58	0.52	0.47
0.160	134-5985●	0.84	0.74	0.65	0.58	0.53

PolySwitch - SRP Series

Strap Battery Pack Devices



The SRP series of products provide reliable non-cycling protection for rechargeable batteries. Weldable nickel leads and a narrow, low-profile design make these devices easy to install directly onto battery cells.

These products are not designed to be re-flow solder process compatible.



These devices are **CSA** and **TUV** Approved, **ELV** Compliant and **UL** Recognised.

Dimensions						
I _H (A)	I _T (A)	V _{max} (V dc)	I _{max} (A)	A Max.	B Max.	C Typ
1.2	2.7	15	100	22.1	5.2	1
1.75	3.8	15	100	23.1	5.2	1
2.0	4.4	30	100	23.4	11	1.1
3.5	6.3	30	100	31.8	13.5	1.1
4.2	7.6	30	100	32.4	13.6	1.1

I_H = Hold current. The maximum current at which the device will not trip at 20°C
 I_T = Trip current. The minimum current at which the device will always trip at 20°C

464667

Price Each						
Order Multiple=5 I Hold (A)	Order Code	5+	50+	100+	250+	2K+
1.2	134-5974●	0.270	0.220	0.192	0.168	0.153
1.75	134-5975●	0.360	0.310	0.260	0.220	0.200
2.0	134-5976●	0.360	0.310	0.260	0.220	0.200
3.5	134-5978●	0.360	0.310	0.260	0.220	0.200
4.2	134-5979●	0.360	0.310	0.260	0.220	0.200

PolySwitch - LR4 Series
Strap Battery Pack Devices

The LR4 devices small thermal mass enables reduced reaction time to over-current events. These products are suited for battery packs intended for computer and camcorder applications.

These devices are **CSA** and **TUV** Approved, **ELV** Compliant and **UL** Recognised.

Maximum voltage - 1.9A to 3.8A I_H 15V dc
 Maximum voltage - 4.5A to 9A I_H 20V dc
 Maximum trip current 100A
 Operating temperature -40°C to +60°C
 Note: Devices are not designed for reflow process.

Dimensions						
I _H (A)	I _T (A)	A Max.	B Max.	C Typ	Mfrs. List No.	Order Code
1.9	3.9	22.1	5.5	1	LR4-190F	134-5903
2.6	5.8	23.1	5.5	1	LR4-260F	134-5905
3.8	8.3	26.0	7.5	1	LR4-380F	134-5906
4.5	8.9	26.0	10.5	1	LR4-450F	134-5907
5.5	10.5	37.0	7.5	1	LR4-550F	134-5908
6.0	11.7	26.0	14.5	1	LR4-600F	134-5909
9.0	16.7	47.6	8.5	1.3	LR4-900F	134-5911

I_H = Hold current. The maximum current at which the device will not trip at 20°C
 I_T = Trip current. The minimum current at which the device will always trip at 20°C

464237

Price Each						
Order Multiple=5 I Hold (A)	Order Code	5+	50+	100+	250+	1K+
2.6	134-5905●	0.51	0.45	0.40	0.36	0.31
3.8	134-5906●	0.56	0.49	0.43	0.40	0.34
4.5	134-5907●	0.59	0.52	0.46	0.42	0.36
5.5	134-5908●	0.65	0.57	0.50	0.46	0.39
6.0	134-5909●	0.73	0.64	0.57	0.52	0.44
9.0	134-5911●	0.66	0.57	0.50	0.46	0.39

8 x 31 mm HRC Cartridge Fuses

gL/gG (General Line)



Voltage rating 400V ac
 Breaking capacity 20kA

- European style industrial ceramic fuses for cable protection and applications where there are no surges to be absorbed
- Manufactured in accordance with **IEC 269**
- Approved by **Lloyds Register of shipping** and **Bureau Veritas**

204541

Price Each						
Order Multiple=5 Rating	Mfrs. List No.	Order Code	5+	25+	100+	250+
2A	Q219227	302-8677	0.57	0.53	0.49	0.47
4A	W222958	302-8689	0.57	0.53	0.49	0.47
6A	A211025	302-8690	0.57	0.53	0.49	0.47
10A	A214613	302-8707	0.57	0.53	0.49	0.47
16A	P216650	302-8719	0.57	0.53	0.49	0.47

Fuseholders, DIN Rail Mounting



- Approved by **Lloyds Register of Shipping** and **Bureau Veritas**

H=78, W=17.5, D(inc. lever)=59
 Terminal capacity = 16mm Rating 25A @ 400V ac

204542

Price Each				
Mfrs. List No.	Order Code	1+	10+	25+
Single Pole	T219253	302-8744	2.96	2.80
			2.74	2.69

Over 480,000 products online



10 x 35mm Cartridge Fuses

High Performance Fast Acting - 10.3 x 35mm
Suitable For Multimeters

- UL recognised

Voltage rating 1000V ac/dc
Breaking capacity 10000A @ 1000V ac/dc

204530

Rating	Mfrs. List No.	Order Code	1+	5+	25+
440mA	OFLU.440T.TA000	994-3331●	8.42	7.83	7.49

High Performance Fast Acting - 10.3 x 35mm
BLS Series - Suitable For Multimeters

- For high ac fault current circuitry
- UL recognised
- CSA approved

Voltage rating 600V ac
Breaking capacity 10000A @ 600V ac/dc

204531

Rating	Mfrs. List No.	Order Code	1+	10+	25+
1A	BLS1	994-3307●	2.90	2.60	2.31
3A	BLS3	994-3315●	2.90	2.60	2.31

Fast Acting - Multi-meter Protection
DMM-B Series

- Designed for Multi-meters only
- Intended to carry 100% of rated current indefinitely
- NOT intended for branch circuit protection
- Melamine Tube with Nickel Plated Endcaps
- UL Recognised

Voltage rating 1000V/dc
Interrupting Rating - DMM-B-11A 20kA
Interrupting Rating - DMM-B-44/100 10kA

444865

Fuse Rating	Mfrs. List No.	Order Code	1+	5+	10+	25+	50+
11A	DMM-B-11A	124-1956	7.97	7.69	7.50	7.31	7.02
440mA	DMM-B-44/100	124-1957	7.97	7.69	7.50	7.31	7.02

10 x 38 mm HRC Cartridge Fuses

High Performance Fast Acting - 10.3 x 38mm
Suitable For Multimeters

- UL recognised

Voltage rating 1000V ac
Breaking capacity 17000A @ 250V ac/dc

204529

Rating	Mfrs. List No.	Order Code	1+	5+	25+
11A	OFLU011.T.TA000	994-3340●	8.42	7.83	7.49

High Performance Fast Acting - 10.3 x 38mm
CLK Series - Suitable For Multimeters

- For high ac fault current circuitry
- UL recognised (to 3A)
- CSA approved

Voltage rating 600V ac
Breaking capacity 100000A @ 600V ac

204527

Rating	Mfrs. List No.	Order Code	1+	10+	25+
1A	OKLK001.T	994-3218●	3.29	2.98	2.67
2A	OKLK002.T	994-3226●	3.29	2.98	2.67
3A	OKLK003.T	994-3234●	3.29	2.98	2.67
4A	OKLK004.T	994-3242●	3.26	2.95	2.65
5A	OKLK005.T	994-3250●	3.29	2.98	2.67
10A	OKLK010.T	994-3269●	3.29	2.98	2.67
15A	OKLK015.T	994-3277●	3.29	2.98	2.67
20A	OKLK020.T	994-3285●	3.29	2.98	2.67
30A	OKLK030.VX832	994-3293●	3.29	2.98	2.67

Over 480,000 products online

High Performance Fast Acting - 10.38 x 38
KTK Series Suitable for Multimeters

- For high ac fault current circuitry
- UL Recognised
- CSA certified

Voltage rating 600V
Breaking capacity 100000A @ 600V

227525

Rating	Mfrs. List No.	Order Code	1+	10+	25+
0.5A	KTK-1/2	348-2819	3.71	3.38	3.23
1A	KTK-1	348-2820	3.06	2.78	2.66
1.5A	KTK-1-1/2	348-2832	3.05	2.85	2.73
2A	KTK-2	348-2844	3.06	2.78	2.66
3A	KTK-3	348-2856	3.06	2.79	2.66
5A	KTK-5	348-2870	3.06	2.79	2.66
6A	KTK-6	348-2881	3.05	2.85	2.73
8A	KTK-8	348-2900	3.85	3.59	3.42
10A	KTK-10	NEW 161-5090▲	3.02	2.65	2.47
12A	KTK-12	NEW 161-5091▲	3.02	2.65	2.47
15A	KTK-15	NEW 161-5092▲	3.02	2.65	2.47
20A	KTK-20	NEW 161-5093▲	3.02	2.65	2.47
25A	KTK-25	NEW 161-5094▲	3.02	2.65	2.47
30A	KTK-30	NEW 161-5095▲	3.02	2.65	2.47

High Performance Quick Blow (F) - 10.3 x 38
KTK-R Series

High performance, fast acting, single-element ceramic fuses for protection of branch circuits, motor control circuits, lighting ballasts and control transformers. A grooved ferrule permits mounting in rejection-type as well as standard fuseholders. UL Recognised and CSA approved.

Voltage rating 600V ac
Breaking capacity 200000A @ 600V ac

204412

Rating	Rating	Order Code	1+	10+	50+	100+
0.5A	KTK-R-1/2	NEW 161-5096▲	6.03	5.30	4.93	4.57
1A	KTK-R-1	218-923	5.15	4.48	4.15	3.97
2A	KTK-R-2	218-935	5.92	4.93	4.21	3.97
3A	KTK-R-3	NEW 161-5097▲	6.03	5.30	4.93	4.57
4A	KTK-R-4	218-947	7.01	6.30	5.60	5.32
5A	KTK-R-5	218-959	5.92	4.93	4.21	3.97
6A	KTK-R-6	NEW 161-5098▲	6.03	5.30	4.93	4.57
8A	KTK-R-8	NEW 161-5100▲	6.03	5.30	4.93	4.57
10A	KTK-R-10	218-960	5.92	4.93	4.21	3.97
15A	KTK-R-15	218-972	5.92	4.93	4.21	3.97
20A	KTK-R-20	218-984	6.16	5.13	4.39	4.12
25A	KTK-R-25	NEW 161-5102▲	6.03	5.30	4.93	4.57
30A	KTK-R-30	218-996	5.97	4.97	4.24	3.99

gR Ultra Rapid Semiconductor Fuses



- European style industrial ceramic ultra rapid fuses for protection of thyristors, diodes etc.
- UL Recognised

Rating 600Vac

Current Rating	Voltage Power Dissipation (W)	Pre-arcing I ² t	Total I ² t @ 600V	Order Code
4A	1.1	1.1	6	607-745
6A	1.8	6	18	607-757
10A	1.7	9	28	607-769
16A	4.8	36	120	607-770
20A	5.8	60	200	607-782
25A	6.8	120	420	607-794
30A	7.8	195	650	607-800

Mfrs. List No. 60-033-05 + Rating

204397

Rating	Order Code	1+	10+	100+	200+
4A	607-745	4.48	4.10	3.94	3.76
6A	607-757	4.48	4.10	3.94	3.76
10A	607-769	4.48	4.10	3.94	3.76
16A	607-770	4.48	4.10	3.94	3.76
20A	607-782	4.48	4.10	3.94	3.76
25A	607-794	4.48	4.10	3.94	3.76
30A	607-800	4.48	4.10	3.94	3.76

700 products added online every week



See our pick of the hottest products and latest technologies in 'What's New?' at www.farnell.co.uk



Fuses & Circuit Breakers

10 x 38 mm HRC Cartridge Fuses - continued

gL (General Line)



European style industrial HRC ceramic fuses manufactured in accordance with **IEC269-2**, **NFC63-210** and **UNE21.103**. Suitable for cable protection and applications where there are no surges to be absorbed.

Voltage rating 500V (32A 499493 = 400V) Breaking capacity 120000 204429

Order Multiple=5		Price Each			
Rating	Order Code	5+	25+	100+	250+
2A	248-708	0.54	0.52	0.50	0.49
4A	248-710	0.54	0.52	0.50	0.49
6A	248-721	0.54	0.52	0.50	0.49
10A	248-733	0.54	0.52	0.50	0.49
16A	248-745	0.54	0.52	0.50	0.49
20A	499-470	0.62	0.55	0.54	0.53
25A	499-481	0.61	0.54	0.53	0.52
32A	499-493	0.60	0.54	0.52	0.51

aM (Motor Rated)




European style industrial HRC ceramic fuses manufactured in accordance with **IEC269-2**, **NFC63-210** and **UNE21.103**. Suitable for applications where an initial surge has to be absorbed (i.e. motor starts).

Voltage rating 500V ac (248-691 = 400V ac) Breaking capacity 120000 204428

Order Multiple=5		Price Each			
Rating	Order Code	5+	25+	100+	250+
2A	248-630	0.68	0.63	0.61	0.60
4A	248-642	0.67	0.62	0.58	0.56
6A	248-654	0.67	0.62	0.58	0.56
10A	248-666	0.67	0.62	0.58	0.56
16A	248-678	0.67	0.62	0.58	0.56
20A	248-680	0.73	0.68	0.65	0.63
25A	248-691	0.89	0.81	0.77	0.76
32A	143-6845●	0.81	0.74	0.71	0.70

Fuse Clips



PCB drilling plan

PCB mounting bright tinned spring bronze fuse clips suitable for all 1 1/2" (10 x 38mm) cartridge fuses.

Rating 20A (dependent on track size of PCB) Mfrs. List No. 1A3400-09 204413

2 Per Pack		Price Per Pack			
Order Code	1+	5+	25+	50+	
120-5149●	0.58	0.46	0.40	0.34	

10 x 38mm (13/32" x 1 1/2") Fuseholder

Waterproof - In-Line



- Non-Breakaway, in line fuse holders
- Copper crimp terminal on load and line side
- Rated at 30A @ 600V

- 161-5119 is **CSA**, **CE** Approved and **UL** Recognised
- 161-5120 is **CSA** Approved

515114

Conductor Size	Mfrs. List No.	Order Code	1+	10+	50+
12AWG to 8AWG	HEB-AA	161-5119▲	14.29	13.43	11.43
10AWG to 6AWG	HEB-BB	161-5120▲	15.66	14.72	12.53

Fuseholders, DIN Rail Mounting



Single pole
H=78, W=17.5,
D (inc. lever)=73.5
D (excl. lever)=58
Terminal capacity=16mm²
Rating 32A @ 400V

Triple pole
H=78, W=52.5
D (inc. lever)=75.5
D (excl. lever)=52
Terminal capacity=16mm²
Rating 32A @ 400V

204427

	Order Code	Price Each			
		1+	10+	25+	50+
Single Pole	248-757	3.52	2.88	2.49	2.20
Triple Pole	542-787	11.70	11.09	10.53	10.28

14 x 51 mm HRC Cartridge Fuses

gR, gL and aM Lines



gR Ultra Rapid Semiconductor Fuses

- European style industrial ceramic ultra rapid fuses for protection of thyristors, diodes, small speed drives, etc.
- **UL** recognised
- Voltage rating 700Vac (UL), 660Vac (IEC)
- Power dissipation: 6 to 10W

Mfrs. List No: 50-124-06+Rating

Rating (A)	Pre-arcing I _{pt}	Total I _{pt} @660V	Order Code	1+	10+	100+	250+
20	21	190	187-161	4.50	4.20	4.02	3.84
25	32	340	187-173	4.50	4.20	4.02	3.84
32	63	620	187-185	4.63	4.32	4.14	3.94
40	140	1050	187-197	4.63	4.32	4.14	3.94
50	250	1900	143-6844●	4.71	4.53	4.30	4.21

gL (General Line)

- European style industrial ceramic fuses for cable protection and applications where there are no surges to be absorbed
- Manufactured in accordance with **IEC 269-2**, **NFC60.200**, **63.210**, **63.211** and **UNE21.108**
- Approved by **Lloyds Register of Shipping** and **Bureau Veritas**

Voltage rating 690Vac (20A, 25A) Breaking capacity 80kA (20A, 25A)
500Vac (32A, 40A) 120kA (32A upwards)
400Vac (50A)

Order Multiple=5		Price Each			
Rating (A)	Order Code	5+	25+	100+	250+
20	187-306	0.85	0.79	0.75	0.72
25	187-203	1.09	1.05	0.98	0.92
32	187-215	0.85	0.79	0.75	0.72
40	187-227	0.85	0.79	0.75	0.72
50	187-239	1.15	1.11	1.04	0.98

aM (Motor Rated)

- European style industrial HRC fuses for applications where an initial surge has to be absorbed (i.e. motor start)
- Manufactured in accordance with **IEC 269-2**, **NFC60.200**, **63.210**, **63.211** and **UNE21.103**
- Approved by **Lloyds Register of Shipping** and **Bureau Veritas**

Voltage rating 690Vac (20A, 25A) Breaking capacity 80kA (20A, 25A)
500Vac (32A, 40A) 120kA (32A upwards)
400Vac (50A)

Order Multiple=5		Price Each			
Rating (A)	Order Code	5+	25+	100+	250+
20	187-240	1.16	1.10	1.06	1.04
25	187-252	1.16	1.10	1.06	1.04
32	187-264	1.11	1.09	1.02	0.96
40	187-276	1.15	1.12	1.06	1.05
50	187-288	1.18	1.15	1.10	1.07

Fuseholder for 14 x 51mm fuses

- Manufactured in accordance with **IEC 269-2**, **947-3**, **NFC63.210-63001**, **VDE0636-1** and **UNE 20129-21103**
- Approved by **Lloyds Register of Shipping** and **Bureau Veritas**

H=106, W=26, D(inc. lever)=81, D(excl. lever)=61.6, Terminal capacity=16mm²

Voltage rating 690Vac (up to 25A)
500Vac (32A, 40A)
400Vac (50A)

204376

	Order Code	Price Each			
		1+	5+	20+	50+
Single Pole Fuseholder	187-290	7.58	7.43	7.18	6.92

22 x 58 mm HRC Cartridge Fuses

gR and aM Lines



gR Ultra Rapid Semiconductor Fuses

- European style industrial ceramic ultra rapid fuses for protection of thyristors, diodes, power transistors etc.
- **UL** recognised

Voltage rating 700V ac (UL), 600V ac IEC
Power dissipation 9.6 to 19W
Breaking capacity 200kA

Mfrs. List No. 50-140-06+Rating (standard)

Rating (A)	Pre-arcing I ² t	Total I ² t @ 660V	Order Code	1+	10+	100+	200+
Standard							
32	63	315	329-5497	9.16	8.37	7.44	6.76
40	140	610	329-5503	12.42	11.43	10.14	9.25
50	210	910	329-5515	12.42	11.43	10.14	9.25
63	510	2260	329-5527	12.54	11.61	10.25	9.37
80	1000	4400	329-5539	12.54	11.61	10.25	9.37
100	2050	8900	329-5540	14.93	13.84	12.28	11.07

aM (Motor Rated)

- European style industrial HRC fuses for applications where an initial surge has to be absorbed (e.g. motor start)
- Manufactured in accordance with IEC 269-3-1, NFC61.201 and UNE21.103
- Approved by Lloyds Register of Shipping and Bureau Veritas

Voltage rating 660Vac (up to 80A) Breaking capacity 80kA (up to 80A)

Rating (A)	Order Code	1+	10+	100+	200+
63	329-5655	1.81	1.66	1.49	1.35
80	329-5667	1.90	1.73	1.56	1.39

Fuseholder for 22 x 58mm fuses

- Manufactured in accordance with IEC 269-2-1, 947-3, NFC63210-63001, VDE0636-1 and UNE20129-21103
- Approved by Lloyds Register of Shipping and Bureau Veritas

Voltage rating 660V ac (up to 80A) Breaking capacity 80kA (up to 80A)
500V ac (100A)
400V ac (125A)H = 140, W = 35, D (incl. lever) = 88, D (excl. lever) = 58, Terminal capacity = 16mm²

227526

	Order Code	1+	10+	25+	50+
Single Pole Fuseholder	329-5692	12.89	11.60	10.95	10.31

BS1361 Style**Bussmann**

Domestic and industrial consumer unit fuses manufactured to comply with BS1361. ASTA certified.

Voltage rating 240V ac
Breaking capacity 16.5kA

Current rating	L	Dia.	Mfrs. List No.	Order Code
5A	23	4.8	TDC119 5A.	540-365
15A	26	10	TDC120 15A.	540-377
20A	26	10	TDC120 20A.	540-389
30A	29	12.7	TDC121 30A.	540-390
45A	35	16.67	TDC122 45A.	540-407

204441

Order Multiple=5	Current Rating	Order Code	5+	25+	100+	250+
	5A	540-365	0.49	0.44	0.40	0.39
	15A	540-377	1.18	1.07	1.01	0.94
	20A	540-389	1.00	0.87	0.85	0.80
	30A	540-390	1.16	1.06	1.00	0.94
	45A	540-407	1.76	1.59	1.52	1.42

Industrial HRC Fuses and Fuseholders**Low Voltage Industrial HRC****Bussmann**


Industrial HRC fuselinks to BS88 and IEC269 (parts 1 and 2) available in general purpose and dual rated motor circuit styles.

Voltage rating	550V ac		Breaking capacity		80kA
Size	Overall Length	Diameter	Fixing Centres	Suitable Fuseholder	Mfrs List No.
F1 (NS)	58.7	13.8	—	556-154	NSD
A1	54.5	13.8	44.5	556-361	NITD
A2	85	13.8	73	556-373	AAO
A3	87	21.4	73	556-385	BAO
A4	111	21.4	94	177-607	CEO

204453




Fuse Rating	Mfrs. List No.	Order Code	1+	20+	50+	100+
Size F1 — Offset Blade Tag - NSD						
2A	NSD2A	120-2348	1.47	1.41	1.32	1.29
4A	NSD4A	120-2349	1.47	1.41	1.32	1.29
6A	NSD6A	120-2350	1.47	1.41	1.32	1.29
10A	NSD10A	120-2351	1.47	1.41	1.32	1.29
16A	NSD16A	120-2353	1.52	1.44	1.37	1.32
20A	NSD20A	120-2354	1.53	1.49	1.39	1.32
25A	NSD25A	120-2409	2.06	1.95	1.85	1.82
32A	NSD32A	120-2410	2.06	1.95	1.85	1.82
Size A1 — Open Ended Slotted Tag - NITD						
2A	NITD2A	120-2355	1.35	1.20	1.17	1.15
4A	NITD4A	120-2356	1.46	1.31	1.28	1.25
6A	NITD6A	120-2357	1.46	1.31	1.28	1.25
10A	NITD10A	120-2358	1.46	1.31	1.28	1.25
16A	NITD16A	120-2359	1.53	1.39	1.32	1.30
20A	NITD20A	120-2360	1.92	1.71	1.67	1.62
25A	NITD-25A	120-2411	2.06	1.95	1.85	1.82
32A	NITD-32A	120-2412	2.06	1.95	1.85	1.82
20A	NITD-20M25A	120-2413	2.04	1.82	1.76	1.73
20A	NITD20M32A	120-2361	2.22	1.98	1.93	1.90
32A	NITD-32M40A	120-2414	3.95	3.55	3.44	3.37
32A	NITD-32M63A	120-2415	3.67	3.31	3.21	3.15
Size A2 — Offset Bolted Tag - AAO						
2A	AAO-2A	120-2416	2.11	2.05	1.90	1.85
4A	AAO-4A	120-2417	2.29	2.22	2.06	2.01
6A	AAO6A	120-2362	2.32	2.07	2.02	1.98
10A	AAO10A	120-2363	2.13	1.91	1.86	1.83
16A	AAO16A	120-2365	2.55	2.28	2.20	2.15
20A	AAO20A	120-2366	2.55	2.28	2.20	2.15
25A	AAO25A	120-2367	2.69	2.42	2.36	2.29
32A	AAO32A	120-2368	2.69	2.42	2.36	2.29
32M40A	AAO-32M40A	120-2419	3.28	2.96	2.86	2.80
32M50A	AAO-32M50A	120-2421	3.10	2.78	2.70	2.64
32M63A	AAO-32M63A	120-2422	3.91	3.50	3.41	3.33
Size A3 — Offset Bolted Tag - BAO						
40A	BAO40A	120-2369	4.29	3.89	3.70	3.62
50A	BAO50A	120-2370	4.29	3.89	3.70	3.62
63A	BAO63A	120-2371	4.92	4.43	4.26	4.18
63M80A	BAO63M80A	120-2423	7.46	6.54	6.31	6.03
63M100A	BAO63M100A	120-2424	7.79	6.83	6.60	6.25
Size A3 - OSD						
80A	OSD80A	120-2385	7.25	6.55	6.14	6.02
100A	OSD100A	120-2386	7.80	6.83	6.62	6.50
Size A4 — Offset Bolted Tag - CEO						
100A	CEO100A	120-2372	9.37	8.79	8.26	7.81
100M125A	CEO100M125A	120-2425	10.89	9.56	9.25	9.06
100M160A	CEO100M160A	120-2426	9.55	8.37	8.10	7.94
CEO - Offset Bolted Tag						
32M200A	CEO32	NEW 161-5070	6.96	6.59	6.22	5.73
40M200A	CEO40	NEW 161-5071	6.96	6.59	6.22	5.73
50M200A	CEO50	NEW 161-5072	6.96	6.59	6.22	5.73
63M200A	CEO63	NEW 161-5073	6.96	6.59	6.22	5.73
80M200A	CEO80	NEW 161-5074	6.96	6.59	6.22	5.73
DEO - Offset Bolted Tags						
125M200A	DEO125	NEW 161-5076	13.36	12.65	11.93	10.97
160M200A	DEO160	NEW 161-5077	13.36	12.65	11.93	10.97
200M200A	DEO200	NEW 161-5078	13.36	12.65	11.93	10.97
ED - Center Bolted Tags						
250M200A	ED250	NEW 161-5079	17.34	16.41	15.48	14.24
315M200A	ED315	NEW 161-5080	17.34	16.41	15.48	14.24
400M200A	ED400	NEW 161-5081	17.34	16.41	15.48	14.24
ESD - Offset Blade Tags						
16M200A	ESD16	NEW 161-5082	3.02	2.85	2.69	2.48
20M200A	ESD20	NEW 161-5083	3.02	2.85	2.69	2.48
25M200A	ESD25	NEW 161-5084	3.02	2.85	2.69	2.48
32M200A	ESD32	NEW 161-5085	3.02	2.85	2.69	2.48
40M200A	ESD40	NEW 161-5086	3.02	2.85	2.69	2.48
50M200A	ESD50	NEW 161-5088	3.02	2.85	2.69	2.48
63M200A	ESD63	NEW 161-5089	3.02	2.85	2.69	2.48

Semi-conductor Protection Fuses**Bussmann**

Industrial HRC Fuses and Fuseholders - continued

Semi-conductor Protection Fuses - continued



Designed for semiconductor protection

240 Volt RMS Series

Rating (A)	Max Power Loss (Watts)	I ² Rating (A ² S)		Former IR List No.	Bussmann List No.	Order Code
		Pre-Arcing (Min)	Max @ 120V			
10	2.5	3.8	12	A350-10	10LCT	120-2309
16	2.5	20	50	A350-16	16LCT	120-2310
20	4	25	80	A350-20	20LCT	120-2311
7	1.5	1.7	10	L350-7	7LET	120-2312
10	1.8	3.8	23	L350-10	10LET	120-2313
12	2	7	42	L350-12	12LET	120-2314
16	2.5	15	70	L350-16	16LET	120-2316
25	4	19	120	L350-25	25LET	120-2317
32	5	32	200	L350-32	32LET	120-2318
35	5	51	320	L350-35	35LET	120-2319
50	7	100	500	—	50LET	120-2429
63	9	180	1100	L350-63	63LET	120-2320
80	10	300	1900	L350-80	80LET	120-2321
100	10	600	3800	L350-100	100LET	120-2322
125	16	600	3800	L350-125	125LET	120-2323
160	20	1100	7000	L350-160	160LET	120-2324
160	17	1100	7000	—	160LMT	120-2326
180	21	1800	12000	L350-180	180LET	120-2325

660 Volt RMS Series

Rating (A)	Max Power Loss (Watts)	I ² Rating (A ² S)		Former IR List No.	Bussmann List No.	Order Code
		Pre-Arcing (Min)	Max @ 415V			
12	3.7	38	55	E1000-12	12ET	120-2329
15	4.6	11	60	E1000-15	15ET	120-2330
20	7.5	18	100	E1000-20	20ET	120-2331
25	7	24	150	E1000-25	25ET	120-2332
32	11	32	190	E1000-32	32ET	120-2333
40	9	100	600	E1000-40	40ET	120-2334
56	14	160	950	E1000-56	56ET	120-2335
80	18	410	2500	E1000-80	80ET	120-2336
65	20	210	1100	EE1000-65	65EET	120-2337
75	20	420	2000	EE1000-75	75EET	120-2338
90	19	480	3000	EE1000-90	90EET	120-2341
110	27	600	4000	EE1000-110	110EET	120-2342
160	26	2400	15000	M1000-160	160MT	120-2343
355	54	18000	100000	MM1000-355	355MMT	120-2347

Former IR product List No. are electrically identical to Bussmann List No. IR's range of fuses were manufactured by Bussmann and then re-branded.

204609

Current Rating	Order Code	Price Each			
		1+	20+	40+	100+
240 Volt RMS Series					
10A	120-2309●	2.63	2.45	2.34	2.23
16A	120-2310●	2.63	2.45	2.34	2.23
20A	120-2311●	2.63	2.45	2.34	2.23
		1+	10+	50+	100+
7A	120-2312●	5.89	5.40	5.17	5.07
10A	120-2313●	5.89	5.40	5.17	5.07
12A	120-2314●	5.97	5.29	4.96	4.86
16A	120-2316●	6.49	5.76	5.39	5.29
25A	120-2317●	6.07	5.65	5.40	5.16
32A	120-2318●	5.95	5.54	5.29	5.06
35A	120-2319●	6.07	5.65	5.40	5.16
50A	120-2429●	6.07	5.65	5.40	5.16
63A	120-2320●	6.07	5.65	5.40	5.16
80A	120-2321●	6.04	5.62	5.37	5.13
100A	120-2322●	6.93	6.45	6.18	5.90
125A	120-2323●	7.86	6.92	6.59	6.47
160A	120-2324●	8.20	7.26	6.97	6.83
160A	120-2326●	13.97	12.40	11.80	11.55
180A	120-2325●	8.20	7.26	6.97	6.83
660 Volt RMS Series					
		1+	10+	50+	100+
12A	120-2329●	7.93	7.15	6.55	6.41
15A	120-2330●	7.30	6.58	6.02	5.89
20A	120-2331●	7.93	7.15	6.55	6.41
25A	120-2332●	7.93	7.15	6.55	6.40
32A	120-2333●	7.93	7.15	6.55	6.40
40A	120-2334●	7.93	7.15	6.55	6.40
56A	120-2335●	7.93	7.15	6.55	6.40
80A	120-2336●	8.59	7.79	7.18	6.75
65A	120-2337●	17.24	15.53	14.85	14.56
75A	120-2338●	17.24	15.53	14.85	14.56
90A	120-2341●	17.24	15.53	14.85	14.56
110A	120-2342●	17.24	15.53	14.85	14.56
160A	120-2343●	16.44	15.36	14.84	14.55
		1+	5+	10+	25+
355A	120-2347●	36.70	32.59	31.49	30.88

'Redspot'™ Series

A1 to A4 and B2



Notes: A1 size fuse carrier has one central fixing hole. A2, A3, A4 and B2 sizes are two hole fixing (see diagram above). B2 size fuse carrier has a different style handle to that shown in the diagram above.

GEC 'Redspot'™ fuse carriers are widely accepted as an industry standard for use with BS88 fuses.

Moulded from a flame retardant non-hygroscopic phenolic resin to **BS771** they are available in black.

The patented non-twist cable clamping screw of large diameter complies with **CEGB** requirements for **Class II duty**, whilst contacts are single screw fixing with large contact area and anti-vibration features.

Approved by Lloyds register for marine applications, **CEGB approval Nr.29** for **Category II duty**.

Size	Mfrs. List No.	Black	Order Code
A1	RS20H		177-604
A2	RS32H		177-605
A3	RS63H		177-606
A4	RS100H		177-607
B2	RS200H		177-608

204620

Size	Colour	Order Code	Price Each			
			1+	10+	50+	100+
A1	Black	177-604	6.71	6.03	5.37	5.03
A2	Black	177-605	9.40	8.46	7.52	7.05
A3	Black	177-606	11.44	10.29	9.14	8.58
A4	Black	177-607	25.46	22.91	20.36	19.09
B2	Black	177-608	139.64	136.90	134.20	131.57

Camaster

Bussmann



A range of fully shrouded HRC fuseholders designed to accommodate offset bolted tag HRC fuselinks to **BS88 (Parts 1 & 2)** and **IEC 269-1 & 2 1986**.

These fuseholders feature a lever operated cam for easy removal of the fuse carrier from the base. This allows increased pressure between fuse carrier and fuse base contacts thus enhancing the electrical performance. Fuselink fixing screws remain captive in the fuse carrier to prevent their loss when fuse changing. Suitable for DIN rail or panel mounting. Supplied as front connection.


Fuse Size	Rating Amps	Max. Cable mm ²	Fuse Type	Dimensions					Mfrs. List No.	Order Code
				A	B	C	D	E		
A1	32	16	NITD	25.4	93.7	60	3.2	17.5	CM32FC	556-361
A2	32	16	AAO	31.8	117.5	60	3.2	17.5	CM32F	556-373
A3	63	70	BAO	35.6	125	60	4.75	16.4	CM63F	556-385
A3	100	70	OCD	35.6	125	60	4.75	16.4	CM100F	968-766

204445

Fuse	Fuse Type	Order Code	1+	10+	20+	50+
A1	NITD	556-361	5.71	5.32	5.11	4.85
A2	AAO	556-373	7.95	7.41	7.11	6.75
A3	BAO	556-385	10.12	9.41	9.05	8.60
A3	OCD	968-766	16.14	15.01	14.36	13.70

Safeloc

Bussmann



Dimensions

A	B	C	D
25.4	76.2	46.5	2.3

Designed to accommodate the F1 size of **BS88** offset blade fuselinks. Featuring a unique slide action carrier, which retains the fuselink for easy insertion to the base. The fuselink blades connect directly with the shrouded base contacts for improved reliability and lower losses. Terminal screws are semi-captive and are front connection. Suitable for 35mm DIN rail or single screw mounting.

Rating	32A	Fuse size	F1
Max. cable size	16mm ²		
Mfrs. List No.	32NNSF		
			204443
Price Each			
Fuse Size	Order Code	1+	10+ 25+ 100+
F1 (NS)	556-154	3.32	3.10 2.99 2.85

204443

Fuse Links

Solid Links

For BS 88 Fuselinks



Solid links for fitting into fuseholders, fuse-switches etc. in place of a B.S. fuselink. Convert fuse switches to circuit isolators, neutral links and shorting links.

WARNING Where a fuseholder is designated for fitting with a solid link it should be suitably labelled or color coded.

233669

Size	Current Rating	Mfrs. List No.	Order Code	5+	25+	50+	100+
A1	20	SLA120	390-8800	1.33	1.22	1.05	1.02
A2	32	SLA232	390-8811	2.30	2.17	2.07	2.02
A3	63	SLA363	390-8823	3.51	3.40	3.21	3.15
A4	100	SLA4100	390-8835	4.12	3.99	3.76	3.68
F1	32	SLF132	390-8884	1.49	1.36	1.19	1.06

Bottle Fuses and Fuseholders

Ultra Rapid (gr).

DII & DIII Series



- High breaking capacity, low power loss
- Class gR
- For protection of semiconductors and small drive units
- Conforms to **DIN49515** and **VDE0636-33**
- Suitable for 3-phase applications


Working voltage 500Vac 440Vdc
Breaking Capacity 50kA

L DII=50, DIII=50
Dia DII=22, DIII=27



DIN Standard Fuses and Fuseholders

uR - 00 Size



Voltage rating
Breaking capacity

600V rms
300kA @600V
200kA @ 700V


- European style '00' size ultra rapid industrial semiconductor fuses
- Suitable for thyristor control applications eg. high speed switching inverters, variable speed drives
- Trip indication microswitch option for fuse interruption signalling
- UL recognised

Current Rating (A)	Power Loss (W)	Pre-arcing I ² t (A ² s)	Total I ² t @660V (A ² s)	Mfrs List No.	Order Code
35	8	66	360	20-412-20 35A	329-5199
50	8	140	770	20-412-20 50A	329-5205
80	17	470	2600	20-412-20 80A	329-5229
160	31	2800	15400	20-412-20 160A	329-5254
315	53	15600	86000	20-412-20 315A	329-5278

227528

Rating	Order Code	1+	5+	Price Each	10+	20+	50+
35A	329-5199	30.27	27.96	24.82	22.57	18.19	
50A	329-5205	30.27	27.96	24.82	22.57	18.19	
80A	329-5229	31.08	28.71	25.42	23.22	18.73	
160A	329-5254	36.03	33.33	29.53	26.87	21.67	
315A	329-5278	47.70	44.09	39.83	36.22	29.76	
Trip Indication Microswitch	329-5291	50.34	48.32	46.39	44.53	42.77	

NH Series



		A	B	C	D	G	H
gL (General Line)	Size C00	78	47	40.5	20.5	15	6
	Size 00	78	47	46	29.5	15	6
	Size 1	135	65	51.5	42	20	6
	Size 2	150	65	59	53	26	6
UR (Ultra Rapid) 63A to 160A	Size 00	78	50	44	28	15	6

Industrial HRC low voltage fuses with a high breaking capacity, designed to give maximum protection against all faults, i.e. small overcurrents and short circuits. Status of operation of the fuse is shown by the visible leaf spring indicator. Construction from a corrosion resistant ceramic body with a high quality blade contact material. Manufactured in accordance with **DIN57636**, and **IEC269**.

gL (General Line)

Suitable for cable protection and applications where there are no surges to be absorbed. Approved to **VDE**, **SEV** and **OVE**.

Voltage Rating 500V ac

204430

	Current Rating	Order Code	1+	25+	100+	250+
Size C00	16A	248-538	3.85	3.44	3.21	3.15
	20A	248-540	3.65	3.28	3.06	2.98
	25A	248-551	3.85	3.44	3.21	3.15
	35A	248-563	3.85	3.44	3.21	3.15
	50A	248-575	3.85	3.44	3.21	3.15
	63A	248-587	3.85	3.44	3.21	3.15
	80A	248-599	3.57	3.21	2.95	2.89
	100A	248-605	3.57	3.21	2.95	2.89
Size 00	125A	248-617	3.83	3.43	3.21	3.16
	160A	248-629	2.70	2.42	2.26	2.21
Size 1	160A	975-953	5.53	4.96	4.73	4.52
	200A	975-965	5.58	5.14	4.92	4.72
	250A	975-977	5.71	5.15	4.49	4.35
Size 2	315A	975-989	9.18	8.46	8.09	7.73
	400A	975-990	9.18	8.46	7.75	7.43

gL (General Line)



gL-D-II Series
2A to 25A



L=50, Dia=21.8
Thread=E27

gL-D-III Series
35A to 63A

L=50, Dia=28
Thread=E33

D11 and D111 style delayed acting HRC fuses approved to **DIN49515**, **VDE0635** and **VDE0636**. They have a voltage rating of 500V ac or dc. The state of the fuse element is indicated by a coloured disc in the end cap. The fuses have low internal wattage and on continuous load capacity are non ageing. Suitable for cable protection and applications where there are no surges to be absorbed.

204612

Order Multiple=5	Current Rating	Mfrs. List No.	Order Code	5+	25+	100+	250+
gL-D-11 Series	2A	Z-DII/SE-2A/GG	170-436	0.78	0.70	0.66	0.56
	4A	Z-DII/SE-4A/GG	170-437	0.78	0.70	0.66	0.56
	6A	Z-DII/SE-6A/GG	170-438	0.78	0.70	0.66	0.56
	10A	Z-DII/SE-10A/GG	170-439	0.48	0.45	0.43	0.37
	16A	Z-DII/SE-16A/GG	170-440	0.53	0.49	0.47	0.42
	20A	Z-DII/SE-20A/GG	170-441	0.53	0.49	0.47	0.42
	25A	Z-DII/SE-25A/GG	170-442	0.53	0.49	0.47	0.42
gL-D-111 Series	35A	Z-DIII/SE-35A/GG	170-443	0.97	0.89	0.85	0.76
	50A	Z-DIII/SE-50A/GG	170-444	0.97	0.89	0.85	0.76
	63A	Z-DIII/SE-63A/GG	170-445	0.92	0.85	0.81	0.71



DIN Standard Fuses and Fuseholders - continued

NH Series - continued



UR (Ultra Rapid)

Suitable for Thyristor control unit applications (eg. variable speed drives).

Voltage rating 500V ac

Size 00	Current Rating	Order Code	Price Each			
			1+	25+	100+	250+
	63A	499-572	13.99	12.55	11.31	10.74
	80A	499-584	13.99	12.55	11.31	10.74
	100A	499-596	14.87	13.69	13.11	12.51
	125A	976-003	18.62	16.29	15.56	14.86
	160A	976-015	19.43	17.88	17.10	16.32

Fuse Base



Single pole ceramic fuse base suitable for use with all size '00' industrial NH fuses.

Rating 160A @ 660V ac


H=52.5, W=118.5, D=33



Order Code	1+	10+	Price Each	
			20+	50+
499-523	4.63	4.43	4.30	4.20

Fuse Base - Size 00

Shroud Kit available



- Single pole polyester fuse base suitable for "00" size NH fuses
- Shroud kit contains 2 terminal covers and 1 fuse cover
- Separating plates supplied in packs of 2

Fuse base rating 160A @ 660V

	Order Code	1+	5+	Price Each/Per Pack		
				10+	25+	50+
Fuse Base	969-096	4.29	3.97	3.81	3.67	3.51
Shroud kit	969-102	4.48	4.31	4.13	3.95	3.79

Load Switch

3 pole



H=179, W=107, D=92

H=251, W=185, D=115

- European style surface mounting 3 pole fuse load switch/disconnector
- Use with NH style industrial HRC fuses
- Removable cover incorporates large window to view fuse rating

Voltage rating	690V ac	Insulation voltage	800V ac
Making capacity	50kA		
Terminal capacity	160A model	250A model	
Cable	10-95mm	25-120mm (cu)	
		35-150mm (Al)	
Bar	20 10	30 10	
Power loss excluding fuses	6W	13W	
Short term withstand current	3kA	10kA	

Rating	Order Code	1+	5+	Price Each		
				10+	20+	30+
160A	969-072	39.37	37.37	35.94	35.22	32.83
250A	969-084	104.55	99.22	97.03	94.68	90.06

Thermal Circuit Breakers

Thermal Fuse - Microtemp



Body: L=14.7, Dia=4.0 Lead dia.=1.0

- Highly reliable, low cost non-resettable axial fuses
- VDE, CSA, FEMKO approvals and UL Recognised
- The leads have a strain relief system to support a load of up to 1.35kgs (3lbs)
- For upper limit temperature protection

Rating	10A @ 250V ac	Max. rupture current:	20A inductive
Break down (when open)	1200V ac		40A resistive
Operating temperature tolerance	0°C to -4°C		

204508

Order Multiple=5		Mfrs. List No.	Order Code	Price Each			
Opening Temperature				5+	50+	100+	500+
72°C	G4A01072C		476-560	0.50	0.49	0.46	0.44
84°C	G4A01084C		476-572	0.50	0.49	0.46	0.44
93°C	G4A01093C		187-008	0.44	0.43	0.40	0.38
98°C	G4A01098C		476-584	0.50	0.49	0.46	0.44
104°C	G4A01104C		187-010	0.44	0.43	0.40	0.38
110°C	G4A01110C		187-021	0.44	0.43	0.40	0.38
117°C	G4A01117C		187-033	0.44	0.43	0.40	0.38
121°C	G4A01121C		476-596	0.50	0.49	0.46	0.44
128°C	G4A01128C		187-045	0.44	0.43	0.40	0.38
144°C	G4A01144C		187-057	0.44	0.43	0.40	0.38
152°C	G4A01152C		187-069	0.44	0.43	0.40	0.38
167°C	G4A01167C		476-602	0.50	0.49	0.46	0.44
184°C	G4A01184C		476-614	0.50	0.49	0.46	0.44
192°C	G4A01192C		187-070	0.44	0.43	0.40	0.38
216°C	G4A01216C		187-082	0.44	0.43	0.40	0.38
229°C	G4A01229C		760-961	0.50	0.49	0.46	0.44
240°C	G4A01240C		187-094	0.44	0.43	0.40	0.38

Thermal Fuse - 'S' Series

ELCUT



Leads: L=51.3, Dia=0.53, Pitch=5.0 H=4.5, W=5.2, D=2.2

Sub-miniature non-resettable thermal fuses approved to CSA and VDE, UL Recognised. The case is completely isolated from either of the connecting leads. The compact size of the 'S' series cutoffs makes them ideal for today's high density mounting requirements.

Rating 1A @ 240V ac

204465/204465

Order Multiple=5		Actual Opening Temperature	Order Code	Price Each			
Max. Rated Operating Temperature				5+	50+	100+	500+
102°C	98°C±2°C		106-419	0.58	0.53	0.50	0.49
115°C	112°C±3°C		106-420	0.58	0.53	0.50	0.49
130°C	126°C±2°C		106-421	0.58	0.53	0.50	0.49
150°C	145°C±2°C		106-422	0.58	0.53	0.50	0.49

Thermal Fuse with Metal Base

DM Series

ORIENT



Plastic Body
H=15.5, W=14.7, D=11.3

Electrical rating	15A @ 250V	Temperature tolerance	0 to -7 degrees Celsius
Approvals	CSA, TUV, UL	Terminal pull test	10kg for 15 sec

204375

Opening Temp (°C)	Rated Holding Temp (°C)	Mfrs. List No.	Order Code	Price Each			
				1+	25+	50+	100+
78	62	DM078H	113-8643	0.97	0.90	0.82	0.79
99	83	DM099H	113-8644	0.97	0.90	0.82	0.79
120	96	DM120H	113-8645	1.00	0.93	0.85	0.82
150	135	DM150H	113-8646	0.78	0.72	0.66	0.63
190	170	DM190H	113-8647	0.78	0.72	0.66	0.63

Troubleshooting tips



Chat live online to one of our technical engineers at
www.farnell.co.uk



Thermal PCB Mounting



Miniature auto-resetting circuit breaker protects equipment against over current conditions.

H=22mm W=12.6mm D=6mm
Pin Spacing 7.5mm x 2.3mm (Legs = 1.0 Dia.)

Current Rating	Max. Interrupt Current	Trip Time		Internal Resistance mΩ	Order Code
		2 x 1 n	3 x 1 n		
1A	20A	<30s	<7s	<150	698-234
1.6A	20A	<30s	<7s	<100	698-246
2.5A	25A	<30s	<7s	<75	698-258
3A	30A	<30s	<7s	<35	698-260
5A	50A	<30s	<7s	<30	698-271

Voltage Rating 250Vac


204477

Current Rating	Order Code	1+	25+	100+	250+
1A	698-234●	2.37	2.02	1.74	1.56
1.6A	698-246●	2.37	2.02	1.74	1.56
2.5A	698-258●	1.86	1.58	1.37	1.22
3A	698-260●	2.37	2.02	1.74	1.56
5A	698-271●	2.37	2.02	1.74	1.56

Thermal PCB Mounting - Low Profile 1410 Series



L=28, W=9, H=10
Actuator L=4.5, W=3



PCB drilling plan

- Fast acting thermal circuit breaker for PCB mounting in a low profile housing with side fitted re-set slide
- Suitable for replacing fuses in many PCB applications
- Approved to **VDE, CSA** and Circuit Breaker for Equipment to **EN 60934** (CBE), **UL** Recognised.

Voltage rating 250Vac, 28Vdc
Insulation resistance 100MΩ @ 500Vdc
Maximum interrupt current x I_N
Typical life 300 ops @ 2 x I_N

Current Rating	Internal Resistance	Mfrs. List No.	Order Code
1A	0.7Ω	1410-L210-L2F1-S02-1A	237-383
1.5A	0.5Ω	1410-L210-L2F1-S02-1.5A	237-395
2A	0.4Ω	1410-L210-L2F1-S02-2A	237-401
3.15A	0.06Ω	1410-L210-L2F1-S02-3.15A	237-425
5A	0.04Ω	1410-L210-L2F1-S02-5A	237-437
6.3A	0.03Ω	1410-L210-L2F1-S02-6.3A	237-449
8A	0.05Ω	1410-L210-L2F1-S02-8A	976-210

204414

Current Rating	Order Code	1+	10+	50+	100+	250+
1A	237-383●	4.53	4.25	4.09	3.88	3.65
1.5A	237-395●	5.02	4.71	4.54	4.34	4.21
2A	237-401●	6.23	5.27	5.07	4.76	4.45
3.15A	237-425●	4.53	4.25	4.09	3.88	3.65
5A	237-437●	4.53	4.25	4.09	3.88	3.65
6.3A	237-449●	4.53	4.25	4.09	3.88	3.65
8A	976-210●	8.54	7.41	6.26	5.13	3.98

Resettable Thermal Overcurrent



1610-21
H = 28.8, W = 20.3, D = 6

- Automotive press to reset circuit breaker
- Colour coded
- Suitable for standard fuse mounting block
- Miniaturised design allows interchangeability with existing automotive blade fuses with improved electrical protection

Maximum voltage rating 28V dc
Typical voltage drop ≤200mV
Service short circuit breaking capacity 300 operations at 50A
Operating temperature -30°C to +60°C

Mfrs. List No.
1610-21-6A = 597-697
1610-21-15A = 597-727
1610-21-8A = 597-703
1610-21-20A = 597-739
1610-21-10A = 597-715
1610-21-25A = 597-740
1610-21 30A = 856-7336
1610-8-WAY BASE & LID = 856-7344

204616/406026

Current Rating	Actuator Colour	Order Code	1+	10+	25+	50+
1610-21						
6A	Moss Green	597-697●	6.99	6.52	6.23	5.95
8A	Honey	597-703●	6.99	6.55	6.30	5.95
10A	Red	597-715●	6.99	6.52	6.23	5.95
15A	Blue	597-727●	6.99	6.55	6.30	5.95
20A	Yellow	597-739●	6.99	6.52	6.23	5.95
25A	Pearl	597-740●	6.99	6.52	6.23	5.95
30A	Light-Green	856-7336●	6.70	6.25	5.99	--
Mounting Base (with lid)						
8 way		856-7344●	12.63	11.36	10.73	--

Thermal Panel Mounting-Subminiature



H=19, W=11, D=27.6.
Panel cut-out=9.5 dia.
Tabs=2.8 x 0.8, 446-786=6.3 x 0.8

Voltage rating 250Vac, 48Vdc
Current derating 10% for rise of 10°C
Test voltage 4000V for 1 minute
Insulation resistance 710MΩ (500V)

Current Rating	Internal Resistance	Mfrs. List No.	Order Code
0.5A	3.3Ω ±5%	106-P30 0.5A	143-569
1A	0.9Ω ±5%	106-P30 1A	143-570
2A	0.25Ω ±20%	106-P30 2A	143-571
3A	0.11Ω ±20%	106-P30 3A	143-827
4A	0.07Ω	106-P30 4A	143-572
5A	0.05Ω	106-P30 5A	143-828
6A	0.05Ω	106-P30 6A	178-740
10A	0.05Ω	106-P10-10A	446-786
Splashproof cover		X201.285.01	178-741
Reset disc		Y301.059.01	178-742

204369

Current Rating	Order Code	1+	10+	50+	100+	250+
0.5A	143-569●	6.96	6.47	6.18	5.90	5.72
1A	143-570●	6.96	6.47	6.18	5.90	5.72
2A	143-571●	6.96	6.47	6.18	5.90	5.72
3A	143-827●	6.96	6.47	6.18	5.90	5.72
4A	143-572●	6.96	6.47	6.18	5.90	5.72
5A	143-828●	6.96	6.47	6.18	5.90	5.72
6A	178-740●	6.96	6.47	6.18	5.90	5.72
10A	446-786●	6.96	6.47	6.18	5.90	5.72
Splashproof cover		1.87	1.68	1.52	1.36	1.21
Reset disc		0.65	0.58	0.53	0.46	0.43

Thermal Overcurrent Circuit Breaker



2 - 5700 Series



H=46.5, W=29, D=14.5
Panel Cut-Out= 9.6mm Dia.

- Single pole thermal circuit breaker
- Push to release/Push to reset snap action mechanism
- Tease and trip free action
- Approved to Circuit Breaker for Equipment (CBE) standard **EN60934**
- Approved by **VDE, CSA, Semko, SEV LRoS** and **BV**
- **UL** Recognised

- Typical applications: Motors, transformers, solenoids, battery chargers, power supplies and extra low voltage systems.

Voltage rating 250V, 50V
Insulation resistance >100MΩ @ 500V dc
Interrupting capacity 1A & 2.5A = 8 x I_N
7A & 10A = 200A
15A, 20A & 25A = 400A

Current Rating	Internal Resistance (Ω)	Mfrs. List No.	Order Code
1A	<0.8	2-5700-IG1-P10-DD-000040 1A	856-7409
2.5A	<0.2	2-5700-IG1-P10-DD-000040 2.5A	856-7417
7A	<0.02	2-5700-IG1-P10-DD-000040 7A	856-7425
10A	<0.02	2-5700-IG1-P10-DD-000040 10A	856-7433
15A	<0.02	2-5700-IG1-P10-DD-000040 15A	856-7441
20A	<0.02	2-5700-IG1-P10-DD-000040 20A	856-7450
25A	<0.02	2-5700-IG1-P10-DD-000040 25A	856-7468

386182

Current Rating	Order Code	1+	25+	100+
1A	856-7409●	6.38	6.01	5.76
2.5A	856-7417●	6.38	6.01	5.76
7A	856-7425●	6.38	6.01	5.76
10A	856-7433●	6.38	6.01	5.76
15A	856-7441●	6.38	6.01	5.76
20A	856-7450●	6.38	6.01	5.76
25A	856-7468●	6.38	6.01	5.76

Thermal Circuit Breaker - Resettable



T9-611P Series



D (Behind Panel) = 34, H and W (Bezel) = 19mm

Rated Voltage 240V ac, 48V dc
Degree of Protection IP 40
Dielectric Strength 1500V ac

- Single pole thermal circuit breaker
- Snap-in (From the front) panel mount
- Slim, fuseholder type body
- Cycling trip-free release
- 6.3 x 0.8mm Quick Connect terminals
- Panel thickness 0.8 to 2.0mm
- **VDE** and **CCC** Approved, **UL** Recognised



Thermal Circuit Breakers - continued

Thermal Circuit Breaker - Resettable - continued

T9-611P Series - continued

522155

Rated Current Mfrs. List No.	Order Code	1+	10+	50+	100+	250+
4A T9-611P-4A	163-7516●	2.44	2.34	2.25	2.16	2.07
5A T9-611P-5A	163-7517●	2.44	2.34	2.25	2.16	2.07
6A T9-611P-6A	163-7518●	2.44	2.34	2.25	2.16	2.07
8A T9-611P-8A	163-7519●	2.44	2.34	2.25	2.16	2.07
10A T9-611P-10A	163-7520●	2.44	2.34	2.25	2.16	2.07
12A T9-611P-12A	163-7521●	2.44	2.34	2.25	2.16	2.07
15A T9-611P-15A	163-7522●	2.44	2.34	2.25	2.16	2.07
16A T9-611P-16A	163-7523●	2.44	2.34	2.25	2.16	2.07

Resettable Thermal Circuit Breaker

Panel Mount - Front or Rear



H = 45, W = 22, D = 9.8

The circuit breakers are installed in an 8.5mm (0.335") diameter hole similar to a glass fuse holder and can be mounted from front or rear. The KD1 provides circuit protection similar to a fuse. Unlike a fuse that must be replaced, pushing the reset button closes the circuit again once the electrical problem has been corrected. Termination is accomplished by .4" quick-connect terminals, which are solderable.

- Resettable pushbutton circuit protection
- Continuous rated current up to 40°C
- CSA Certified, VDE Approved, SEV Approved 3A to 10A, UL Recognised

Maximum voltage rating	250V ac - 50V dc
Interrupting capacity	1000A @ 250V ac, 200A @ 50V dc
Typical life	5000 ops
Dielectric strength	1500V ac
Insulation resistance	100Mohm @ 500V dc

460878

Mfrs. List No.	Current Rating	Order Code	1+	10+	50+	100+	250+
KD1-1	1A	133-8862●	3.500	2.910	2.620	2.450	2.280
KD1-2	2A	133-8863●	3.660	3.050	2.740	2.570	2.380
KD1-3	3A	133-8864●	3.660	3.050	2.740	2.570	2.380
KD1-4	4A	133-8865●	3.660	3.050	2.740	2.570	2.380
KD1-5	5A	133-8866●	3.660	3.050	2.740	2.570	2.380
KD1-6	6A	133-8867●	3.660	3.050	2.740	2.570	2.380
KD1-7	7A	133-8868●	3.660	3.050	2.740	2.570	2.380
KD1-8	8A	133-8871●	3.660	3.050	2.740	2.570	2.380
KD1-9	9A	133-8872●	2.280	1.900	1.700	1.590	1.480
KD1-10	10A	133-8873●	4.330	3.610	3.240	3.040	2.810
KD1-12	12A	133-8874●	3.660	3.050	2.740	2.570	2.380
KD1-15	15A	133-8875●	3.660	3.050	2.740	2.570	2.380
Accessories							
006-10417	Retaining Clip	133-8876●	0.230	0.210	0.195	0.184	0.173
1213/44	Sealing Boot	133-8877●	1.510	1.340	1.200	1.100	1.020

Thermal Panel Mounting with Switch



L=66.6 (in OFF position)
 Bezel=19 x 19
 Depth behind panel=47.5
 Panel cut-out (double flat)=13.8 x 16 dia
 Panel thickness=0.8 to 1.6
 Tabs=6.3 x 0.8

- Single pole 'fuseholder size' thermal circuit breaker featuring a unique latching push button operation which allows the breaker to be switched ON or OFF
- Two colour button also provides visual indication by showing a white band when the breaker is in the 'OFF' or 'tripped' position
- Approved to VDE, CSA, LRoS, BV, SEMKO and Circuit Breaker for Equipment to EN60934, UL Recognised.
- Typical applications: Motors, transformers, solenoids, office machines and instrumentation

Voltage rating	250Vac, 28Vdc operating area	4000Vac mounting area	2000Vac
Insulation resistance	>100MΩ		

Tripping Time @ 23°C	Rated Current	2 x In	3 x In	4 x In	5 x In	6 x In	8 x In	10 x In
0.5A to 5A	13-46s	5.8-13s	3.9-7.5s	3.0-5.5s	2.2-4.4s	1.3-3.3s	0.9-2.6s	0.4-0.7s
10A to 16A	10-38s	4.3-7.5s	2.5-4.4s	1.3-3.2s	0.8-2.1s	0.56-1.0s		

Mfrs. List No. 110-F112-P1M1-xxA, where xx = current rating in amps.

204426

Current Rating	Internal Resistance Ω	Order Code	1+	10+	25+	100+
0.5A	4.5	100-3728●	9.54	8.88	8.54	8.11
1A	1.1	100-3729●	9.54	8.88	8.54	8.11
2A	0.25	100-3730●	9.54	8.88	8.54	8.11
3A	0.13	100-3731●	9.54	8.88	8.54	8.11
5A	0.05	100-3733●	9.54	8.88	8.54	8.11
10A	0.02	100-3734●	9.36	8.76	8.43	7.99
16A	0.02	100-3735●	9.36	8.76	8.43	7.99

Thermal Circuit Breaker

Push to Reset - W28 Series



- Single pole thermal circuit breaker
- Push to reset snap action mechanism
- Button extends for visual trip indication
- Approved by CSA and VDE, UL Recognised

Note: NOT CSA, UL on 20A, NOT VDE on 16A or 20A

H=19.31, W=19.31, D=38.99mm
 Panel Cut-Out= 15.875-16.129mm Dia.

Max. Operating Voltage
 Dielectric Strength
 Interrupting capacity
 Resettable Overload Capacity
 Termination
 Mounting

250V ac, 32V dc, 50/60 Hz
 >1500V ac
 1000A @ 250V ac, 50/60 Hz and 32V dc
 6 x rated current 2A, 6 x rated current 3A to 20A
 6.35 x 0.813mm Quick Connect
 Snap-In (from panel front)

411550

Current Rating	Mfrs. List No.	Order Code	1+	25+	100+
0.5A	W28-XQ1A-0.50	NEW 143-6216●	3.53	3.32	3.11
0.5A	W28-XQ1A-0.50	NEW 143-6216●	3.53	3.32	3.11
0.75A	W28-XQ1A-0.75	NEW 143-6217●	3.53	3.32	3.11
1A	W28-XQ1A-1	NEW 143-6218●	3.47	3.26	3.05
2A	W28-XQ1A-2	965-9064●	7.10	6.67	6.24
3A	W28-XQ1A-3	965-9072●	3.29	2.91	2.63
4A	W28-XQ1A-4	NEW 143-6219●	2.02	1.90	1.77
5A	W28-XQ1A-5	965-9080●	3.47	3.26	3.05
6A	W28-XQ1A-6	NEW 143-6220●	2.02	1.90	1.77
7A	W28-XQ1A-7	NEW 143-6221●	2.02	1.90	1.77
8A	W28-XQ1A-8	NEW 143-6222●	2.02	1.90	1.77
10A	W28-XQ1A-10	965-9099●	3.47	3.26	3.05
8A	W28-XQ1A-8	NEW 143-6222●	2.02	1.90	1.77
15A	W28-XQ1A-15	965-9102●	3.14	2.78	2.49
20A	W28-XQ1A-20	965-9110●	3.47	3.26	3.05

Thermal Circuit Breaker

Push to Reset - W54 Series



- Push button to reset breaker
- Cannot be manually tripped
- Button extends for visual trip indication
- UL Recognised

H=35, W=14.6, D=31
 Panel Cut-Out=11.2mm Dia.

Max. Operating Voltage
 Dielectric Strength
 Interrupting capacity
 Resettable Overload Capacity
 Termination
 Mounting
 Operating temperature

250V, 50V, 50/60 Hz
 >1500V ac
 1000A @ 250V ac, 50/60 Hz and 32V dc
 10 x Rated Current
 6.3 x 0.031mm Quick Connect
 9.8 x 12.6mm (from panel front)
 0 to 60°C

Current Rating	Internal Resistance (Ω) @ 25°C	Mfrs. List No.	Order Code
5A	0.050	W54-XB1A4A10-5	965-9129
10A	0.025	W54-XB1A4A10-10	965-9137
15A	0.017	W54-XB1A4A10-15	965-9145
20A	0.012	W54-XB1A4A10-20	965-9153
30A	0.008	W54-XB1A4A10-30	965-9161

411558

Current Rating	Order Code	1+	25+	100+	250+	500+
5A	965-9129●	2.09	1.96	1.83	1.64	1.52
10A	965-9137●	2.09	1.96	1.83	1.64	1.52
15A	965-9145●	2.09	1.96	1.83	1.64	1.52
20A	965-9153●	2.39	2.25	2.10	1.88	1.74
30A	965-9161●	2.44	2.29	2.14	1.92	1.77

Thermal Circuit Breaker

Compact Push to Reset - W57 Series



- Compact design with plastic M11 thread
- Push button to reset breaker
- Cannot be manually tripped
- Button extends for visual trip indication
- UL Recognised

H=29.2, W=22.6, D=14.5
 Panel Cut-Out=11.2mm Dia.

Max. Operating Voltage
 Dielectric Strength
 Interrupting capacity
 Resettable Overload Capacity
 Termination
 Mounting
 Operating temperature

250V, 50V, 50/60 Hz
 >1500V ac
 1000A @ 250V ac, 50/60 Hz and 32V dc
 10 x Rated Current
 6.3 x 0.031mm - Quick Connect
 9.8 x 9.6mm (from panel front)
 0 to 60°C

Current Rating	Internal Resistance (Ω) @ 25°C	Mfrs. List No.	Order Code
5A	0.050	W57-XB1A4A10-5	965-9170
10A	0.025	W57-XB1A4A10-10	965-9188
15A	0.017	W57-XB1A4A10-15	965-9196
20A	0.012	W57-XB1A4A10-20	965-9200

411559

Current Rating	Order Code	1+	25+	100+	250+	500+
5A	965-9170	2.15	2.02	1.89	1.69	1.56
10A	965-9188	2.15	2.02	1.89	1.69	1.56
15A	965-9196	2.15	2.02	1.89	1.69	1.56
20A	965-9200	2.15	2.02	1.89	1.69	1.56

Thermal Circuit Breaker

Push to Reset - W58 Series



H = 34.93, W = 16.76, D = 34.93 (Body)

Max. Operating Voltage
Dielectric Strength
Interrupting capacity
Resettable Overload Capacity
Termination
Mounting

- Push button to reset breaker
- Cannot be manually tripped
- Button extends for visual trip indication
- Knurled nut/Hex. nut mounting hardware included
- CSA Approved, UL Recognised

250V ac, 50V dc
>1500V ac
1000A @ 250V ac, and 2000A @ 50V dc
10 Times rated current
Quick connect
Bush

480801

Current Rating	Mfrs. List No.	Order Code	1+	25+	100+	250+
1A	W58-XB1A4A-1A	143-6201	3.94	3.70	3.46	3.10
2A	W58-XB1A4A-2A	143-6202	3.94	3.70	3.46	3.10
3A	W58-XB1A4A-3A	143-6203	3.94	3.70	3.46	3.10
4A	W58-XB1A4A-4A	143-6204	3.94	3.70	3.46	3.10
5A	W58-XB1A4A-5A	143-6205	2.65	2.49	2.33	2.09
6A	W58-XB1A4A-6A	143-6206	3.16	2.97	2.78	2.49
7A	W58-XB1A4A-7A	143-6207	3.16	2.97	2.78	2.49
8A	W58-XB1A4A-8A	143-6208	3.16	2.97	2.78	2.49
10A	W58-XB1A4A-10A	143-6209	2.65	2.49	2.33	2.09
12A	W58-XB1A4A-12A	143-6210	3.16	2.97	2.78	2.49
15A	W58-XB1A4A-15A	143-6212	2.65	2.49	2.33	2.09
20A	W58-XB1A4A-20A	143-6213	2.65	2.49	2.33	2.09
25A	W58-XB1A4A-25A	143-6214	3.16	2.97	2.78	2.49
30A	W58-XB1A4A-30A	143-6215	3.16	2.97	2.78	2.49

Thermal Circuit Breaker - Resettable

TS-701 Series



- Single pole thermal circuit breaker
- 3/8" x 28T Threaded neck for panel mount
- Cycling trip-free release
- 6.3 x 0.8mm Quick Connect terminals
- CSA Approved, UL Recognised

New

Body - H = 31, W = 35.5, D = 14.6mm

Rated Voltage	250V ac, 50V dc	Dielectric Strength	1500V ac
Short Circuit Capacity	200A	Ambient temperature	+40°C

522348

Rated Current	Mfrs. List No.	Order Code	1+	10+	50+	100+	250+
3A	TS-701-HT-3	163-7524	2.68	2.55	2.42	2.30	2.17
5A	TS-701-HT-5	163-7525	2.68	2.55	2.42	2.30	2.17
7A	TS-701-HT-7	163-7527	2.68	2.55	2.42	2.30	2.17
12A	TS-701-HT-12	163-7528	2.68	2.55	2.42	2.30	2.17
20A	TS-701-HT-20	163-7529	2.68	2.55	2.42	2.30	2.17

700 products added online every week



See our pick of the hottest products and latest technologies in 'What's New?' at www.farnell.co.uk

Thermal Circuit Breaker - Resettable

TS-709 Series



- Single pole thermal circuit breaker
- 7/16" x 28T (Plastic) Threaded neck for panel mount
- Cycling trip-free release
- 6.3 x 0.8mm Quick Connect terminals
- CSA Approved, UL Recognised

New

Body - H = 22.5, W = 29.5, D = 14.3mm

Rated Voltage	250V ac, 32V dc	Dielectric Strength	1500V ac
Short Circuit Capacity	200A	Ambient temperature	+30°C

522351

Rated Current	Mfrs. List No.	Order Code	1+	10+	50+	100+	250+
5A	TS-709-5	163-7530	2.55	2.42	2.30	2.19	2.08
8A	TS-709-8	163-7531	2.55	2.42	2.30	2.19	2.08
12A	TS-709-12	163-7532	2.55	2.42	2.30	2.19	2.08
15A	TS-709-15	163-7533	2.55	2.42	2.30	2.19	2.08

Thermal Panel Mounting



- Panel mounting single pole press to reset thermal circuit breaker with push-on connectors
- VDE and CSA approved, UL Recognised
- Typical applications: battery chargers, power supplies, motors, wheelchairs, stairlifts, etc.

H=32, W=14, D=27
Panel cut-out=9.5 dia
Tabs=6.3 x 0.8

Voltage rating
Current rating
Tripping time in seconds at 21°C
Insulation resistance
Mfrs. List No.

250Vac or 28Vdc
trip current is 125% of rated current
100% - NO TRIP 200% - 5 to 25
300% - 1.5 to 8 400% - 1 to 5
100M Ω

1658-G21-02-P10-8A + Rating

204391

Current Rating	Order Code	1+	10+	50+	100+	250+
8A	954-0636	7.72	6.91	6.72	6.28	6.12
10A	954-0644	6.81	6.23	5.95	5.67	5.32
15A	954-0660	6.81	6.23	5.95	5.67	5.32
20A	954-0679	7.72	6.91	6.72	6.28	6.12
25A	954-0687	7.72	6.91	6.72	6.28	6.12

High Performance Thermal Circuit Breaker

4130 Series



- Single pole thermal circuit breaker
- Push to reset snap action mechanism
- Tease and trip free action
- High fault current switching
- Approved to Circuit Breaker for Equipment (CBE) standard EN60934, and VDE.
- UL Recognised
- Typical applications: Motors, transformers, solenoids, battery chargers, power supplies and extra low voltage systems.

H=50, W=32, D=18
Panel Cut-Out= 12.2mm Dia.

Voltage rating
Insulation resistance
Operating temperature
Max. interrupt current
Typical life (50V dc)
Typical life (28V dc)

240V, 50V
>100Mohm @ 500V dc
-30°C to 60°C
800A
300 operations @ 2 x I_N
500 operations @ 2 x I_N

Current Rating	Internal Resistance (Ω)	Mfrs. List No.	Order Code
30A	<0.02	4130-G211-K4M1 30A	856-7140
35A	<0.02	4130-G211-K4M1 35A	856-7158
40A	<0.01	4130-G211-K4M1 40A	856-7166
50A	<0.01	4130-G211-K4M1 50A	856-7174
60A	<0.01	4130-G211-K4M1 60A	856-7182
70A	<0.01	4130-G211-K4M1 70A	856-7190

386174

Current Rating	Order Code	1+	25+	100+
30A	856-7140	13.39	12.55	12.06
35A	856-7158	13.39	12.55	12.06
40A	856-7166	13.39	12.55	12.06
50A	856-7174	13.39	12.55	12.06
60A	856-7182	13.39	12.55	12.06
70A	856-7190	13.39	12.55	12.06



Thermal Circuit Breakers - continued



Hydraulic - Magnetic



- Single pole hydraulic, magnetic circuit breaker with toggle actuation
- Medium delay characteristics
- Industry standard panel mounting
- Push-on connectors.
- Approved to VDE Circuit Breaker for Equipment standard EN60934, CSA, LRoS, BV and QPL, UL Recognised
- Typical applications: Control equipment, communication systems, transportation and power supplies

H=50.8, W=15, D=50.8, Fitting Hole Pitch=42.15
Mounting Thread=M3, Max Depth=4.5

Voltage rating	240Vac, 80Vdc
Typical life	10000 operations at 1xI _N inductive load
Temperature range	-40°C to +85°C
Dielectric strength	3000Vac
Insulation resistance	≥100MΩ @ 500Vdc
Max. interrupt rating	3500A
Shock	100g (11 ms) at 0.8xI _N to IEC68-2-27, test EA

Current Rating	Internal Resistance (Ω)	Mfrs. List No.	Order Code
5A	0.04	8340-F410-P1M2-A2H0-5A	954-0725
10A	≤0.02	8340-F410-P1M2-A2H0-10A	954-0733
15A	≤0.02	8340-F410-P1M2-A2H0-15A	954-0741
20A	≤0.02	8340-F410-P1M2-A2H0-20A	954-0750
25A	≤0.02	8340-F410-P1M2-A2H0-25A	954-0768


204393

Current Rating	Order Code	1+	25+	100+
5A	954-0725	18.48	17.18	15.70
10A	954-0733	18.48	17.18	15.70
15A	954-0741	18.48	17.18	15.70
20A	954-0750	18.48	17.18	15.70
25A	954-0768	18.48	17.18	15.70

Thermal-Magnetic DIN Rail Mounting



201 Series



- Slimline (12.5mm width) thermal magnetic manufactured from glass reinforced polyester
- CBE EN60934, VDE, DEMKO, LRoS and CSA approved, UL Recognised
- Circuit breaker mounts directly onto 35mm standard symmetrical DIN rail
- Can be easily removed by a quick release and connections are by way of recessed screw terminals
- Typical applications: Process control systems and instrumentation

Voltage rating	250Vac, 65Vdc	Shock	25g to IEC68-2-27, test Ea
Dielectric strength	3000Vac	Vibration	5g to IEC68-2-6, test FC, meth A
Insulation resistance	>100MΩ @ 500V	Weight	Approx 60g
Typical life at 2 x I _N	5000ops	Instantaneous magnetic trip	>7.5I _N , ≤10I _N
Colour	Black		

Tripping times @ 23°C

Rated Current	Tripping Time	Rated Current	Tripping Time
I _R	no trip	4 x I _R	1.5-9s
2 x I _R	<30s	5 x I _R	0.8-6s
3 x I _R	<7s	6 x I _R	0.003-4s

Mfrs. List No. 201 + current rating

220498

Current Rating	Internal Resistance (Ω)	Order Code	1+	25+	50+
1A	1.67	954-0547	21.91	20.61	19.75
2A	0.38	954-0555	21.91	20.61	19.75
3A	0.19	954-0563	21.91	20.62	19.75
5A	0.061	954-0571	21.91	20.61	19.75
10A	<0.02	954-0580	21.91	20.62	19.75
15A	<0.02	954-0598	21.91	20.62	19.75

Miniature Thermal Rocker

1410 Series



- Thermal rocker circuit breaker
- Red illumination when on
- Compact size
- Approved to Circuit Breaker for Equipment (CBE) standard EN60934, SEV (EN60934), and CSA, UL Recognised
- Typical applications: Motors, transformers, solenoids, PCBs, appliances and instrumentation

H=32, W=17, D=33
Panel Cut-Out=28 x 12.7

Voltage rating	240Vac, 48Vdc UL/CSA	Max. interrupt current	12 x I _N up to 2.5A
Insulation resistance	>100MΩ @ 500Vdc		8 x I _N 5A and above
Operating temperature	-20°C to +60°C		

Current Rating	Internal Resistance (Ω)	Mfrs. List No.	Order Code
1A	<1	1410F110P1F1W14QE4 1A	954-0776
1.8A	<0.8	1410F110P1F1W14QE4 1.8A	954-0784
2.5A	<0.12	1410F110P1F1W14QE4 2.5A	954-0792
5A	<0.1	1410F110P1F1W14QE4 5A	954-0806
6.3A	<0.1	1410F110P1F1W14QE4 6.3A	954-0814
8A	<0.1	1410F110P1F1W14QE4 8A	954-0822

204499

Current Rating	Order Code	1+	10+	25+	50+	100+	250+
1A	954-0776	11.06	10.42	10.19	9.98	9.48	9.28
1.8A	954-0784	11.06	10.42	10.19	9.98	9.48	9.28
2.5A	954-0792	11.06	10.42	10.19	9.98	9.48	9.28
5A	954-0806	11.50	10.84	10.59	10.38	9.85	9.65
6.3A	954-0814	11.06	10.42	10.19	9.98	9.48	9.28
8A	954-0822	11.50	10.84	10.59	10.38	9.85	9.65

Thermal Circuit Breaker - Rocker Actuated



TA35 Series



- Positive trip-free release
- Snap-in mounting
- Embossed (1 0) legend
- Quick Connect terminals
- Additional IP65 protection cover available
- VDE, CCC Approved, UL Recognised

Body - H = 33.5, D = 33.8mm
W - 1 Pole = 14.5, 2 Pole = 26,
3 Pole = 37.4mm

Rated Voltage - 1 Pole	240V ac, 32V dc	Degree of Protection	IP 40, Terminal side IP 00
Rated Voltage - 2 Pole	240V ac, 32V dc	Dielectric Strength	1500V ac
Rated Voltage - 3 Pole	415V ac / 240V ac	Ambient temperature	-10°C +55°C

522739

Rated Current	Mfrs. List No.	Order Code	1+	10+	25+	50+	100+
1 Pole							
3A	TA35-CFTWF030C0	163-7598	4.37	3.93	3.56	3.27	3.27
5A	TA35-CFTWF050C0	163-7600	4.37	3.93	3.56	3.27	3.27
10A	TA35-CFTWF100C0	163-7601	4.37	3.93	3.56	3.27	3.27
12A	TA35-CFTWF120C0	163-7602	4.37	3.93	3.56	3.27	3.27
15A	TA35-CFTWF150C0	163-7603	4.37	3.93	3.56	3.27	3.27
16A	TA35-CFTWF160C0	163-7604	4.37	3.93	3.56	3.27	3.27
20A	TA35-CFTWF200C0	163-7606	4.37	3.93	3.56	3.27	3.27
2 Pole							
3A	TA35-CBTWF030C0	163-7607	7.91	7.03	6.49	5.95	5.95
5A	TA35-CBTWF050C0	163-7608	7.91	7.03	6.49	5.95	5.95
10A	TA35-CBTWF100C0	163-7609	7.91	7.03	6.49	5.95	5.95
12A	TA35-CBTWF120C0	163-7610	7.91	7.03	6.49	5.95	5.95
15A	TA35-CBTWF150C0	163-7611	7.91	7.03	6.49	5.95	5.95
16A	TA35-CBTWF160C0	163-7612	7.91	7.03	6.49	5.95	5.95
20A	TA35-CBTWF200C0	163-7613	7.91	7.03	6.49	5.95	5.95
3 Pole							
5A	TA35-CKDWF050C0	163-7614	11.22	10.10	9.19	8.43	8.43
10A	TA35-CKDWF100C0	163-7615	11.22	10.10	9.19	8.43	8.43
Protection Cover (IP65)							
1 Pole	CZZ11	163-7616	0.77	0.73	0.69	0.66	0.66
2 Pole	CZZ21	163-7618	0.86	0.82	0.78	0.74	0.74
3 Pole	CZZ31	163-7619	1.06	1.01	0.96	0.91	0.91

Thermal Rocker with Switch



- Versatile single & double pole rocker switches combined with a thermal circuit breaker
- Returns to 'OFF' position when put in overload conditions
- UL Recognised, VDE, CSA and SEMKO approved.

Panel cut-out: a=50.5 x 21.5,
b=44.5 x 22
Tabs=6.35 or 2 x 2.8
No volt release modules
H=33.5, W=22, D=21

Voltage rating	250Vac/50Vdc	Typical life expectancy @ I _N	>50000 ops
Dielectric strength	3000Vac	Max. interrupt rating	200A (single pole) 300A (double pole)
Insulation resistance	>100MΩ @ 500V	Operating temperature	-30°C to +60°C

Current Rating	Internal Resistance (Ω)	Dimensions H W D	Cut-out	Mfrs. List No.	Order Code
10A	0.02	54	25 35 a	3120-F311-W01X-10A	954-0610
16A	0.02	54	25 35 a	3120-F311-W01X-16A	954-0628
3A	0.06	48	25 35 b	3120-F521-W01X-3A	954-0490
5A	0.03	48	25 35 b	3120-F521-W01X-5A	954-0504
10A	0.02	48	25 35 b	3120-F521-W01X-10A	954-0512
16A	0.02	48	25 35 b	3120-F521-W01X-16A	954-0520

204371

Current Rating	Order Code	1+	Price Each 25+	100+
Single Pole				
10A	954-0610●	15.84	14.92	13.57
16A	954-0628●	8.86	8.35	7.59
Double Pole				
3A	954-0490●	15.84	14.92	13.57
5A	954-0504●	15.84	14.92	13.57
10A	954-0512●	15.84	14.92	13.57
16A	954-0520●	15.84	14.92	13.57

MCB's and Accessories

Miniature Circuit Breakers

PLS6 Series - 6 kA



6kA Breaking capacity devices suitable for Din rail mounting. Single and double breakers with B and C type tripping characteristics to IEC/EN 60898.

B type characteristic offers tripping response of 3-5 times rated current. Suitable for domestic and commercial applications such as lighting and heating circuits as well as small building applications.

C type characteristic offers tripping response of 5-10 times rated current. Suitable for motor control and fluorescent lighting circuits where the current inrush may be higher.

- Compatible with standard bus bar
- IP20 standard protection
- Clear Indication of contact position by front toggle
- All current ratings are colour coded by front toggle
- Terminals have upper and lower self-lifting terminals
- Distance between contacts $\geq 4\text{mm}$ for secure isolation
- Tripping in accordance with IEC/EN 60898

Terminal capacity	1 X 25, 2 X 10mm ²	Breaking capacity	6kA
Rated voltage (Max)	415V ac / 48V dc	Degree of Protection	IP20

435868

Current Rating	Mfrs. List No.	Order Code	1+	5+	10+	25+
Type B Single Pole						
1A	PLS6-B1	120-5288●	17.54	16.49	16.14	15.80
2A	PLS6-B2	120-5289●	14.93	14.01	13.71	13.42
3A	PLS6-B3	120-5290●	15.92	14.95	14.63	14.32
6A	PLS6-B6	120-5291●	7.88	7.41	7.25	7.09
10A	PLS6-B10	120-5292●	7.39	6.92	6.77	6.63
16A	PLS6-B16	120-5293●	7.13	6.70	6.56	6.42
20A	PLS6-B20	120-5294●	5.57	5.22	5.10	4.99
25A	PLS6-B25	120-5295●	7.13	6.70	6.56	6.42
32A	PLS6-B32	120-5296●	6.96	6.52	6.38	6.24
Type B Double Pole						
1A	PLS6-B1/2	120-5301●	30.66	28.83	28.21	27.60
2A	PLS6-B2/2	120-5302●	33.68	31.66	30.99	30.33
4A	PLS6-B4/2	120-5303●	23.62	22.19	21.73	21.30
6A	PLS6-B6/2	120-5305●	23.96	22.52	22.04	21.57
10A	PLS6-B10/2	120-5306●	17.01	15.99	15.66	15.33
16A	PLS6-B16/2	120-5307●	17.01	15.99	15.66	15.33
20A	PLS6-B20/2	120-5308●	17.01	15.99	15.66	15.33
25A	PLS6-B25/2	120-5309●	19.14	17.98	17.61	17.24
32A	PLS6-B32/2	120-5310●	19.14	17.98	17.61	17.24
Type C Single Pole						
1A	PLS6-C1-DW	120-5329●	15.55	14.93	14.30	13.70
2A	PLS6-C2-DW	120-5331●	15.24	14.64	14.02	13.43
4A	PLS6-C4-DW	120-5332●	10.78	10.49	10.21	9.95
6A	PLS6-C6-DW	120-5333●	7.51	7.20	6.90	6.77
8A	PLS6-C8-DW	120-5334●	7.97	7.64	7.33	7.19
10A	PLS6-C10-DW	120-5335●	7.14	6.85	6.57	6.29
12A	PLS6-C12-DW	120-5336●	7.36	7.06	6.77	6.64
13A	PLS6-C13-DW	120-5337●	7.36	7.06	6.77	6.64
15A	PLS6-C15-DW	120-5338●	7.36	7.06	6.77	6.64
16A	PLS6-C16-DW	120-5339●	7.14	6.85	6.57	6.29

Current Rating	Mfrs. List No.	Order Code	1+	5+	10+	25+
Type C Single Pole						
20A	PLS6-C20-DW	120-5340●	6.93	6.65	6.38	6.25
25A	PLS6-C25-DW	120-5342●	7.14	6.85	6.57	6.29
32A	PLS6-C32-DS	120-5343●	6.90	6.62	6.35	6.08
40A	PLS6-C40-DW	120-5344●	7.73	7.43	7.12	6.82
Type C Double Pole						
1A	PLS6-C1/2	120-5347●	24.68	23.70	22.71	21.76
2A	PLS6-C2/2	120-5348●	24.24	23.27	22.30	21.37
3A	PLS6-C3/2	120-5349●	24.51	23.55	22.57	22.13
4A	PLS6-C4/2	120-5350●	19.66	18.87	18.09	17.33
6A	PLS6-C6/2	120-5351●	13.41	12.87	12.34	12.10
8A	PLS6-C8/2	120-5352●	14.04	13.46	12.91	12.66
10A	PLS6-C10/2	120-5354●	12.07	11.59	11.11	10.65
12A	PLS6-C12/2	120-5355●	12.44	11.93	11.45	11.22
16A	PLS6-C16/2	120-5356●	12.01	11.53	11.05	10.83
20A	PLS6-C20/2	120-5357●	11.91	11.44	10.96	10.74
25A	PLS6-C25/2	120-5358●	14.37	13.80	13.22	12.95
32A	PLS6-C32/2	120-5359●	15.10	14.50	13.89	13.31
40A	PLS6-C40/2	120-5360●	16.33	16.09	15.84	15.53

FOR MORE INFORMATION & CHOICE

Product Search

Consumer Unit



RoHS Compliant Items Only | Advanced Search

Miniature Circuit Breakers

PLSM Series - 10 kA



Single pole
H=80, W=17.5, D=60mm

Double pole
H=80, W=35, D=60mm

- Compatible with standard bus bar
- IP20 standard protection
- Clear Indication of contact position by front toggle
- All current ratings are colour coded by front toggle
- Terminals have upper and lower self-lifting terminals
- Distance between contacts $\geq 4\text{mm}$ for secure isolation
- Tripping in accordance with IEC/EN 60898

Terminal capacity	1 to 25mm ²	Breaking capacity	10kA
Rated voltage (max)	415V ac / 48V dc	Operational Life	≥ 8000 operating cycles

10kA Breaking capacity devices suitable for Din rail mounting. Single and double pole breakers with B and C type tripping characteristics to IEC/EN 60898.

B type characteristic offers tripping response of 3-5 times rated current. Suitable for domestic and commercial applications such as lighting and heating circuits as well as small building applications.

C type characteristic offers tripping response of 5-10 times rated current. Suitable for motor control and fluorescent lighting circuits where the current inrush may be higher

419373

Current Rating	Mfrs. List No.	Order Code	1+	10+	25+	50+
Type B Single Pole						
6A	PLSM-B6	108-5665●	9.42	8.48	7.54	6.86
10A	PLSM-B10	108-5650●	8.75	7.88	7.01	6.37
16A	PLSM-B16	108-5652●	8.75	7.88	7.01	6.37
20A	PLSM-B20	108-5654●	8.75	7.88	7.01	6.37
25A	PLSM-B25	108-5658●	8.75	7.88	7.01	6.37
Type B Double Pole						
6A	PLSM-B6/2	108-5686●	26.69	24.03	21.37	19.43
10A	PLSM-B10/2	108-5667●	25.37	22.83	20.30	18.45
16A	PLSM-B16/2	108-5671●	20.30	18.65	17.25	16.04
20A	PLSM-B20/2	108-5674●	25.37	22.83	20.30	18.45
25A	PLSM-B25/2	108-5676●	25.37	22.83	20.30	18.45
Type C Single Pole						
1A	PLSM-C1	108-5649●	8.32	7.82	7.65	7.48
2A	PLSM-C2	108-5659●	8.32	7.82	7.65	7.48
4A	PLSM-C4	108-5662●	8.32	7.82	7.65	7.48
6A	PLSM-C6	108-5666●	8.32	7.82	7.65	7.48
10A	PLSM-C10	108-5651●	7.73	7.26	7.12	6.98
16A	PLSM-C16	108-5653●	7.73	7.26	7.12	6.98
20A	PLSM-C20	108-5656●	7.73	7.26	7.12	6.98
32A	PLSM-C32	108-5661●	7.73	7.26	7.12	6.98
Type C Double Pole						
1A	PLSM-C1/2	108-5673●	39.68	37.30	36.50	35.71
2A	PLSM-C2/2	108-5677●	24.49	23.02	22.53	22.05
4A	PLSM-C4/2	108-5681●				

MCB's and Accessories - continued

Miniature Circuit Breakers - continued

PLSM Series - 10 kA - continued

Current Rating	Mfrs. List No.	Order Code	1+	10+	25+	50+
Type C Double Pole						
6A	PLSM-C6/2	108-5687●	23.00	21.62	21.16	20.70
10A	PLSM-C10/2	108-5668●	22.58	21.24	20.78	20.33
16A	PLSM-C16/2	108-5672●	22.58	21.24	20.78	20.33
20A	PLSM-C20/2	108-5675●	22.58	21.24	20.78	20.33
32A	PLSM-C32/2	108-5679●	22.58	21.24	20.78	20.33

MCB Residual Current Protection Unit

Add On Unit - PBSM



2 pole H=90, W=70, D=60mm
4 pole H=90, W=125, D=60mm

Fastening Screw M 2.5 (Slotted one-way)
Terminal Screws M 5 (Combined Philips/standard head)
Rated voltage 230V
Tripping 250A Instantaneous
Degree of Protection IP 40

All these accessories are compatible for all the Moeller MCB ranges.



- Line voltage-independent tripping
- Combine with MCB to produce RCBO (combined RCD/ MCB device)
- Rated current of either 40 or 63A
- IP20 standard protection
- Clear Indication of contact position by front toggle
- All current ratings are colour coded by front toggle
- Terminals have upper and lower self-lifting terminals
- Terminals are finger and hand touch safe, BGV A3, OVE-EN 6

435921

Current Trip Rating	Mfrs. List No.	Order Code	1+	5+	10+	25+
2 Pole Type, <40A Rated current						
30mA	PBSM-402/003	120-5380●	44.24	42.73	39.85	37.61
100mA	PBSM-402/01	120-5381●	43.21	41.75	38.92	36.75
300mA	PBSM-402/03	120-5382●	43.21	41.75	38.92	36.75
4 Pole Type, <40A Rated current						
30mA	PBSM-404/003	120-5388●	57.47	55.48	51.74	48.83
100mA	PBSM-404/01	120-5391●	53.25	51.43	47.95	45.26

C60H MCB Type B, C & D



- Type B, C and D circuit breakers
- Single, 2 and 3-pole versions in ratings from 1 to 63 amps
- Positive contact indication in accordance with 16th Edition (BS7671) IEE Wiring Regulations
- Equipped with tunnel terminals for bare cable connection :- 1 to 25A - 25mm sq., 32 to 63A - 35mm sq.
- Magnetic tripping in accordance with BSEN 60898
- Suitable for direct panel or DIN rail mounting or for use with Merlin Gerin type A and B pan assemblies

The Merlin Gerin, Multi 9, C60H range of miniature circuit breakers are suitable for interrupting fault currents up to 10kA 415 volts according to BSEN 60898.

C60H Type B - suitable for protection of circuits against overload and short circuits in commercial and industrial distribution and domestic applications. Tripping range 3 to 5 times rated current.

C60H Type C - suitable for protection of circuits against overload and short circuits in general commercial and industrial distribution and in applications with moderate inrush currents, such as certain lighting systems. Tripping range 5 to 10 times rated current.

C60H Type D - suitable for protection of circuits against overload and short circuits in general commercial and industrial distribution and in applications with high inrush currents, such as transformers, motors and certain lighting systems. Tripping range 10 to 14 times rated current.

Dimensions			Dimensions			Dimensions		
1 pole	H	W	D	2 pole	H	W	D	3 pole
	81	18	70		81	36	70	

213859

Type B	Mfrs. List No.	Order Code	1+	5+	10+
Single Pole					
1A	C60HB101	142-1046●	12.36	11.56	11.18
2A	C60HB102	142-1047●	11.71	11.04	10.80
4A	C60HB104	142-1048●	10.80	10.18	9.95
6A	C60HB106	142-1051●	10.47	9.86	9.64
10A	C60HB110	142-1052●	9.47	8.93	8.73
16A	C60HB116	142-1053●	9.47	8.93	8.73
20A	C60HB120	142-1054●	9.47	8.93	8.73

Type B	Mfrs. List No.	Order Code	1+	5+	10+
Single Pole					
25A	C60HB125	142-1055●	9.37	8.74	8.46
32A	C60HB132	142-1056●	9.47	8.93	8.73
40A	C60HB140	142-1057●	10.37	9.77	9.55
50A	C60HB150	142-1058●	8.18	7.64	7.39
63A	C60HB163	142-1059●	11.55	10.89	10.65
Two Pole					
1A	C60HB201	142-1060●	35.54	33.17	32.09
2A	C60HB202	142-1061●	33.46	31.46	30.82
4A	C60HB204	142-1063●	31.71	29.83	29.20
6A	C60HB206	142-1064●	29.86	28.09	27.49
10A	C60HB210	142-1065●	27.42	25.79	25.26
16A	C60HB216	142-1066●	27.42	25.79	25.26
20A	C60HB220	142-1067●	27.42	25.79	25.26
25A	C60HB225	142-1068●	27.40	25.57	24.75
32A	C60HB232	142-1069●	27.42	25.79	25.26
40A	C60HB240	142-1070●	29.93	28.16	27.53
50A	C60HB250	142-1071●	32.08	29.94	28.99
63A	C60HB263	142-1072●	24.73	23.09	22.34
Three Pole					
1A	C60HB301	142-1073●	51.04	47.66	46.10
2A	C60HB302	142-1075●	47.83	44.97	44.04
4A	C60HB304	142-1076●	46.94	43.81	42.38
6A	C60HB306	142-1077●	44.35	41.72	40.83
10A	C60HB310	142-1078●	41.14	38.69	37.87
16A	C60HB316	142-1079●	41.14	38.69	37.87
20A	C60HB320	142-1080●	41.14	38.69	37.87
25A	C60HB325	142-1081●	40.70	37.98	36.75
32A	C60HB332	142-1082●	41.14	38.69	37.87
40A	C60HB340	142-1083●	43.92	41.32	40.42
50A	C60HB350	142-1084●	34.75	32.45	31.39
63A	C60HB363	142-1085●	47.86	44.99	44.05
Type C					
Single Pole					
1A	C60HC101	142-1100●	12.27	11.53	11.29
2A	C60HC102	142-1101●	11.71	11.03	10.80
4A	C60HC104	142-1102●	10.80	10.18	9.95
6A	C60HC106	142-1103●	10.47	9.87	9.65
10A	C60HC110	142-1105●	9.47	8.93	8.73
16A	C60HC116	142-1106●	9.47	8.93	8.73
20A	C60HC120	142-1107●	9.47	8.93	8.73
25A	C60HC125	142-1108●	9.37	8.74	8.46
32A	C60HC132	142-1109●	9.47	8.93	8.73
40A	C60HC140	142-1110●	10.37	9.77	9.55
50A	C60HC150	142-1111●	11.01	10.28	9.94
63A	C60HC163	142-1112●	10.31	9.61	9.30
Two Pole					
1A	C60HC201	142-1113●	35.08	32.73	31.67
2A	C60HC202	142-1114●	33.59	31.35	30.34
4A	C60HC204	142-1115●	31.84	29.72	28.76
6A	C60HC206	142-1117●	29.86	28.09	27.48
10A	C60HC210	142-1118●	27.42	25.79	25.24
16A	C60HC216	142-1119●	27.42	25.79	25.24
20A	C60HC220	142-1120●	27.42	25.79	25.24
25A	C60HC225	142-1121●	27.13	25.33	24.50
32A	C60HC232	142-1122●	27.42	25.79	25.24
40A	C60HC240	142-1123●	29.93	28.16	27.54
50A	C60HC250	142-1124●	28.26	26.38	25.52
63A	C60HC263	142-1125●	32.44	30.51	29.86
Three Pole					
1A	C60HC301	142-1126●	39.99	37.33	36.13
2A	C60HC302	142-1127●	35.70	33.33	32.24
4A	C60HC304	142-1129●	46.12	43.39	42.47
6A	C60HC306	142-1131●	44.35	41.72	40.81
10A	C60HC310	142-1132●	41.14	38.69	37.87
16A	C60HC316	142-1133●	41.14	38.69	37.87
20A	C60HC320	142-1134●	41.14	38.69	37.87
25A	C60HC325	142-1135●	40.70	37.98	36.75
32A	C60HC332	142-1136●	41.14	38.69	37.87
40A	C60HC340	142-1137●	43.92	41.32	40.42
50A	C60HC350	142-1138●	46.56	43.79	42.85
63A	C60HC363	142-1139●	47.86	45.00	44.06
Type D					
Single Pole					
1A	C60HD101	142-1154●	12.54	11.70	11.32
2A	C60HD102	142-1155●	12.29	11.58	11.34
4A	C60HD104	142-1156●	11.34	10.69	10.45
6A	C60HD106	142-1157●	10.99	10.36	10.12
10A	C60HD110	142-1158●	9.95	9	

Type B	Mfrs. List No.	Order Code	1+	5+	10+
Three Pole					
1A	C60HD301	142-1180●	44.52	41.56	40.22
2A	C60HD302	142-1181●	37.18	34.70	33.58
4A	C60HD304	142-1182●	48.42	45.55	44.57
6A	C60HD306	142-1183●	46.57	43.80	42.87
10A	C60HD310	142-1184●	43.19	40.62	39.76
16A	C60HD316	142-1185●	43.19	40.62	39.76
20A	C60HD320	142-1186●	43.19	40.62	39.76
25A	C60HD325	142-1187●	43.19	40.62	39.76
32A	C60HD332	142-1188●	43.19	40.62	39.76
40A	C60HD340	142-1191●	46.11	43.36	42.46
50A	C60HD350	142-1192●	48.90	45.98	45.02
63A	C60HD363	142-1193●	50.26	47.27	46.26

RMG Earth Leakage Protection RCDs



- 2 and 4-pole versions in ratings from 16 to 100A
- Positive contact indication in accordance with 16th Edition of the IEE Wiring Regulations
- Sensitivity 10, 30, 100 or 300mA
- Voltage rating 2 pole - 110/240V, 4 pole-240/415V
- Equipped with tunnel terminals for bare cable connection: 16-80A - 35mm², 100A - 50mm²
- Suitable for use as an incoming device on Merlin Gerin type A pan assembly

The Merlin Gerin, Multi 9, RMG range of residual current devices provides the functions of isolation, switching and earth leakage protection of electrical circuits. The time-delayed version provides the above features whilst enabling discrimination with downstream devices.

204558

Rating (A)	Sensitivity (mA)	Mfrs. List No.	Order Code	1+	5+	10+
RMG RCDs - 2 Pole						
16	10	RMG160102	142-0981●	78.33	73.12	70.65
25	30	RMG250302	142-0983●	56.35	53.00	51.38
40	30	RMG400302	142-0984●	59.49	55.95	54.06
63	30	RMG630302	142-0986●	71.61	67.33	65.85
RMG RCDs - 2 Pole, with delay						
100	300	23116	142-0998●	106.72	99.62	96.26
RMG RCDs - 4 Pole						
25	30	RMG250304	142-1000●	72.84	68.51	66.20
40	30	RMG400304	142-1003●	77.81	73.15	70.67
63	30	RMG630304	142-1005●	104.80	98.53	95.20
63	100	RMG631004	142-1006●	87.10	81.32	78.57
RMG RCDs - 4 Pole, with delay						
100	300	23227	142-1012●	255.66	248.93	242.55

Electrical Auxiliaries

For 2 and 4 Pole RMG's



477523

Description	Mfrs. List No.	Order Code	1+	5+	10+
Shunt Trip Release (MX)	26946	142-1014●	25.03	23.30	22.31
Under Voltage Release (MN)	26960	142-1015●	42.08	40.01	38.29
Auxiliary Switch (OFS)	26923	142-1016●	17.81	16.40	15.88
Auxiliary Switch (OF)	26924	142-1017●	16.43	15.46	15.12
Fault Indicating Switch (SD)	26927	142-1018●	16.33	15.23	14.77

RCBO, Combined MCB/RCD

6kA



- Provide protection against the effects of earth leakage. Overload and short circuit currents
- Symmetrical DIN Rail mounting for all commercial, industrial and domestic electrical distribution systems
- 30mA sensitivity, breaking capacity 6kA, 2 pole switching (phase and neutral)
- Integrated filter prevents unwanted tripping due to transient voltages
- Visual indication of trip due to earth faults
- Complies with BSEN 60898 and BS EN61009

H=81, W=36, D=75

204521

MCB Rating	Mfrs. List No.	Order Code	1+	5+	10+
6A	19661	142-0973●	72.55	68.23	65.71
10A	19663	142-0974●	70.48	66.28	63.86
16A	19665	142-0976●	70.48	66.28	63.86
20A	19666	142-0977●	70.48	66.28	64.95
25A	19667	142-0978●	70.48	66.28	64.95
32A	19668	142-0979●	70.48	66.28	64.95
40A	19669	142-0980●	72.55	68.23	65.71

Switch Disconnectors



- Current ratings: 32A, 63A, 100A and 125A
- 1P, 2P, 3P, 3P+N and 4P versions
- Specification: BS5419: 1977, category of duty AC22, IEC 947-3
- Positive contact indication in accordance with 16th Edition of the IEE Wiring Regulations
- Cable capacity : equipped with tunnel terminals for bare cable connection 32A - 10mm², 63A - 50mm².
- DIN rail mounting or within enclosure suitable for DIN profile equipment
- 3P+N version lockable in either ON or OFF position

Suitable for use as a switch disconnector in all types of circuit as defined in 16th Edition of IEE Wiring Regulations.

Rating (A)	Voltage	Poles (mA)	Mfrs. List No.	Order Code
32	240/415	2	15010	142-1022
63	240/415	2	15014	142-1023
100	240/415	2	15091	142-1024
125	230	2	MGI1252	142-1019
125	415	3	MGI1253N	142-1020

213853

Current Rating (A)	Order Code	1+	5+	10+
32	142-1022●	7.41	6.91	6.68
63	142-1023●	15.06	14.06	13.60
100	142-1024●	18.06	16.86	16.31
125	142-1019●	15.56	14.65	14.34
125	142-1020●	47.11	43.96	42.53

Comb Busbars, Terminals & Installation Accessories



- Fully insulated for protection against accidental live contact
- Complete with insulated end covers
- Available in 24-way 1P, 2P, 3P & 4P
- Accessories and terminals suitable for Merlin Gerin pan assemblies

Comb Busbars	Mfrs. List No	Order Code
1 row: 12-Single pole MCBs	14881	142-1026
1 row: 6-Two pole MCBs	14882	142-1027
2 rows: 12-Two pole MCBs	14892	142-1031
1 row: 4-Three pole MCBs	14883	142-1028
2 rows: 8-Three pole MCBs	14893	142-1032
Terminals and installation accessories		
1P, 2P insulation accessories (endcaps+boots)	14886	142-1034
3P, 4P insulation accessories (endcaps+boots)	14887	142-1035
Insulating boots for unused connections (pack)	14888	142-1036
1P terminal block(2X25mm+4x16mm)	14936	142-1038
2P terminal block(2X25mm+4x16mm)	14937	142-1039
Terminal bar for earth/neutral conns, 183mm	99217	142-1042
Terminal bar for earth/neutral conns, 222mm	99219	142-1043
Terminal bar for earth/neutral conns, 332mm	99221	142-1044

213856

Mfrs. List No.	Order Code	1+	5+	10+
Comb Busbars				
14881	142-1026●	5.60	5.23	5.05
14882	142-1027●	8.95	8.51	8.16
14892	142-1031●	31.51	29.43	28.47
14883	142-1028●	15.01	14.02	13.56
14893	142-1032●	36.52	34.09	32.98
Terminals & Installation acc.				
14886	142-1034●	8.22	7.67	7.41
14887	142-1035●	7.45	6.95	6.71
14888	142-1036●	10.14	9.45	9.16
14936	142-1038●	6.10	5.69	5.51
14937	142-1039●	8.36	7.79	7.55
99217	142-1042●	8.97	8.38	8.13
99219	142-1043●	10.89	10.17	9.87

Over 480,000 products online



Consumer Units and Distribution Boxes

IP40 Consumer Units

Insulated and Metal Versions



- Preformed knockouts
- Distinct wiring zones
- Earth and Neutral terminal blocks fully rated to 100A
- Complete shrouding of all live parts
- Cover designed to stay open as required
- Pozidrive screwdriver fits all screws in the board and devices

Mfrs. List No.	No. of Outgoing Ways	Dimensions (mm)	Mfrs. List No.	No. of Outgoing Ways	Dimensions (mm)
BC-P2	2	Height 172 Width 111 Depth 111	BC-M2	2	Height 223 Width 180 Depth 113
BC-P6	6	Height 225 Width 244 Depth 111	BC-M6	6	Height 223 Width 252 Depth 113
BC-P12	12	Height 225 Width 351 Depth 111			

446619

No. of Ways	Mfrs. List No.	Order Code	1+	5+	10+	25+
Plastic - 2 Pole, 100mA Main Switch Controlled						
2	BC-P2	126-6781	23.21	22.29	21.39	20.53
6	BC-P6	126-6782	29.35	28.17	27.05	25.96
12	BC-P12	126-6784	39.60	38.01	36.49	35.04
Metal - 2 Pole, 100mA Main Switch Controlled						
2	BC-M2	126-6793	34.79	33.39	32.06	30.78
6	BC-M6	126-6794	38.47	36.93	35.46	34.03
Blanking Strip - 6 Modules Wide						
6	KLV-AP-45-W	126-6804	0.57	0.55	0.53	0.51

IP65 Sealed Distribution Boxes



- **IP54 (IP65)** when using a suitable cable gland rated Distribution Boxes for housing DIN Rail Mounting Components such as MCBs, RCCBs, Timers and Fuses.
- Designed to incorporate multiples of 17.5mm modules mounted on the DIN rail.
- Includes an Earth and Neutral Terminal Block and Blanking Strip for unused ways.
- Cable entry glands and labelling strips supplied.
- Offers widths to accommodate 2, 4, 8 or 12 modules to **DIN43880**
- Impact resistant non-flammable thermoplastic construction.

Temperature resistant up to +70°C

224477

H	W	D	Order Code	1+	10+	50+	100+	500+
130	94	81	531-741	20.88	19.57	18.56	17.40	16.25
180	110	110	531-753	25.77	24.23	23.96	22.49	21.05
180	182	110	531-765	35.37	33.48	32.62	30.71	28.65
180	254	110	531-777	44.70	42.27	41.71	39.06	36.74

IP65 Distribution Boxes



- 3 to 28 way distribution boxes
- Grey in colour similar to RAL 7035
- Pre-assembled **IP65** sealing membranes
- Flame resistant polystyrene, complying with **DIN VDE 0471**
- Individual transparent doors can be lead sealed, blanking off of individual rows
- With 150mm distance between rails, the distribution boards provide generous wiring space

Type	Knockouts	Terminals
AK03	Top End: 3 x M20 Bottom: 2 x M20/M25 Side walls (each): 2 x M20 Base, Floor: 1 x M20	2 x 4 Pole, 6/16mm ²
AK05	Top End: 4 x M20, 1 x M20/M25 Side walls (each): 2 x M20 Base, Floor: 1 x M20	2 x 5 Pole, 6/16mm ²
AK09	Top End: 8 x M20, 1 x M25/M32 Side walls (each): 2 x M20 Base, Floor: 2 x M20/M25	2 x 7 Pole, 6/16mm ²
AK12	Top End: 8 x M20, 2 x M20/M25, 1 x M32/M40 Side walls (each): 2 x M20 Base, Floor: 2 x M20/M25	2 x 12 Pole, 6/16mm ²
AK14	Top End: 17 x M20, 2 x M20/M25, 1 x M32/M40 Bottom: 15 x M20, 2 x M20/M25, 1 x M32/M40 Side walls (each): 8 x M20, 2 x M25/M32	3 x Screw clamping points, 2.5 to 16mm ² 14 Screwless clamping points, 1.5 to 4mm ²

No. of Ways	Dimensions (mm)	Mfrs. List No.	Order Code
3	Length 150 Width 100 Depth 96	735-403	776-7498
5	Length 200 Width 125 Depth 122	735-405	776-7501
9	Length 200 Width 200 Depth 122	735-409	776-7510

No. of Ways	Length	Width	Depth	Mfrs. List No.	Order Code
12	200	250	122	735-412	776-7528
14	300	300	142	735-414	776-7536

347437

Type	Order Code	1+	5+	10+	25+
AK03	776-7498	18.60	16.54	14.88	13.54
AK05	776-7501	25.42	22.61	20.35	18.50
AK09	776-7510	34.43	30.62	27.54	25.06
AK12	776-7528	43.97	39.10	35.19	31.98
AK14	776-7536	46.25	43.47	40.86	38.41

Distribution Enclosures

2 and 4 Module



261-324 4 module standard enclosure
261-312 2 module splashproof enclosure

- Complete with DIN rail & earth terminals
- Accommodate MCB's, RCD's RCBO's & Switch Disconnectors
- Standard enclosures to **IP30**
- Splashproof enclosures to **IP44**

Order Codes	Modules	Style	H	W	D	Fixing Centres
261-300	2	Standard	149	76	76	106
261-312	2	Splashproof	200	123	112	140 x 160
261-324	4	Standard	188	121	74	82.5 + 140 to ctr

204419

Enclosure	Mfrs. List No.	Order Code	1+	5+	10+
2 module (standard)	5502S	261-300	12.03	11.42	10.95
2 module (splashproof)	5702S	261-312	20.47	19.45	18.47
4 module (standard)	5504S	261-324	17.64	16.76	15.92

125A Standard A boards - 1P+N

For use with C60H range



- Designed, manufactured and tested to **BS EN 60439-3**
- Busbar rating 125A
- Voltage rating 230/240V ac
- Distributed neutral
- Din rail mounting with fully shrouded busbars
- Ingress protection **IP31** to **BS EN 60529**
- Complete with 5 single pole blanking plates
- Cable capacity (neutral and earth bar) 25mm²

Mfrs. List No.	No. of outgoing ways	Height	Width	Depth
MGAN6	6	264	260	127
MGAN9	9	264	315	127
MGAN12	12	264	370	127

477563

No. of Ways	Mfrs. List No.	Order Code	1+	5+
6	MGAN6	142-1212	39.74	37.78
9	MGAN9	142-1213	69.70	67.87
12	MGAN12	142-1214	59.69	56.72

Standard B boards - TP + N

For use with C60H range



- Designed, manufactured and tested to **BS EN 60439-3**
- Busbar rating 250A
- Voltage rating 400/415V ac
- Distributed neutral
- Din rail mounting with fully shrouded busbars
- Ingress protection **IP31** to **BS EN 60529**
- Complete with 5 single pole blanking plates
- Cable capacity (neutral and earth bar) 25mm²

Mfrs. List No.	No. of outgoing ways	Height	Width	Depth
MGBN6	6	484	470	158
MGBN8	8	538	470	158
MGBN16	16	808	470	158

477564

No. of Ways	Mfrs. List No.	Order Code	1+	5+	10+
6	MGBN6	142-1215	209.18	203.67	198.45
8	MGBN8	142-1216	155.41	147.65	142.67
16	MGBN16	142-1218	376.30	366.40	357.00