

COMAIR ROTRON

ebm
MOTORS AND FANS

micronel

multicomp

PAPST

SANYO DENKI

Contents

Page

Accessories	719
Axial Flow Fans - Low Voltage dc	714
Axial Flow Fans - Mains ac	710
Backward Curved Fans	720
Blowers	721
Fan Speed Controllers	723
Flatpack Fans	720
High Performance ac/dc Fans	713
Mixed Flow Fans	720
Thermal Speed Controlled Fans	714



Make Farnell-Newark InOne
your first choice -
search over 300,000 products at
www.farnell-newarkinone.com.sg

Can't find the product
you are looking for?

19
Fans

311672

Dimensions			Voltage	Order Code	Price Each				
H	W	D	V		1+	5+	10+	25+	+
171.5	150.4	55	230	102-3677	172.29	157.65	144.24	133.55	--
171.5	150.44	55	115	102-3678	172.29	157.65	144.24	133.55	--

171mm

'Falcon'



- Feathered edge impeller for low noise
- Stainless steel ball bearings
- Die-cast aluminium alloy venturi with flame retardant polycarbonate propeller
- CSA and VDE approved, UL recognised



Voltage V ac	Power Watts	Air Flow cu ft/min	ltrs/sec	Noise dBA@1m	Mfrs. List No.	Order Code
115	41	250	118	54.8	FA2B32.	162-5597
240	40.5	250	118	54.8	FA77B3 31660.	162-5585

Dimensions			Voltage	Order Code	Price Each				
Dia	D		V		1+	5+	10+	15+	+
171.5	55	115V	162-5597	174.60	151.86	139.65	121.07	--	--
171.5	55	240V	162-5585	189.99	166.92	155.00	153.73	--	--
Finger Guards					1+	+	+	+	+
171 Dia			170-5404	7.72	--	--	--	--	--

Voltage V ac	Power Watts	Air Flow cu ft/min	ltrs/sec	Noise dBA@1m	Mfrs. List No.	Order Code
115	41	250	118	54.8	FA2B3 031659	102-3657
240	40.5	250	118	54.8	FA77B3 031660	102-3656

204357

Dimensions			Voltage	Order Code	Price Each				
Dia	D		V		1+	5+	10+	15+	+
171.5	55	115V	102-3657	174.60	151.86	139.65	121.07	--	--
171.5	55	240V	102-3656	189.99	166.92	155.00	153.73	--	--
Finger Guards					1+	+	+	+	+
171 Dia			170-5404	7.72	--	--	--	--	--

172mm

ebmpapst



- Metal fan housing and impeller
- Thermally protected external rotor capacitor motor
- Fitted with ball bearings
- VDE, and CSA approved, UL recognised

H=150, W=172, D=38
Dia=172, D=51

Voltage V ac	Power Watts	Air Flow cu ft/min	ltrs/sec	Noise dBA@1m	Operating Temp °C	Mfrs. List No.	Order Code
115	24	229.4	108.2	57	-30°C to +80°C	7006ES	960-1120
230	29	194.1	91.5	52	-30°C to +65°C	7056ES	960-1139
115	29	294.1	138.7	58	-30°C to +75°C	6028ES	960-1147
230	26	247.1	116.6	54	-30°C to +75°C	6078ES	960-1155

204339

Dimensions			Voltage	Order Code	Price Each				
H	W	D	V		1+	10+	25+	50+	+
150	172	38	115V	960-1120	206.08	199.24	187.77	162.48	--
150	172	38	230V	960-1139	206.08	199.24	187.77	162.48	--
51	Dia.172	51	115V	960-1147	220.99	213.26	200.97	173.88	--
51	Dia.172	51	230V	960-1155	220.99	213.26	200.97	173.88	--
Finger Guards									
150mm			117-1810	7.62	6.71	6.05	5.11	--	--
172mm			117-1812	8.15	7.17	6.47	6.00	--	--

171mm

'Major and Patriot'

Major
Patriot
H=171.50, W=150.40, D=50.80, Dia=171.50, D=50.80

- Feathered edge impeller for low noise
- Stainless steel ball bearing
- CSA and VDE approved, UL recognised
- 3.05mm solder terminals



Voltage V ac	Power Watts	Air Flow cu ft/min	ltrs/sec	Noise dBA@1m	Operating Temp °C	Mfrs. List No.	Order Code
115	31	200	94	55.8	-28°C to +70°C	MR2B3 028245	102-3660
230	30	200	94	55.8	-28°C to +70°C	MR77B3 028309	102-3650
115	31	200	94	54	-28°C to +70°C	PT2B3 028254	102-3661
230	30	200	94	54	-28°C to +70°C	PT77B3 028312	102-3649

204338

Dimensions				Order Code	Price Each				
H	W	D	Voltage		1+	10+	25+	50+	+
Major									
171.5	150.4	50.8	115V	102-3660	126.53	112.86	102.42	87.81	--
171.5	150.4	50.8	230V	102-3650	131.00	116.79	105.96	90.84	--
Patriot									
171.5	Dia.	50.8	115V	102-3661	126.53	112.86	102.42	87.81	--
171.5	Dia.	50.8	230V	102-3649	140.18	122.61	107.01	90.84	--
Finger Guards									
171.5	150.4			118-7494	9.37	9.24	8.04	7.58	--
171 Dia				118-7495	8.33	7.84	6.87	6.67	--

175.5mm

'Tarzan'



H=175.50 W=175.50 D=111.80

- Sealed Ball Bearing
- CSA and TUV approved, UL recognised
- Earthed through fan mounting hole
- Supplied with 304mm lead

Voltage V ac	Power Watts	Air Flow cu ft/min	ltrs/sec	Noise dBA@1m	Operating Temp °C	Mfrs. List No.	Order Code
115	90/70	280	132	61.6	-18°C to +66°C	020169	102-3651

204336

			Price Each				
Voltage	Connector Type	Order Code	1+	10+	25+	50+	+
115V	Lead	102-3651	169.32	143.94	124.29	--	--
Finger Guards		118-7496	12.01	10.64	9.02	8.92	--

254mm

'Caravel'



- Sealed ball bearings
- Earthed through tapped hole on fan case
- Available with 304mm lead or 3.05mm solder terminals
- CSA approved, UL recognised

D=88.90, Dia=254.00

Voltage V ac	Power Watts	Air Flow cu ft/min	ltrs/sec	Noise dBA@1m	Operating Temp °C	Mfrs. List No.	Order Code
115	67	455	215	45.4	-30°C to +60°C	CLE2L2 020188	102-3662
230	60	455	215	45.4	-30°C to +60°C	CLE3L2 020190	102-3658
115	67	455	215	45.4	-30°C to +60°C	CLE2T2 020189	102-3659
230	60	455	215	45.4	-30°C to +60°C	CLE3T2 020191	102-3653

204337

Connection Voltage		Type	Order Code	1+	10+	Price Each		
115V		Lead	102-3662	125.01	106.26	25+	50+	+
230V		Lead	102-3658	127.89	108.72	92.95	--	--
115V		Solder Terminal	102-3659	131.34	114.27	103.02	99.12	--
230V		Solder Terminal	102-3653	134.31	116.85	105.33	95.79	--
Finger Guards			118-7495	8.33	7.84	6.87	6.67	--



RoHS Directive

Worried about the part number lottery?
Count on us for traceability
-visit www.rohs.info

**Don't risk anyone
else for RoHS**

Prices are in Singapore Dollars and exclusive of GST.
Due to the volatile nature of certain products,
prices are subject to change without notice.

255mm
'Caravel XL'

- Aluminium motor base and polycarbonate impeller
- Termination via 24" lead wires
- Stainless steel ball bearings

Voltage (V ac)	Power (Watts)	Airflow (CFM)	Noise (dBA)	Speed (RPM)	Dimensions (WxHxD)	Mfrs. List No.	Order Code
115	115	825	60.0	2400	255x255x107	CLE2L5	118-7515
230	110	825	60.0	2675	255x255x107	CLE3L5	118-7516

347054

Order Code	Price Each			
	1+	5+	10+	25+
118-7515	225.34	207.31	190.41	185.91
118-7516	225.34	207.31	190.41	165.25

AC Axial Fan

ebmpapst



- Reliable and rugged plate fans suitable for industrial application
- External rotor motor gives good speed control and energy efficiency
- Sickle blades provide lower sound levels, higher pressure development and improved air flow
- Insulation class F (unless otherwise stated) motor with maintenance free sealed for life bearings

NEW

- Terminal box protected by IP 54
- Galvanised painted wall plate with full bell-mouth and inlet guard

Voltage	Power Input	Air Flow	Noise (dBA)	Dimensions (WxHxD)	Weight	Mfrs. List No.	Order Code
230V ac, 50/60Hz	47W	945m³/h	44	370 x 370 x 49mm	3.4kg	W4S250-DI02-06*	101-1725
230V ac, 50/60Hz	120W	2441m³/h	49	430 x 430 x 62mm	6.8kg	W4E315-DP18-38	101-1726
230V ac, 50/60Hz	180W	3110m³/h	54	485 x 485 x 68mm	6.8kg	W4E350-DP06-39	101-1727
230V ac, 50/60Hz	300W	5000m³/h	61	540 x 540 x 86mm	7.3kg	W4E400-DS02-38	101-1729
230V ac, 50/60Hz	470W	6732m³/h	61	576 x 576 x 86mm	9.6kg	W4E450-DV01-38	101-1731

Note: * Denotes Class B Motor

416707

Mfrs. List No.	Order Code	Price Each		
		1+	2+	5+
W4S250-DI02-06	101-1725	448.73	333.77	296.66
W4E315-DP18-38	101-1726	453.75	359.45	319.48
W4E350-DP06-39	101-1727	522.30	410.81	365.15
W4E400-DS02-38	101-1729	603.93	474.94	422.21
W4E450-DV01-38	101-1731	652.89	532.71	473.54

High Performance ac/dc Fans

171.5mm, 225mm

ebm
MOTORS AND FANS

- Robust all-metal construction
- Ball bearings
- Reverse mounting for sucking or blowing
- Locked rotor protection by built-in thermal cut-out
- Mounting in any position
- CSA, VDE approved, UL recognised

AC Compact Fans		Supply - 230V - Single Phase - 50Hz				Mfrs. List No.	Order Code
Air Flow (l/s)	Dimensions H W D	Impeller	Noise Level dBA@1m				
104	171.5 171.5 51	143	54	6058ES		960-1198	
257	225 225 80	200	59	W2E200-HH38-01		960-1201	

213833

Type	Mfrs. List No.	Order Code	Price Each			
			1+	5+	10+	25+
AC Compact	6058ES	960-1198	123.32	111.07	106.72	—
AC Compact	W2E200-HH38-01	960-1201	199.63	189.66	179.36	168.49
AC Compact	04013-2-4039	117-1827	15.51	15.12	14.37	12.33
AC Compact	78128-2-4039	117-1828	24.68	23.58	22.41	19.20

AC & DC Axial Flow Fans



- CE, CUR, TUV approved, UL recognised
- Supplied with 300mm lead
- Full range of fans, ac, dc, slimline and green
- Long life
- Stable operation
- Operating temperature range -10°C to +90°C
- Green range supplied with 3 wires

Voltage V dc	Power Watts	Air Flow cu. ft./min.	ltrs./sec.	Noise dBA@1m	Mfrs. List No.	Order Code
AC - Slimline						
220/240	14/13.5	20	9.4	32.25	SF23080AT/2082HBL.GN	960-6190
220/240	14/13.5	33.5	15.8	38.5	SF23092A/2092HBL.GN	960-6203
220/240	19/18	72	35.6	45	DP201AT/2122HBL.GN	960-6220
AC - Low Cost						
220/240	14/13.5	30	9.44	35	SF23080A/2083HSL.GN	960-6238
115	20/18	95	44.8	45.5	SP101A/1123HSL.GN	960-6246
220/240	20/19	95	44.8	47	DP201A/2123HSL.GN	960-6254
DC - Slimline						
5	0.9	4.9	2.31	29	GM0503PEV1-8.N.GN	960-6262
5	0.55	5.3	2.5	28	GM0504PEV2-8.GN	960-6270
DC - Ultra Slimline						
12	0.7	3.0	1.41	25	GM1203PFV2-8.GN	960-6289
12	0.8	4.5	2.12	21	GM1235PFV2-8.GN	960-6297
12	0.6	6.0	2.83	28.5	KDE1204PFV2.11.MS.A.GN	960-6300
DC - Standard						
12	0.9	6.8	3.2	29	KDE1204PKV2.MS.GN	960-6319
24	1.0	7	3.3	29	KDE2404PKV2.MS.A.GN	960-6327
12	1.1	19.3	9.09	31	KDE1206PTV2.13.MS.A.GN	960-6335
24	1.9	19.3	9.09	31	KDE2406PTV2.13.MS.A.GN	960-6343
12	2.1	39	18.37	32	KDE1208PTV2.13.MS.A.GN	960-6351
24	2.4	6.8	3.2	29	KDE2408PTV2.13.MS.A.GN	960-6360
12	2.0	44	20.7	33	KDE1209PTV2.13.MS.A.GN	960-6378
24	2.2	45	21.2	34	KDE2409PTV2.13.MS.A.GN	960-6386
12	3.6	80	37.7	41	KD1212PTB2-6A.GN	960-6394
24	4.1	80	37.7	41	KD2412PTB2-6A.GN	960-6408
12	6.8	108	50.9	42	KD1212PMB1-6A.GN	960-6416
24	5.5	98	46.2	36.5	KD2412PMB2-6A.GN	960-6424
DC - Green						
12	0.8	8.6	4.05	36	GM1204PFVX-AF.GN	960-6432
12	1.4	10.8	5.08	27.5	KDE1204PKVX.MS.AF.GN	960-6440
12	1.9	18	8.5	37	GM1205PHVX-AF.GN	960-6459
12	1.4	21	9.9	36	GM1206PHV1-AF.GN	960-6467
12	1.6	22	10.4	32	KDE1206PHV1.MS.AF.GN	960-6475
12	1.1	26.2	12.34	38	KDE1206PTVX.MS.AF.GN	960-6483

232443/341589

Dimensions (mm)	Mfrs. List No.	Order Code	1+	5+	10+	25+
AC - Slimline						
80 x 80 x 25	SF23080AT/2082HBL.GN	960-6190	21.46	19.81	18.94	18.39
92 x 92 x 25	SF23092A/2092HBL.GN	960-6203	21.46	19.81	18.94	18.39
120 x 120 x 25	DP201AT/2122HBL.GN	960-6220	21.46	19.81	18.94	18.39
AC - Low Cost						
80 x 80 x 38	SF23080A/2083HSL.GN	960-6238	17.85	16.48	15.75	15.30
120 x 120 x 38	SP101A/1123HSL.GN	960-6246	17.85	16.48	15.75	15.30
120 x 120 x 38	DP201A/2123HSL.GN	960-6254	17.85	16.48	15.75	15.30
DC - Slimline						
30 x 30 x 6	GM0503PEV1-8.N.GN	960-6262	18.45	17.03	16.28	15.82
40 x 40 x 6	GM0504PEV2-8.GN	960-6270	18.45	17.03	16.28	15.82
DC - Ultra Slimline						
30 x 30 x 10	GM1203PFV2-8.GN	960-6289	18.45	17.03	16.28	15.82
35 x 35 x 10	GM1235PFV2-8.GN	960-6297	18.45	17.03	16.28	15.82
40 x 40 x 10	KDE1204PFV2.11.MS.A.GN	960-6300	9.81	9.05	8.65	8.40
DC - Standard						
40 x 40 x 20	KDE1204PKV2.MS.GN	960-6319	11.42	10.55	10.08	9.79
40 x 40 x 20	KDE2404PKV2.MS.A.GN	960-6327	11.42	10.55	10.08	9.79
60 x 60 x 25	KDE1206PTV2.13.MS.A.GN	960-6335	11.42	10.55	10.08	9.79
60 x 60 x 25	KDE2406PTV2.13.MS.A.GN	960-6343	11.42	10.55	10.08	9.79
80 x 80 x 25	KDE1208PTV2.13.MS.A.GN	960-6351	9.81	9.05	8.65	8.40
80 x 80 x 25	KDE2408PTV2.13.MS.A.GN	960-6360	11.42	10.55	10.08	9.79
92 x 92 x 25	KDE1209PTV2.13.MS.A.GN	960-6378	9.81	9.05	8.65	8.40
92 x 92 x 25	KDE2409PTV2.13.MS.A.GN	960-6386	11.42	10.55	10.08	9.79
120 x 120 x 25	KD1212PTB2-6A.GN	960-6394	19.61	18.10	17.30	16.81
120 x 120 x 25	KD2412PTB2-6A.GN	960-6408	19.61	18.10	17.30	16.81
120 x 120 x 38	KD1212PMB1-6A.GN	960-6416	19.61	18.10	17.30	16.81
120 x 120 x 38	KD2412PMB2-6A.GN	960-6424	19.61	18.10	17.30	16.81
DC - Green						
40 x 40 x 10	GM1204PFVX-AF.GN	960-6432	9.81	9.06	8.66	8.41
40 x 40 x 20	KDE1204PKVX.MS.AF.GN	960-6440	10.74	9.92	9.48	9.21
60 x 60 x 15	GM1206PHV1-AF.GN	960-6467	10.74	9.92	9.48	9.21
60 x 60 x 20	KDE1206PHV1.MS.AF.GN	960-6475	10.74	9.92	9.48	9.21
60 x 60 x 25	KDE1206PTVX.MS.AF.GN	960-6483	10.74	9.92	9.48	9.21

DC Axial Fans (Panaflo)

Hydro Wave Bearing



Compliant
Non-compliant
RoHS
Limited stock - RoHS replacement available

Panaflo axial fans suit a wide range of applications. They force air out in a "funnel" type pattern, and are ideal when cooling a specific area such as a power supply that is surrounded by numerous components with minimum ventilation available. Panaflo's unique Hydro Wave Bearing (HWB) addresses the traditional weakness of sleeve bearings, axial friction. The HWB system utilizes a thrust plate that "floats" on a circulating film of oil greatly reducing axial friction and bearing deterioration. The HWB pattern on the bearing virtually eliminates thrust plate contact.

- Locked rotor protection
- Auto-start function
- Lower circuit noise
- Easy access to lead wires (2) via plug-in connector on housing
- CSA Approved and UL Recognised

Dimensions (mm)	109-8888 & 109-8886	109-8889 & 109-8890	109-8891 & 109-8892	109-8893 & 109-8894
Dimensions (H x W x D)	60 x 60 x 25.5	80 x 80 x 25.5	92 x 92 x 25.5	120 x 120 x 38
Fixing hole $\varnothing$	4	4.5	4.5	4.5
Fixing centres	50 x 50	71.5 x 71.5	82.5 x 82.5	105 x 105

Voltage V dc	Power W	Air Flow cu.ft./min	m ³ /min	Noise dB	Current mA	Speed rpm	Mfrs. List No.
12	1.86	19.1	0.54	32	155	4200	FBA06A12H1A
24	2.04	19.1	0.54	32	85	4200	FBA06A24H1A
12	2.08	39.6	1.12	32	173	2950	FBA08A12H1A
24	2.52	39.6	1.12	32	105	2950	FBA08A24H1A
12	2.7	56.8	1.61	35	225	2850	FBA09A12H1A
24	3.36	56.8	1.61	35	140	2850	FBA09A24H1A
12	2.16	68.9	1.95	30	180	1700	FBA12G12L1A
24	2.64	68.9	1.95	30	110	1700	FBA12G24L1A

419664

Mfrs. List No.	Order Code	1+	5+	10+	25+	+
FBA06A12H1A	109-8886	45.24	41.99	40.39	37.92	--
FBA06A24H1A	109-8888	45.24	41.99	40.39	37.92	--
FBA08A12H1A	109-8889	49.09	44.33	44.17	41.40	--
FBA08A24H1A	109-8890	49.09	44.33	44.17	41.40	--
FBA09A12H1A	109-8891	64.38	58.43	54.20	49.87	--
FBA09A24H1A	109-8892	64.38	58.43	54.20	49.87	--
FBA12G12L1A	109-8893	83.49	78.51	75.13	68.71	--
FBA12G24L1A	109-8894	83.49	78.51	75.13	68.71	--

Thermal Speed Controlled Fans

'VARIOFAN'



80mm H=80, W=80, D=25
Cut-out $\varnothing$ =77, Lead length=310
Fix. centres=71.5 x 71.5 x 4

92mm H=92, W=92, D=25
Cut-out $\varnothing$ =89, Lead length=310
Fix. centres=82.5 x 82.5 x 4.3

119mm H=119, W=119, D=32
Cut-out $\varnothing$ =115, Lead length=310
Fix. centres=105 x 105 x 4

- Variable speed
- External NTC thermistor controls speed/airflow relative to temperature
- Thermistor supplied but not fitted, for user flexibility
- Fan speed automatically reduces by upto 50% as thermistor temperature decreases
- Overload and reverse polarity protected
- Glass reinforced plastic (POCAN) housing
- 80mm version VDE approved

Life expectancy >27500 hours (sleeve bearing (SB)) -20°C to +65°C
>37500 hours (ball bearing (BB))

Voltage V dc	Range V dc	Temp. of NTC °C	of NTC °C	Power Watts	Air Flow cu ft/min	l/s	Noise dBA@1m	Bearing type.	Mfrs. List No.	Order Code
80mm, Slim										
12	8 to 14	30	86.8	0.8	15.9	7.5	10	SB	8412NGMLV	960-0264
		50	30.0	1.5	26.5	15.5	19			
92mm, Slim										
12	8 to 14	30	86.8	1.9	29.5	14.0	16	SB	3412NGV	960-0272
		50	30.0	2.4	49.4	23.4	32			
119mm, Standard										
12	8 to 12.6	30	86.8	1.4	41.2	19.4	22	BB	4312MV-R	960-0183
		50	30.0	3.4	82.5	29.7	40			

204291


	Order Code	1+	10+	25+	50+	+
80mm, Slim	960-0264	45.14	43.00	41.74	39.50	--
92mm, Slim	960-0272	45.79	43.63	42.37	40.13	--
119mm, Standard	960-0183	86.78	81.65	76.83	72.99	--

Axial Flow Fans - Low Voltage dc

Micro Slim - 6mm Deep

5 V dc

multicomp




- 25, 30 and 40mm micro slim fans
- Ideal for precision cooling or compact equipment
- Patented single coil brushless 8 pole motor
- Locked rotor protection
- Precision ball bearings

Operating Voltage		5V dc		Operating Life		50000 hrs			
Operating temperature		-10°C to +70°C							
Dimensions		Power	Air Flow	Noise					
H	W	D	Type	Watts	cu ft/min	l/s	Order Code		
				dBA @ 1m	Mfrs.	List No.			
25	25	6	Low Noise, 25mm	0.4	1.2	0.57	21	GM0502PEV2-8.N.GN	960-6114
25	25	6	Standard, 25mm	0.6	1.6	0.76	29	GM0502PEV1-8.N.GN	960-6106
30	30	6	Low Noise, 30mm	0.45	2.4	1.15	20	GM0503PEV2-8.N.GN	960-6149
30	30	6	Standard, 30mm	0.65	3	1.43	25	GM0503PEV1-8.N.GN	960-6130
40	40	6	Low Noise, 40mm	0.5	4.35	2.07	22	GM0504PEV2-8.N.GN	960-6173
40	40	6	Standard, 40mm	0.7	5.5	2.6	26	GM0504PEV1-8.N.GN	960-6165

204367

	Voltage V dc	Order Code	1+	10+	25+	50+	+
25mm							
Low Noise	5	960-6114	26.35	25.29	23.94	20.88	--
Standard	5	960-6106	26.35	25.29	23.94	20.88	--
30mm							
Low Noise	5	960-6149	26.35	25.29	23.94	20.88	--
Standard	5	960-6130	26.35	25.29	23.94	20.88	--
40mm							
Low Noise	5	960-6173	26.35	25.29	23.94	20.88	--
Standard	5	960-6165	26.35	25.29	23.94	20.88	--

Miniature, 'Ultrastim'



- 25, 30, 35 and 40mm ultra slim fans
- Ideally suited for precision cooling
- Patented Single - coil brushless 8 pole motor design
- Locked rotor protection
- Low power consumption
- Fitted with precision ball bearings
- TUV approved, UL recognised

Voltage V dc	Power Watts	Air Flow cu ft/min	l/s	Noise dBA@1m	Mfrs. List No.	Order Code
12 ± 15%	0.72	2.0	0.9	24	GM1202PFV2-8.GN	960-6491
12 ± 15%	0.84	3.0	1.4	20.5	GM1203PFV2-8.GN	960-6505
12 ± 15%	0.84	4.5	2.1	21	GM1235PFV2-8.GN	960-6513
12 ± 15%	0.6	6.2	2.9	24.5	KDE1204PFV2.11.MS.A.GN	960-6521

204331

Dimension H W D	Voltage V dc	Order Code	1+	10+	25+	50+	+
25 25 10	12	960-6491	29.99	26.10	24.81	21.51	--
30 30 10	12	960-6505	29.99	26.10	24.81	21.51	--
35 35 10	12	960-6513	29.99	26.10	24.81	21.51	--
40 40 10	12	960-6521	22.15	19.38	18.36	16.08	--

Miniature, Tube Fans

micronel



- Brushless, low noise
- Black reinforced plastic housing and impeller
- Supplied with 200mm flying leads
- Sleeved bearings

Voltage V dc	Power Watts	Air Flow cu ft/min	l/s	Noise dBA@1m	Mfrs. List No.	Order Code
24mm Dia						
6	0.19	1.77	0.83	33	D241L-006GK-1	117-5738
12	0.26	2.12	1	38	D241L-012GK-1	117-5739

Prices are in Singapore Dollars and exclusive of GST.
Due to the volatile nature of certain products,
prices are subject to change without notice.

		Price Each				
Voltage	Order Code	1+	5+	10+	25+	+
60mm, Super Low Noise						
12V	960-1317	50.92	43.59	39.29	34.10	--
24V	960-0329	34.57	29.59	26.67	23.15	--
60mm, Standard						
24V	960-0345	34.57	29.59	26.67	23.15	--
12V	960-0310	35.62	31.89	28.75	24.95	--
12V	960-0647	35.62	31.89	28.75	24.95	--
24V	960-0655	35.62	31.89	28.75	24.95	--
80mm, Super Low Noise						
12V	960-1333	54.99	47.07	42.43	36.82	--
12V	960-1341	54.99	47.07	42.43	36.82	--
80mm, Standard						
12V	959-9827	53.34	45.66	41.15	35.71	--
48V	960-1325	62.85	55.41	50.89	44.17	--
92mm, Super Low Noise						
12V	960-1350	56.93	48.73	43.92	38.12	--
92mm, Standard						
12V	959-9851	52.30	44.77	40.35	35.02	--
24V	959-9860	52.30	44.77	40.35	35.02	--
119mm, Super Low Noise						
12V	960-1368	59.60	53.33	48.07	41.72	--
24V	960-1376	57.20	48.96	44.13	38.30	--
119mm, Super Low Noise, 38mm Depth						
12V	960-0469	54.99	47.07	42.43	36.82	--
24V	960-0493	54.99	47.07	42.43	36.82	--
119mm, Low Noise						
12V	960-1384	59.60	53.33	48.07	41.72	--
24V	960-1392	57.20	48.96	44.13	38.30	--
119mm, Low Noise, 38mm Depth						
12V	960-0477	54.99	47.07	42.43	36.82	--
24V	960-0507	54.99	47.07	42.43	36.82	--
119mm, Standard						
12V	959-9878	53.82	46.07	41.52	36.04	--
24V	959-9886	53.82	46.07	41.52	36.04	--
48V	960-1406	63.56	55.82	51.27	44.49	--
119mm, Standard, 38mm Depth						
12V	960-0698	55.05	49.32	44.45	38.58	--
24V	960-0701	55.05	49.32	44.45	38.58	--
127mm, Standard						
24V	960-1090	106.00	93.08	85.50	74.20	--
135mm, Standard						
12V	960-1104	189.39	170.98	157.04	136.29	--
24V	960-1112	148.49	134.06	123.13	106.86	--

Standard



- UL94V-0 plastic casing and impeller
- Shielded ball bearings
- Reverse polarity protected
- Auto-restart facility will shut-down the current if a blockage occurs
- Connection by two 300mm lead wires + Red, - Black
- CSA approved, UL recognised

Fan size			40mm	60mm	120mm			
Cut-out ☒			38	57	114.5			
Fix Centres			32	50	105			
Fix. hole ☒			4	4	4.3			
Dimensions			Voltage	Power	Air Flow	Noise	Mfrs. List No.	Order Code
H	W	D	V dc	Watts	cu ft/min	dBA@1m		
40	40	15	5	0.6	6	28	1606KL-01W-B30-L00	101-2743
40	40	15	5	1.2	8.1	34	1606KL-01W-B50-L00	101-2744
40	40	15	12	0.8	6	28	1606KL-04W-B30-L00	942-0134
40	40	15	12	1.02	8.1	34	1606KL-04W-B50-L00	101-2746
40	40	15	24	1.08	6	28	1606KL-05W-B30-L00	101-2747
40	40	15	24	0.5	8.1	34	1606KL-05W-B50-L00	101-2748
50	50	10	5	10.2	6.4	28.5	2004KL-01W-B30-M00	101-2749
50	50	10	5	6.4	10.2	34	2004KL-01W-B50-M00	101-2750
50	50	10	12	10.2	6.4	23	2004KL-04W-B30-M00	101-2751
50	50	10	12	1.92	10.2	34	2004KL-04W-B50-M00	101-2752
52	52	15	12	1.08	12	25.5	2106KL-04W-B40-L00	101-2753
60	60	20	12	0.6	10.9	22.5	2408NL-04W-B10-P00	101-2754
60	60	20	12	1.32	17.6	31.5	2408NL-04W-B50-P00	101-2755
60	60	20	24	0.96	10.9	22.5	2408NL-05W-B10-P00	101-2756
60	60	20	24	1.32	17.6	31.5	2408NL-05W-B50-P00	101-2758
60	60	25	12	1.44	23.5	35	2410ML-04W-B30-E00	942-0142
60	60	25	12	1.44	37	46	2410ML-04W-B80-E00	101-2759
60	60	25	24	6.20	19	31	2410ML-05W-B30-E00	101-2760
60	60	25	24	1.44	37	50	2410ML-05W-B80-E00	101-2761
60	60	25	12	0.6	13	19	2410RL-04W-B10-C00	101-2762

Dimensions	Voltage	Power	Air Flow	Noise		
60 60 25	12	1.8	24	33.5	2410RL-04W-B50-C00	101-2763
60 60 25	12	3.24	28.5	38	2410RL-04W-B70-C00	101-2764
60 60 25	24	0.96	13	19	2410RL-05W-B10-C00	101-2765
60 60 25	24	2.88	24	33.5	2410RL-05W-B50-C00	101-2766
60 60 25	24	4.80	28.5	38	2410RL-05W-B70-C00	101-2767
80 80 15	12	2.04	28.2	30	3106KL-04W-B40-C00	101-2768
80 80 15	12	2.76	32.8	34	3106KL-04W-B50-C00	101-2771
80 80 25	12	2.76	38.8	34	3110KL-04W-B50-P00	101-2772
80 80 25	24	2.88	38.8	34	3110KL-05W-B50-P00	101-2773
80 80 25	12	0.84	24	22	3110RL-04W-B10-C00	101-2774
80 80 25	12	3.00	38.5	32.5	3110RL-04W-B50-C00	101-2775
80 80 25	12	4.08	44.5	36	3110RL-04W-B70-C00	101-2776
80 80 25	24	0.96	24	22.0	3110RL-05W-B10-C00	101-2777
80 80 25	24	3.36	38.5	32.5	3110RL-05W-B50-C00	101-2778
80 80 25	24	4.32	44.5	36.0	3110RL-05W-B70-C00	101-2779
92 92 32	12	2.52	47.3	34	3612KL-04W-B30-B00	101-2780
92 92 32	12	5.64	69.9	43.5	3612KL-04W-B50-B00	101-2781
92 92 32	24	2.40	47.3	34	3612KL-05W-B30-B00	101-2783
92 92 32	24	6.0	69.9	43.5	3612KL-05W-B50-B00	101-2784
92 92 38	12	15.6	107	54	3615KL-04W-B70-E01	101-2785
92 92 38	24	16.8	189.0	53	3615KL-05W-B70-E00	101-2786
119 119 25	12	3.36	88.2	35	4710KL-04W-B30-E00	101-2787
120 120 25	12	6.84	90	39	4710KL-04W-B50-E00	942-0150
119 119 25	24	3.60	88.2	35	4710KL-05W-B30-E00	101-2788
119 119 25	24	6.96	114.7	41.5	4710KL-05W-B50-E00	101-2789
119 119 32	12	5.76	99.9	44	4712KL-04W-B30-P00	101-2790
119 119 32	24	6.72	99.9	44	4712KL-05W-B30-P00	101-2791
120 120 38	12	6.6	108.2	42.5	4715KL-04W-B30-P00	942-0169
119 119 38	24	7.44	108.0	42.5	4715KL-05W-B30-P00	101-2792
150 172 25	12	2.06	250	62.5	5910PL-04W-B50-L00	101-2793
150 172 25	48	35.5	290	65.4	5910PL-05W-B70-L00	101-2795

204297

Dimensions			Voltage	Price Each					
H	W	D	Vdc	Order Code	1+	10+	25+	50+	+
40	40	15	5	101-2743	47.85	43.52	40.92	37.24	--
40	40	15	5	101-2744	47.85	43.52	40.92	37.24	--
40	40	15	12	942-0134	46.29	41.71	39.60	34.78	--
40	40	15	12	101-2746	47.85	43.52	40.92	37.24	--
40	40	15	24	101-2747	47.85	43.52	40.92	37.24	--
40	40	15	24	101-2748	47.85	43.52	40.92	37.24	--
50	50	10	5	101-2749	39.39	36.46	35.48	31.57	--
50	50	10	5	101-2750	39.39	36.46	35.48	31.57	--
50	50	10	12	101-2751	39.39	36.46	35.48	31.57	--
50	50	10	12	101-2752	39.39	36.46	35.48	31.57	--
52	52	15	12	101-2753	34.18	30.60	27.83	25.23	--
60	60	20	12	101-2754	57.35	45.90	38.25	34.34	--
60	60	20	12	101-2755	57.35	45.90	38.25	34.34	--
60	60	20	24	101-2756	57.35	45.90	38.25	34.34	--
60	60	20	24	101-2758	57.35	45.90	38.25	34.34	--
60	60	25	12	942-0142	54.30	48.89	46.37	40.79	--
60	60	25	12	101-2759	56.12	51.04	47.91	43.68	--
60	60	25	24	101-2760	56.12	51.04	47.91	43.68	--
60	60	25	24	101-2761	56.12	51.04	47.91	43.68	--
60	60	25	12	101-2762	27.83	24.15	21.97	18.23	--
60	60	25	12	101-2763	27.83	24.15	21.97	18.23	--
60	60	25	12	101-2764	27.83	24.15	21.97	18.23	--
60	60	25	24	101-2765	27.83	24.15	21.97	18.23	--
60	60	25	24	101-2766	27.83	24.15	21.97	18.23	--
60	60	25	24	101-2767	27.83	24.15	21.97	18.23	--
80	80	15	12	101-2768	39.55	35.94	32.45	28.58	--
80	80	15	12	101-2771	39.55	35.94	32.45	28.58	--
80	80	25	12	101-2772	65.36	52.28	43.55	39.87	--
80	80	25	24	101-2773	65.36	52.28	43.55	39.87	--
80	80	25	12	101-2774	31.12	27.50	25.16	21.74	--
80	80	25	12	101-2775	31.12	27.50	25.16	21.74	--
80	80	25	12	101-2776	31.12	27.50	25.16	21.74	--
80	80	25	24	101-2777	31.12	27.50	25.16	21.74	--
80	80	25	24	101-2778	31.12	27.50	25.16	21.74	--
80	80	25	24	101-2779	31.12	27.50	25.16	21.74	--
92	92	32	12	101-2780	59.40	54.52	51.49	43.19	--
92	92	32	12	101-2781	59.40	54.52	51.49	43.19	--
92	92	32	24	101-2783	59.40	54.52	51.49	43.19	--
92	92	32	24	101-2784	59.40	54.52	51.49	43.19	--
92	92	38	12	101-2785	61.68	56.96	54.78	46.61	--
92	92	38	24	101-2786	61.68	56.96	54.78	46.61	--
119	119	25	12	101-2787	54.52	49.61	46.61	42.48	--
120	120	25	12	942-0150	52.76	47.53	45.11	39.66	--
119	119	25	24	101-2788	54.52	49.61	46.61	42.48	--
119	119	25	24	101-2789	54.52	49.61	46.61	42.48	--
119	119	32	12	101-2790	57.81	53.48	50.84	46.90	--
119	119	32	24	101-2791	57.81	53.48	50.84	46.90	--
120	120	38	12	942-0169	59.25	53.36	50.68	44.51	--
119	119	38	24	101-2792	61.23	55.69	52.37	47.69	--
150	172	25	12	101-2793	301.09	271.50	249.17	215.58	--
150	172	25	48	101-2795	301.09	271.50	249.17	215.58	--

Operating temperature -10°C to +70°C			Life expectancy >50000 hours @ 40°C			
Dimensions	Voltage Vdc	Power Watts	Air Flow cu ft/min	ltrs/sec	Noise dBA @ 1m	Order Code
40mm						
40 x 40 x 20	12V	1	7.3	3.4	26	960-6645
40 x 40 x 20	24V	0.96	6.2	2.9	25	960-6653
60mm						
60 x 60 x 25	12V	1.4	18	8.4	31	960-6661
60 x 60 x 25	24V	1.9	18	8.4	31	960-6670
80mm						
80 x 80 x 25	12V	2	35	16.5	32	960-6688
80 x 80 x 25	24V	3.12	35	16.5	32	960-6696
92mm						
92 x 92 x 25	12V	2.1	45	21.2	34	960-6700
92 x 92 x 25	24V	2.9	45	21.2	34	960-6718
119mm						
119 x 119 x 25	12V	3.6	80	37.7	41	960-6726
119 x 119 x 25	24V	4.8	80	37.7	42	960-6734
119 x 119 x 38	12V	6.8	108	50.9	42	960-6742
119 x 119 x 38	24V	5.5	98	46.2	36	960-6750
	40mm	60mm	80mm	92mm	119mm	
Height	40	60	80	92	119	
Width	40	60	80	92	119	
Depth	20	25	25	25	25	
Cut-out ☉	38	58	77	89	116	
Fix Centres	32 x 32	50 x 50	71.5 x 71.5	82.5 x 82.5	104.8 x 104.8	
Fix Centres ☉	4.5	4.5	4.5	4.3	4.3	

204301

Size		Voltage	Price Each					
H	W	D	V dc	Order Code	1+	10+	25+	50+
40	40	20	12	960-6645	36.63	32.04	28.83	22.68
40	40	20	24	960-6653	36.63	32.04	28.83	22.68
60	60	25	12	960-6661	40.48	33.90	31.44	26.55
60	60	25	24	960-6670	40.48	33.90	31.44	26.55
80	80	25	12	960-6688	39.02	32.58	30.24	24.84
80	80	25	24	960-6696	39.02	32.58	30.24	24.84
92	92	25	12	960-6700	40.70	35.37	33.09	24.96
92	92	25	24	960-6718	40.70	35.37	33.09	24.96
119	119	25	12	960-6726	43.45	38.88	36.93	30.93
119	119	25	24	960-6734	43.45	38.88	36.93	30.93
119	119	38	12	960-6742	45.99	41.10	39.03	33.18
119	119	38	24	960-6750	45.99	41.10	39.03	33.18

Long Life

SANYO DENKI



- Up to 20 years (200,000 hours) continuous operation, 5 times longer life than conventional fans
- Diecast aluminium housing with UL94V-1 plastic impeller
- Oversize ball bearings
- Reverse polarity and locked rotor protection
- Connection by two 300mm, 24Awg leads
- Conforms to EN609-50

Life expectancy >200,000 hrs (120mm), >100,000 hrs (80mm, 92mm and 140mm)

Dimensions			Voltage	Power	Air Flow	Noise	Mftrs.	Order
H	W	D	V dc	Watts	cu ft/min	ltrs/sec	dBA @ 1m	List No.
80	80	25	12	2.1	37.5	17.73	32	109L0812H402
80	80	25	24	2.1	37.5	17.73	32	109L0824H402
92	92	25	12	2.5	48.9	23	33	109L0912H402
92	92	25	24	2.8	48.9	23	33	109L0924H402
120	120	38	12	4.8	106	50	41	109L1212H102
120	120	38	24	5	106	50	41	109L1224H102
120	120	38	48	5.7	106	50	41	109L1248H102
140	140	51	12	16.8	209	98.5	52	109L1412H502
140	140	51	24	14.4	209	98.5	52	109L1424H502

Fan size	80mm	92mm	120mm	140mm
Cut-out ☉	78	89	117	136
Fixing centres	71.5	82.5	104.8	142.5
Fixing hole ☉	4.3	4.3	4.3	4.3

204322

Size		Voltage	Price Each				
H	W	D	V dc	Order Code	1+	5+	20+
80	80	25	12	994-8198	105.90	100.83	85.90
80	80	25	24	994-8201	105.90	100.83	85.90
92	92	25	12	994-8210	119.13	113.43	96.61
92	92	25	24	994-8228	119.13	113.43	96.61
120	120	38	12	994-8236	182.24	173.50	147.80
120	120	38	24	994-8244	182.24	173.50	147.80
120	120	38	48	994-8163	182.24	173.50	147.80
140	140	51	12	994-8171	241.78	230.17	196.12
140	140	51	24	994-8180	241.78	230.17	196.12

Humidity Protected

ebmpapst



- Improved humidity protection ≤95%
- Designed to meet humidity range according to group C of DIN40040 item 3.3

Limits of relative humidity are: Annual Mean Value ≤95%
Maximum value a) On 30 days of the year (naturally distributed) 100 %
b) On all other days occasionally (under observance of the annual mean value 100%, dewing is allowed)

Voltage	Range	Power	Air Flow	Noise	Bearing	Mftrs.	Order
V dc	V dc	Watts	cu ft/min	dBA@1m	Type	List No.	Code
12	8 to 15	2.0	19.4	9.1	SB	8412NGR	960-0108
24	18 to 28	0.7	19.4	9.1	SB	8414NGR	960-0116
12	6 to 15	5	100	47.2	BB	4312R	960-0124
24	12 to 28	5	100	47.2	BB	4314R	960-0132

204348

Dimensions		Voltage	Price Each				
H	W	D	V dc	Order Code	1+	10+	25+
80	80	25	12	960-0108	43.25	41.11	38.90
80	80	25	24	960-0116	43.25	41.11	38.90
120	120	32	12	960-0124	65.90	62.59	59.31
120	120	32	24	960-0132	65.90	62.59	59.31

IP54 Rated

ebmpapst



- IP54 rating gives protection in extreme environmental conditions
- Complete stator and PCB are totally encapsulated in polyurethane which is applied under high vacuum pressure forming a one piece moulding
- High quality stainless steel bearing system

Dimensions			Voltage	Power	Air Flow	Noise	Mftrs.	Order
H	W	D	V dc	Watts	cu ft/min	ltrs/sec	dBA @ 1m	List No.
80	80	32	12	2.2	32	15.1	36	8312U
80	80	32	24	2.2	32	15.1	36	8314U
120	120	32	12	5.4	82.4	38.8	39	4312U
120	120	32	24	2.6	82.4	38.8	39	4314U

204351

Dimensions		Voltage	Price Each				
H	W	D	V dc	Order Code	1+	10+	25+
80	80	32	12	960-0140	88.29	83.88	79.44
80	80	32	24	960-0159	83.49	79.32	75.35
120	120	32	12	960-0167	95.78	91.00	86.22
120	120	32	24	960-0175	95.78	91.00	86.22



In stock and ready to despatch,
300,000 products in our Asia, US
and Europe warehouses.

300,000 products at your fingertips

IP54 Rated Sprite DC and Muffin XL DC



- Internal fan encapsulation to prevent damage from dust & water
- Die-cast venturi, with **UL94-V0** flame retardant polypropylene impeller
- Stainless steel ball bearings
- Two lead wires AWG22, **UL 1061**
- **UL** recognised, **CSA** and **TUV** approved
- Order code 118-7531 supplied with tachometer



Voltage V dc	Current A	Power Watts	Noise dBA@1m	Speed RPM	Air Flow cu ft/min	Mfrs. List No.	Order Code
24	0.13	3	47.6	3500	35	SD24B5-E2 039029	102-3667
24	0.25	6	50	3100	110	MD24B5-E2 039030	102-3672
24	0.63	15	53.6	3200	150	GL24B7E	118-7531

311680

Dimensions			Voltage V	Order Code	Price Each				
H	D				1+	5+	10+	25+	+
80	42	24		102-3667	109.35	100.05	91.56	84.77	--
119	39.1	24		102-3672	120.27	110.04	100.68	93.23	--
127	38	24		118-7531	195.92	187.00	178.89	171.44	--

127mm 'Galaxy'



- Feathered edge impeller for low noise
- Stainless steel ball bearings
- **CSA** and **VDE** approved, **UL** recognised
- 3.05mm solder terminals



Voltage V dc	Power Watts	Air Flow cu ft/min	lts/sec	Noise dBA@1m	Mfrs. List No.	Order Code
12	15	150	71	53.6	GL12B4	102-3647
24	15	150	71	53.6	GL24B4 031075	102-3648

204365

Dimensions			Voltage V dc	Order Code	Price Each				
H	W	D			1+	5+	10+	15+	+
127	127	38	12	102-3647	119.23	109.50	101.36	95.40	--
127	127	38	24	102-3648	119.23	109.50	101.36	95.40	--

172mm



- Metal fan housing and impeller
- Fitted with ball bearings
- Electronic protection against reverse polarity and blocking
- Electronic motor current limitation on start up and when rotor is blocked
- **VDE** and **CSA** approved, **UL** recognised

ebmpapst


Voltage V dc	Power Watts	Air Flow cu ft/min	lts/sec	Noise dBA@1m	Mfrs. List No.	Order Code
12	12	206	97.7	50	6212NM	960-0213
24	18	241.3	114	55	6224N	960-0221

204360

Dimensions			Voltage V dc	Order Code	Price Each				
Dia.	Depth				1+	5+	10+	15+	+
172	51	12		960-0213	146.58	142.88	139.26	131.92	--
172	51	24		960-0221	127.88	124.68	121.50	115.10	--

Accessories


Finger Guards and Filters



204347

Finger Guards	Order Code	1+	10+	25+	50+	+	+
40mm, Metal	112-4757	6.15	5.64	5.31	4.83	--	--
50/62mm, Metal	112-4759	6.55	6.09	5.73	5.40	--	--
80mm, Metal	112-4760	7.08	6.36	6.03	5.61	--	--
80mm, Plastic	112-4771	5.45	5.13	4.50	3.99	--	--
92mm, Metal	112-4761	7.31	7.20	6.99	6.57	--	--
92mm, Plastic	112-4774	5.54	5.25	4.71	3.81	--	--
119mm, Metal	112-4762	7.83	7.08	6.66	6.30	--	--
119mm, Plastic	112-4772	6.21	5.64	5.07	4.44	--	--
127mm, Metal	112-4773	10.50	9.09	7.59	6.60	--	--
135mm, Metal	117-1803	11.67	10.27	9.26	8.56	--	--
160mm, Metal	112-4763	9.58	8.91	8.49	8.13	--	--
Filters							
60/62mm	117-1799	32.01	28.65	26.94	24.39	--	--
80mm	117-1791	40.94	40.11	38.88	36.81	--	--
119mm	117-1796	34.09	33.39	32.40	29.82	--	--
160mm	117-1808	46.39	41.52	38.46	33.96	--	--
		1+	10+	25+	50+	+	+
Replacement Filters (5 Per Pack)							
60/62mm	117-1801	3.09	2.79	2.52	2.52	--	--
80mm	117-1797	3.65	3.18	3.00	2.91	--	--
119mm	117-1798	4.53	4.05	3.75	3.51	--	--
160mm	117-1809	6.77	6.12	5.43	4.92	--	--

Metal Mesh Filter



Fan Mount

- Designed for 120mm fans
- Black fibre glass reinforced plastic bezel with inserted stainless steel wire mesh

204361

Mfrs. List No.	Order Code	1+	10+	25+	50+	+
LZ40N	117-1813	28.64	26.94	26.25	24.81	--

19

Fans


ebmpapst

Compliant
Non-compliant
+ Limited stock - RoHS replacement available

RoHS

Filter Assemblies

ebmpapst



- Mount directly onto existing fixing locations
- Assemblies consist of 3 elements, outer grill cover, inner fixing plate and filter pad
- The grill cover is moulded in polycarbonate with a matt finish, it incorporates quick release fasteners to assist filter changes
- The inner fixing plate is constructed of steel sheet with a black epoxy powder finish. A plastic screen provides protection when the filter is changed and the fan is running
- The filter pad is made of white synthetic bonded fibre to **P15/150R**
- The filter will achieve 75% dust particle retention down to 5-10 microns in size, can withstand temperatures up to 100°C and is flame resistant to **BS2963**
- Reduction in airflow of 20-30%

311653

Filter Assemblies	Mfrs. List No.	Order Code	Price Each/Per Pack
80mm	PMFA80T	117-1820	4.95
120mm	PMFA120T	117-1821	8.79
Replacement Filters			
80mm x 5 filters	FP80T	117-1822	3.51
120 x 5 filters	FP120T	117-1825	3.66

19

Fans

Filter Assemblies



- Assemblies consist of guard, polyurethane foam filter, and media retainer
- Manufactured from **UL94-V0** high impact plastic

204318

Filter Assemblies	Order Code	1+	10+	25+	50+	+
80mm	112-4764	11.11	10.32	9.54	7.98	--
92mm	112-4765	12.01	11.16	10.29	8.58	--
119mm	112-4767	13.29	12.36	11.40	9.54	--
Replacement Filters (5 Per Pack)						
80mm	112-4768	6.15	5.97	5.46	4.50	--
92mm	112-4769	6.46	5.82	5.37	4.23	--
119mm	112-4770	7.19	6.24	5.76	4.80	--

EMC Screened Filters

ebmpapst



- High efficiency EMC screened axial fan filters/finger guards
- One piece welded mesh construction
- Excellent overall screening effectiveness over fan aperture
- Only 1% airflow reduction, compared with 20% from a conventional woven mesh filter


Size	Average screening effectiveness (dB) 40MHz 1GHz/1.1 GHz - 4GHz	Mfrs. List No.	Order Code
40mm	—	PRF40.	341-4530
60/62mm	14.05/15.40	PRF60.	593-631
80mm	23.05/25.80	PRF80	117-1805
92mm	24.74/25.14	PRF90.	593-655
119mm	31.79/22.95	PRF120..	593-667

204305

Size	Order Code	1+	10+	25+	50+	+
40mm	117-1826	16.38	--	--	--	--
60/62mm	117-1804	26.59	22.95	21.81	15.30	--
80mm	117-1805	25.61	22.08	21.00	14.40	--
92mm	117-1806	27.82	24.03	22.83	15.63	--
119mm	117-1807	28.83	24.87	23.64	17.88	--

Mixed Flow Fans

ebmpapst

Low Voltage DC, 172mm
High Airflow Pressure

- Combines the structural features of axial and radial fans
- Generates greater static pressure than a standard axial fan
- Metal housing with glass reinforced plastic impeller
- Fully integrated commutation electronics, electronic protection against reverse polarity and blocking

Voltage	Dimensions Dia	D	Power Watts	Air Flow cu ft/min	ltrs/sec	Noise dBA	Mfrs. List No.	Order Code
24V dc	172	51	37	317.8	149.9	63	DV6224	960-0604

204353

Dimensions Dia	D	Voltage	Order Code	1+	10+	25+	50+	+
172	51	24V dc	960-0604	181.47	172.37	163.30	154.43	--

Backward Curved Fans

Backward Curved Centrifugal Fan
230V ac

ebmpapst



- Ideal for sucking applications against pressure systems, example: extraction from hoods and cabinets
- Non-overloading characteristics
- Utilises external rotor motors
- Built-in thermal protection
- Maintenance-free ball bearings
- Operation possible without scroll

Impeller (mm)	Air Flow (l/s)	Noise level (dB)	Mfrs. List No.	Order Code
133	72	55	R2S133-AE17-05	960-1228
175	119	56	R2S175-AB56-01	960-1236
190	576	63	R2E190-A026-05	960-1244
220	860	74	R2E220-AA40-05	101-1723
225	850	70	R2E225-AT51-05+CAP	960-1252

213834

Air Flow (l/s)	Mfrs. List No.	Order Code	1+	5+
72	R2S133-AE17-05	960-1228	122.68	116.56
119	R2S175-AB56-01	960-1236	163.24	155.07
160	R2E190-A026-05	960-1244	203.57	197.38
900	R2E220-AA40-05	101-1723	205.65	184.36
236	R2E225-AT51-05+CAP	960-1252	279.31	251.37

Flatpack Fans

High Static Pressure for Crowded Enclosures

ebmpapst



- Durable construction - fibreglass blower wheel and housing mounted on galvanised steel plate
- Electronic protection against reverse polarity and thermal overload
- Air flows into axis of rotation and exhausts through port on one edge
- Supplied with two connecting leads approx 300mm long with stripped and tinned ends
- Advanced ball bearing design for very long operational life, 121mm ac fans have sleeved bearings

Operating temperature -20°C to +60°C

Dimensions H W D	Voltage	Power Watts	Air Flow cu ft/min	ltrs/sec	Noise dBA	Mfrs. List No.	Order Code
121 121 37	115V ac	19.5	24.7	11.7	56	RL90-18/00.	311-1570
121 121 37	230V ac	20	23.5	11.1	56	RL90-18/50.	311-1581

Dimensions H W D	Voltage	Order Code	1+	10+	25+	50+	+
121 121 37	115V ac	311-1570	106.25	100.96	95.63	85.02	--
121 121 37	230V ac	311-1581	106.25	100.96	95.63	85.02	--

Dimensions H W D	Voltage	Power Watts	Air Flow cu ft/min	ltrs/sec	Noise dBA	Mfrs. List No.	Order Code
121 121 37	12V dc	5.5	23.5	11	58	RL90-18/12N	959-9932
121 121 37	24V dc	5	23.5	11	58	RL90-18/14N	959-9940
121 121 37	115V ac	19.5	24.7	11.7	56	RL90-18/00	960-0230
121 121 37	230V ac	20	23.5	11.1	56	RL90-18/50	960-0248
135 135 38	24V dc	5.5	32.4	15.2	55	RG90-18/14N	959-9959

Prices are in Singapore Dollars and exclusive of GST.
Due to the volatile nature of certain products,
prices are subject to change without notice.

Dimensions	Power	Air Flow	Noise	Mfrs.	
135 135 38 230 dc	22	31.8	15 58	RG90-18/56	960-0876
180 180 40 24 ac	5	51.5	24.3 58	RG125-19/14N	959-9967
220 220 56 12V dc	21	118.9	56.1 66	RG160-28/12	960-0868
220 220 56 24V dc	20	122.9	57.9 66	RG160-28/14N	959-9975
220 220 56 230 dc	47	118.9	56.1 66	RG160-28 56S	960-0884

204293

Dimensions	Order Code	1+	10+	25+	50+	+
H W D Voltage						
121 121 37 12V dc	959-9932	89.06	84.60	80.40	76.39	--
121 121 37 24V dc	959-9940	94.00	89.32	84.89	80.63	--
121 121 37 115V ac	960-0230	106.25	100.96	95.63	85.02	--
121 121 37 230V ac	960-0248	106.25	100.96	95.63	85.02	--
135 135 38 24V dc	959-9959	100.55	95.53	90.75	86.22	--
135 135 38 230V ac	960-0876	84.37	80.17	76.17	72.36	--
180 180 40 24V dc	959-9967	117.11	111.29	105.72	100.45	--
220 220 56 12V dc	960-0868	227.80	210.74	205.16	178.29	--
220 220 56 24V dc	959-9975	223.34	206.61	201.10	185.69	--
220 220 56 230V ac	960-0884	200.11	180.05	171.04	152.74	--

Low Voltage DC, 120mm, 162mm 'Biscuit' and 'Spinnaker'



- Air flows into axis of rotation and exhausts through port on one edge
- Ideal for crowded enclosures or where space is a premium
- Stainless steel ball bearings
- Electronic locked rotor protection
- CSA and VDE approved, UL recognised

Voltage V dc	Power Watts	Air Flow cu ft/min	lts/sec	Noise dBA@1m	Mfrs. List No.	Order Code
12	11	25	11.8	51	BD12A3 032176	102-3654
24	11	25	11.8	51	BD24A3 032179	102-3655
24	30	60	28.3	57	SPD24B1	118-7493

204363

Dimensions	Voltage	Order Code	1+	5+	10+	15+	+
H W D V dc							
120 120 31 12	12	102-3654	78.93	68.68	63.15	58.49	--
120 120 31 24	24	102-3655	71.25	63.21	57.00	52.80	--
162 162 41 24	24	118-7493	153.08	143.87	137.75	122.84	--

Low Voltage DC



H = 47, W = 50
L = (203 = 899-914, 260 = 899-926, 365 = 899-938)

- Crossflow fans provide a long but narrow air discharge pattern
- Ideal for cooling electronics in assembly carriers
- Locked rotor and polarity protected
- Very low noise level

Voltage V dc	Power Watts	Air Flow cu ft/min	lts/sec	Noise dBA@1m	Mfrs. List No.	Order Code
12	6.1	39.4	18.6	48	Q2G030-EA21-01	960-1570
12	8	53	25	51	Q2G030-GC01-01	960-1589
12	8.5	76.5	36.1	49	Q2G030-FB01-01	960-1597

227522

Length	Voltage V dc	Order Code	1+	5+	10+	25+
203mm	12	960-1570	145.68	138.41	131.13	123.39
260mm	12	960-1589	183.75	174.60	165.38	148.49
365mm	12	960-1597	180.53	171.55	163.35	--



- FREE to all account holders
- Notification of obsolete, end of line and end of stock items
- Replacement or upgrade recommendations

**Advanced warning of
obsolete components**

Blowers



Low Voltage Blowers



- 12, 24VDC input electronically commutated blowers
- Operating temperature 0-50°C
- Choice of 76 and 145mm housings
- Maximum pressure to 64 mbar
- Maximum air flows to 18L/sec
- Adjustable air performance
- Compact size
- Long life
- ISO 9002

Mfrs. List No.	Case Dia. (mm)	Overall Height (mm)	Outlet Tube Dia. (O.D. in mm)	VDC	Max. Pressure (mBar Sealed)	Max Flow (L/sec)	Order Code
116521-52	145	84	31.55	24	20	18	113-8976
119349-51	76	71	20.62	12	24	8.5	113-8969
119350-51	76	71	20.62	24	24	8.5	113-8970

233668

Mfrs. List No.	Order Code	1+	2+	5+
116521-52	113-8976	1,108.36	991.70	933.37
119349-51	113-8969	639.80	572.46	538.80
119350-51	113-8970	639.80	572.46	538.80



Low Voltage Blowers



- 12, 24VDC input electronically commutated blowers
- Operating temperature 0-50°C
- 127mm housing
- Maximum pressure to 60 mbar
- Maximum air flows to 21L/sec
- Electrical and mechanical control versions
- Internal and external drive versions
- Adjustable air performance
- Thermal protection/locked rotor protection
- Compact size & long life

Mfrs. List No.	Overall Height (mm)	Outlet Tube Dia. (O.D. in mm)	VDC	Max. Pressure (mBar Sealed)	Max. Flow L/Sec	Control Type	Order Code
150016-51	76.2	24	30	16	16	External	113-8971
119382-52	68.58	12	30	16	16	External	113-8973
119384-52	68.58	24	30	16	16	Mechanical	113-8974
119379-52	68.58	24	60	21	21	External	113-8975

233679

Mfrs. List No.	Order Code	1+	2+	5+
150016-51	113-8971	464.49	415.60	391.15
119382-52	113-8973	805.65	720.82	678.44
119384-52	113-8974	805.65	720.82	678.44
119379-52	113-8975	903.56	808.44	760.89

Centrifugal Fans



- Backward curve centrifugal fan, which can be operated with or without a scroll
- Impeller is completely made of plastic PA6.6, injection moulded round a sheet metal plate
- Supplied with inlet ring and capacitor
- Ideal for systems requiring high pressure development

Voltage	Power Input	Air Flow	Noise	Dimensions (WxHxD)	Weight	Mfrs. List No.	Order Code
230V ac, 50/60Hz	58/75W	570/620	52/64	190 x 62.8mm	1.2kg	R2E190-A026-05	101-1722
230V ac, 50/60Hz	85/90W	860/900	73/74	220 x 71mm	1.5kg	R2E220-AA40-05	101-1723

416703

Mfrs. List No.	Order Code	1+	2+	5+	+	+
R2E190-A026-05	101-1722	173.00	158.06	140.52	--	--
R2E220-AA40-05	101-1723	205.65	184.36	163.92	--	--

Compliant
Non-compliant
RoHS
+ Limited stock - RoHS replacement available

DC Centrifugal Blowers



- Brushless DC motor with plastic fan housing and impeller
- High static pressure performance
- Permanently lubricated dual ball bearing system
- Long life and high reliability (L10 40,000 hours continuous operation at 60°C ambient)
- Current limited system with reverse polarity protection
- UL, CSA and TUV approved

Voltage V dc	Power Watts	Air Flow cu. ft./min.	Noise dBA@1m	Operating Temp °C	Mfrs. List No.	Order Code
12	4.44	12.7	41.5	-10 to +60	109BD12HA2	994-8015
24	4.08	12.71	41.5	-10 to +60	109BD24HA2	994-8023
12	7.2	27.5	52	-10 to +60	109BF12HA2	994-8031
24	7.2	27.5	52	-10 to +60	109BF24HA2	994-8040
12	6.24	27.54	46	-10 to +60	109BJ12HA2	994-8058

233520

SANYO DENKI

Dimensions (mm)	Mfrs. List No.	Order Code	1+	5+	10+	20+
75.5 x 76 x 30	109BD12HA2	994-8015	45.47	44.59	44.13	—
76 x 76 x 30	109BD24HA2	994-8023	57.68	54.90	50.34	46.46
120 x 120 x 32	109BF12HA2	994-8031	61.69	58.84	53.93	49.80
120 x 32 x 32	109BF24HA2	994-8040	61.69	58.84	53.93	49.80
127 x 127 x 32	109BJ12HA2	994-8058	89.64	85.43	78.44	72.39

Single Inlet Blowers - AC



- High performance single inlet fans with an external rotor motor offering the advantage of matched motor and impeller in a compact space saving design
- Motors are IP 44 rated, sealed for life, maintenance free, class B insulation and precision ball bearings
- Impeller is forward curved multi-vane type 'force' fitted for vibration free operation and efficient cooling

- Scroll is made from die-cast aluminium with motor capacitor and terminal block
- May be mounted in any position

Voltage	Power Input	Air Flow	Noise	Dimensions (WxHxD)	Mfrs. Weight List No.	Order Code
230V ac, 50/60Hz	41/44W	155/155	54/54	159 x 168 x 82mm	1.3kg G2E108-AA01-50	101-1719
230V ac, 50/60Hz	80/100W	255/265	61/62	178 x 184 x 98mm	1.8kg G2E120-AR77-A6	101-1720
230V ac, 50/60Hz	240/280W	600/570	72/71	226 x 247.5 x 100mm	2.9kg G2E160-AD03-50	101-1721

416698

Mfrs. List No.	Order Code	1+	2+	5+
G2E108-AA01-50	101-1719	296.24	272.57	242.30
G2E120-AR77-A6	101-1720	327.29	301.15	267.69
G2E160-AD03-50	101-1721	628.28	578.12	513.90

Double Inlet Blowers - AC



- Dual inlet fans with an external rotor motor offering the advantage of matched motor and impeller in a compact space saving design
- Motor are IP44 rated, sealed for life, maintenance free, class B insulation, precision ball bearings and side mounted capacitor and terminal block
- Impeller is forward curved multi-vane type force fitted for vibration free operation and efficient cooling
- Heavy duty body made from galvanised steel
- May be mounted in any position

Voltage	Power Input	Air Flow	Noise	Dimensions (WxHxD)	Mfrs. Weight List No.	Order Code
230V ac, 50/60Hz	87/100W	435/410	58/57	162x165x146mm	1.5kg D2E097-BI56-50	101-1707
230V ac, 50/60Hz	87/190W	700/500	58/57	204x213x168mm	3.3kg D2E133-CI33-87	101-1708
230V ac, 50/60Hz	87/195W	810/600	56/57	204x213x232mm	4.4kg D2E133-DM27-D8	101-1709
230V ac, 50/60Hz	87/80W	540/510	54/57	171.5x180x215mm	2.6kg D4E133-AA01-57	101-1718
230V ac, 50/60Hz	87/270W	935/690	62/57	206x219x232mm	4.2kg D2E146-AP47-75	101-1710
230V ac, 50/60Hz	87/330W	970/690	68/57	206x219x232mm	4.2kg D2E146-AP47-75	101-1711
230V ac, 50/60Hz	87/245W	1250/1240	64/57	225x241x232mm	4.5kg D4E160-EG06-11	101-1712
230V ac, 50/60Hz	87/460W	2400/1900	66/57	295x333x255mm	11kg D4E180-BA02-25	101-1713
230V ac, 50/60Hz	87/420W	2260/2260	64/57	327x371x287mm	11.9kg D4E200-BA05-50	101-1714
230V ac, 50/60Hz	87/700W	2600/2600	67/57	327x370x287mm	12.1kg D4E225-BC01-36	101-1715
230V ac, 50/60Hz	87/1230W	3730/3220	75/57	387x392x298mm	16.3kg D4E250-BA01-12	101-1717

416686

Mfrs. List No.	Order Code	1+	2+	5+
D2E097-BI56-50	101-1707	310.14	279.64	248.55
D2E133-CI33-87	101-1708	424.39	381.94	339.50
D2E133-DM27-D8	101-1709	424.39	381.94	339.50
D4E133-AA01-57	101-1718	440.69	397.21	353.07
D2E146-AP43-62	101-1710	528.84	492.71	437.96
D2E146-AP47-75	101-1711	528.84	492.71	437.96

Mfrs. List No.	Order Code	1+	2+	5+
D4E160-EG06-11	101-1712	665.94	601.10	534.34
D4E180-BA02-25	101-1713	927.09	835.49	742.66
D4E200-BA05-50	101-1714	1,038.08	935.81	831.85
D4E225-BC01-36	101-1715	1,047.88	944.21	839.30
D4E250-BA01-12	101-1717	1,204.58	1,086.06	965.40

DC Compact Blower



- High level of reliability
- Precision ball bearing
- Brushless DC Motor
- Auto restart/reverse polarity protection
- Housing - Plastic (Black) UL94V-0 (except 5910PL series Aluminium (Black))
- Impeller - Plastic (Black) UL94V-0
- UL/CSA/VDE/CE approved
- RoHS Compliant



NEW

Dimensions H W D	Voltage V dc	Power Watts	Air Flow cu ft/min	Noise dBA@1m	Mfrs. List No.	Order Code
45 44 12	12	1.08	2.65	35	BM4515-04W-B30-L00	101-2796
45 44 12	12	2.28	3.5	43	BM4515-04W-B50-L00	101-2797
51 51 15	12	0.72	2.1	26	BM5115-04W-B30-L00	101-2798
51 51 15	12	2.16	3.5	42	BM5115-04W-B50-L00	101-2799
51 51 25	12	0.72	3.5	27	BM5125-04W-B30-L00	101-2801
51 51 25	12	2.88	6.7	43	BM5125-04W-B50-L00	101-2802
76 76 25	12	1.92	7.8	39	BG0702-B043-000-00	101-2803
76 76 25	12	3.00	9.5	43	BG0702-B045-000-00	101-2804
76 76 25	24	2.4	7.8	39	BG0702-B053-000-00	101-2805
76 76 25	24	3.36	9.5	43	BG0702-B055-000-00	101-2806
97 94 33	12	4.8	20.5	47.5	BG0903-B042-000-00	101-2807
97 94 33	12	12.4	28.6	54.5	BG0903-B044-000-00	101-2808
97 94 33	24	5.04	20.5	42.5	BG0903-B052-000-00	101-2810
97 94 33	24	11.8	28.6	52.5	BG0903-B054-000-00	101-2811
107 25 25	12	6.7	21.9	48	BG1002-B044-000-00	101-2813
120 120 32	12	11.16	33.2	54	BG1203-B045-000-00	101-2814
120 120 32	24	11.52	33.2	54	BG1203-B055-000-00	101-2815

416717

Dimensions H W D	Voltage Vdc	Order Code	1+	10+	25+	50+	+
45 44 12	12	101-2796	44.46	40.10	36.72	33.23	—
45 44 12	12	101-2797	44.46	40.10	36.72	33.23	—
51 51 15	12	101-2798	44.46	40.10	36.72	33.23	—
51 51 15	12	101-2799	44.46	40.10	36.72	33.23	—
51 51 25	12	101-2801	44.46	40.10	36.72	33.23	—
51 51 25	12	101-2802	44.46	40.10	36.72	33.23	—
76 76 25	12	101-2803	57.74	52.44	50.55	44.11	—
76 76 25	12	101-2804	57.74	52.44	50.55	44.11	—
76 76 25	24	101-2805	57.74	52.44	50.55	44.11	—
76 76 25	24	101-2806	57.74	52.44	50.55	44.11	—
97 94 33	12	101-2807	67.83	62.63	60.77	54.49	—
97 94 33	12	101-2808	67.83	62.63	60.77	54.49	—
97 94 33	24	101-2810	67.83	62.63	60.77	54.49	—
97 94 33	24	101-2811	67.83	62.63	60.77	54.49	—
107 25 25	12	101-2813	67.83	62.63	60.77	54.49	—
120 120 32	12	101-2814	90.72	85.67	81.77	76.69	—
120 120 32	24	101-2815	90.72	85.67	81.77	76.69	—

121mm 'Biscuit'



- Single piece diecast aluminium venturi with plastic impeller
- Termination via two 0.110" terminals
- Sleeve bearings
- Operating temperature: -10°C to 70°C
- 118-7526 and 118-7527 complete with thermal speed control



NEW

Voltage (V dc)	Power (Watts)	Airflow (CFM)	Noise (dBA)	Speed (RPM)	Dimensions (WxHxD)	Mfrs. List No.	Order Code
12	3.4	25	51.2	1575	121x121x31	BD12S3H	118-7526
24	11.0	25	51.2	3050	121x121x31	BD24S3H	118-7527
12	10.8	26	51.2	3040	121x121x31	BD12B3	118-7528
24	11.5	26	51.2	3100	121x121x31	BD24B3	118-7529

347090

Order Code	1+	5+	10+	25+
118-7526	112.31	101.39	93.12	90.91
118-7527	112.31	101.39	93.12	90.91
118-7528	78.04	68.53	62.94	61.43
118-7529	78.04	68.53	62.94	54.62

Prices are in Singapore Dollars and exclusive of GST.
Due to the volatile nature of certain products,
prices are subject to change without notice.

Windjammer

AC Blowers (Vacuum or Pressure)



- 120 or 240VAC electronically commutated blower with high flow fan system
- Blower offers a fan system that can be used for either vacuum or pressure
- Operating temperature 0-50°C
- The drive system has a rectifier/filter network, a commutation controller and an electronically commutated DC motor
- The drive system in the Bypass configuration has a cooling fan

- In the ThruFlow configuration, the drive motor is in the working air system
- Maximum pressure to 357mbar
- Maximum air flow to 145 L/sec
- Electrical and mechanical control versions
- Adjustable air performance
- Thermal protection/locked rotor protection
- Separation of cooling air and working air in bypass configuration
- Working air is the cooling air in the Thru-Flow configuration
- Compact size and long life
- UL component recognised
- CSA and TUV certified

Mfrs. List No.	Height	Outlet Tube	Type	Stage	VAC Max. Amps	Watts	Max. Pressure (mBar Sealed)	Open Flow L/Sec	Control Type	Order Code
Configuration: By Pass										
116634-53	152.4	31.75	B	Single	120 4	250	79	32	Mechanical	113-8977
116640-52	152.4	31.75	B	Single	120 4	250	79	32	Electrical	113-8978
116637-53	157.48	44.45	B	Single	120 4	250	67	54	Mechanical	113-8979
116636-53	182.88	44.45	B	Two	120 4.5	250	119	42	Mechanical	113-8980
116642-53	182.88	44.45	B	Two	120 4.5	250	119	42	Electrical	113-8981
116632-56	193.04	31.75	B	Three	120 4.5	250	188	23	Mechanical	113-8982
116638-58	193.04	31.75	B	Three	120 4.5	250	188	23	Electrical	113-8983
117634-51	152.4	31.75	E	Single	240 2.5	400	74	33	Mechanical	113-8985
117640-51	152.4	31.75	E	Single	240 2.5	400	74	33	Electrical	113-8986
117637-51	157.48	44.45	E	Single	240 2.5	400	62	54	Mechanical	113-8987
117643-52	157.48	44.45	E	Single	240 2.5	400	62	54	Electrical	113-8988
117636-51	185.42	44.45	E	Two	240 3	400	112	46	Mechanical	113-8989
117642-52	185.42	44.45	E	Two	240 3	400	112	46	Electrical	113-8990
117635-53	193.04	44.45	E	Three	240 3.5	400	151	41	Mechanical	113-8991
117641-51	193.04	44.45	E	Three	240 3.5	400	151	41	Electrical	113-8992
117632-52	195.58	31.75	E	Three	240 3.5	400	174	27	Mechanical	113-8994
117638-53	195.58	31.75	E	Three	240 3.5	400	174	27	Electrical	113-8995
117459-55	196.85	31.75	E	Four	240 4	400	212	60	Electrical	113-9014
119102-51	160.02	44.45	H	Single	120 7	800	109	76	Mechanical	113-8997
119101-51	160.02	44.45	H	Single	120 7	800	109	76	Electrical	113-8998
119104-51	187.96	44.45	H	Two	120 8	800	188	56	Mechanical	113-8999
119103-51	187.96	44.45	H	Two	120 8	800	188	56	Electrical	113-9000
117418-51	200.66	31.75	H	Three	120 9	800	285	32	Mechanical	113-9001
117417-51	200.66	31.75	H	Three	120 9	800	285	32	Electrical	113-9002
119152-52	160.02	44.45	K	Single	240 7.5	1200	134	90	Mechanical	113-9003
119151-51	160.02	44.45	K	Single	240 7.5	1200	134	90	Electrical	113-9004
119154-51	185.42	44.45	K	Two	240 9.5	1200	241	74	Mechanical	113-9005
119153-51	185.42	44.45	K	Two	240 9.5	1200	241	74	Electrical	113-9006
117416-51	198.12	31.75	K	Three	240 10	1200	357	39	Mechanical	113-9007
117415-51	198.12	31.75	K	Three	240 10	1200	357	39	Electrical	113-9008

Configuration: Thru Flow										
116629-53	106.68	31.75	A	Single	120 4	250	79	32	Electrical	113-9011
116630-56	127	31.75	A	Two	120 4.5	250	129	29	Electrical	113-9012
117629-52	106.68	31.75	D	Single	240 2.5	400	77	32	Electrical	113-9013

Mfrs. List No.	Order Code	1+	2+	5+
116634-53	113-8977	1,359.29	1,216.20	1,144.69
116640-52	113-8978	1,370.39	1,226.13	1,154.00
116637-53	113-8979	1,359.29	1,216.20	1,144.69
116636-53	113-8980	1,381.62	1,236.18	1,163.47
116642-53	113-8981	1,387.28	1,241.23	1,168.22
116632-56	113-8982	1,392.94	1,246.34	1,173.00
116638-58	113-8983	1,404.11	1,256.30	1,182.41
117634-51	113-8985	1,471.55	1,316.65	1,239.18
117640-51	113-8986	1,482.69	1,326.61	1,248.55
117637-51	113-8987	1,471.55	1,316.65	1,239.18
117643-52	113-8988	1,482.69	1,326.61	1,248.55
117636-51	113-8989	1,488.35	1,331.69	1,253.34
117642-52	113-8990	1,499.58	1,341.74	1,262.81
117635-53	113-8991	1,505.24	1,346.79	1,267.56
117641-51	113-8992	1,516.41	1,356.78	1,276.97
117632-52	113-8994	1,505.24	1,346.79	1,267.56
117638-53	113-8995	1,516.41	1,356.78	1,276.97
117459-55	113-9014	2,632.22	2,467.71	2,303.17
119102-51	113-8997	1,898.12	1,698.33	1,598.43
119101-51	113-8998	1,909.38	1,708.42	1,607.90
119104-51	113-8999	1,914.95	1,713.37	1,612.59
119103-51	113-9000	1,926.21	1,723.46	1,622.06
117418-51	113-9001	1,931.78	1,728.44	1,626.78
117417-51	113-9002	1,943.10	1,738.56	1,636.29
119152-52	113-9003	1,987.96	1,778.69	1,674.05
119151-51	113-9004	1,999.25	1,788.82	1,683.58
119154-51	113-9005	2,004.79	1,793.77	1,688.24
119153-51	113-9006	2,016.02	1,803.82	1,697.71
117416-51	113-9007	2,021.71	1,808.90	1,702.50
117415-51	113-9008	2,032.91	1,818.93	1,711.93
116629-53	113-9011	1,376.08	1,231.24	1,158.81
116630-56	113-9012	1,364.82	1,221.15	1,149.31
117629-52	113-9013	1,460.29	1,306.56	1,229.71

233682

Fan Speed Controllers


System 3000

Automatic Control for 12,24 and 48V dc Fans

ebmpapst



H=38, W=63, L=175
Mounting 4 x 3.5mm holes, 50 x 165 cntrs



The system 3000 is a comprehensive solution for the control and monitoring of PAPST DC fans, altogether providing a thermal management system for electronic equipment. It offers a modular approach enabling the monitor module to function as a separate monitoring unit or as a complete system integrated with the Control Module

Monitor Module

- Monitoring for upto 6 DC fans or blowers with open collector alarm outputs
- Alarm outputs for direct or remote fan status
- Individual fan alarm output
- Supports 12,24 or 48 Volt DC fans
- Several fan fail threshold settings available
- Easy to integrate and connect to equipment
- Operates as a stand-alone monitor or can be combined with System 3000 Control Module

Monitor Module


Input voltage	12 or 24 and 48Vdc $\pm 10\%$
Protection	Reverse Polarity and power limiting on 5V supply
Max power rating	50W direct module, connection and power leads can be connected externally if combined power ratings are greater than 50W
Operating temperature	0°C to +70°C
Humidity	40% to 80%
Outputs	Relay SPCO, 40Vdc/500mA for fan fail
Monitor Module	Open collector/20mA for fan status

Control Module

Input voltage	12, 24 or 48dc $\pm 10\%$
Protection	Reverse polarity and power limiting on 5V supply
Max power rating	65W
Min power rating	5W
Operating Temperature	0°C to +70°C
Humidity	40% to 80%
Outputs	40Vdc/500mA Relay SPCO for over temperature and thermistor fail open collector/20mA for over temperature, thermistor fail and standby mode

204355

Fan Voltage	Mfrs. List No.	Order Code	1+	5+	Price Per Pack	+	+
24 & 48V dc	S3000-M24-48	960-0574	145.71	138.42	132.85	--	--



In stock and ready to despatch,
300,000 products in our Asia, US
and Europe warehouses.

300,000 products at your fingertips

19

Fans

Compliant
Non-compliant
Limited stock - RoHS replacement available

RoHS



724 Fans



19

Fans